03/08/22 10·33 am	COUNSEL	KC/SC	SCS1919A-2

Senator moves to amend S.F. No. 1919 as follows:
Delete everything after the enacting clause and insert:
"Section 1. Minnesota Statutes 2020, section 103I.005, subdivision 17a, is amended to
read:
Subd. 17a. Temporary boring Submerged closed loop heat exchanger. "Temporary
boring" "Submerged closed loop heat exchanger" means an excavation that is 15 feet or
more in depth, is sealed within 72 hours of the time of construction, and is drilled, cored,
washed, driven, dug, jetted, or otherwise constructed to a heating and cooling system that
(1) conduct physical, chemical, or biological testing of groundwater, including
groundwater quality monitoring is installed in a water supply well;
(2) monitor or measure physical, chemical, radiological, or biological parameters of
earth materials or earth fluids, including hydraulic conductivity, bearing capacity, or
resistance utilizes the convective flow of groundwater as the primary medium of heat
exchange;
(3) measure groundwater levels, including use of a piezometer contained potable water
as the heat transfer fluid; and
(4) determine groundwater flow direction or velocity operates using nonconsumptive
recirculation.
A submerged closed loop heat exchanger also includes submersible pumps, a heat exchanger
device, piping, and other necessary appurtenances.
See 2 Minnesete Statutes 2020 section 1021 005 is amonded by adding a subdivision
Sec. 2. Minnesota Statutes 2020, section 103I.005, is amended by adding a subdivision
to read:
Subd. 17b. Temporary boring. "Temporary boring" means an excavation that is 15
feet or more in depth, is sealed within 72 hours of the time of construction, and is drilled,
cored, washed, driven, dug, jetted, or otherwise constructed to:
(1) conduct physical, chemical, or biological testing of groundwater, including
groundwater quality monitoring;
(2) monitor or measure physical, chemical, radiological, or biological parameters of
earth materials or earth fluids, including hydraulic conductivity, bearing capacity, or
resistance;
(3) measure groundwater levels, including use of a piezometer; and
(1) Browner Brown and resident and of a problement, and

Sec. 2. 1

02/00/22 10 22	COLDICET	T7 C /C C	0.0010101.0
03/08/22 10:33 am	COUNSEL	KC/SC	SCS1919A-2

2.1	(4) determine groundwater flow direction or velocity.
2.2	Sec. 3. Minnesota Statutes 2020, section 103I.005, subdivision 20a, is amended to read:
2.3	Subd. 20a. Water supply well. "Water supply well" means a well that is not a dewatering
2.4	well or environmental well and includes wells used:
2.5	(1) for potable water supply;
2.6	(2) for irrigation;
2.7	(3) for agricultural, commercial, or industrial water supply;
2.8	(4) for heating or cooling; and
2.9	(5) for containing a submerged closed loop heat exchanger; and
2.10	(6) for testing water yield for irrigation, commercial or industrial uses, residential supply,
2.11	or public water supply.
2.12	Sec. 4. [1031.631] INSTALLATION OF A SUBMERGED CLOSED LOOP HEAT
2.13	EXCHANGER.
2.14	Subdivision 1. Installation. Notwithstanding any other provision of law, the
2.15	commissioner must allow the installation of a submerged closed loop heat exchanger in a
2.16	water supply well. A project may consist of more than one water supply well on a particular
2.17	site.
2.18	Subd. 2. Setbacks. Water supply wells used only for the nonpotable purpose of providing
2.19	heating and cooling using a submerged closed-loop heat exchanger are exempt from isolation
2.20	distance requirements greater than 10 feet.
2.21	Subd. 3. Construction. The screened interval of a water supply well constructed to
2.22	contain a submerged closed-loop heat exchanger completed within a single aquifer may be
2.23	designed and constructed using any combination of screen, casing, leader, riser, sump, or
2.24	other piping combinations, so long as the screen configuration does not interconnect aquifers.
2.25	Subd. 4. Permits. A submerged closed loop heat exchanger is not subject to the permit
2.26	requirements in this chapter.
2.27	Subd. 5. Variances. A variance is not required to install or operate a submerged closed
2.28	loop heat exchanger."
2 20	Amend the title accordingly

Sec. 4. 2