to the there with the state of the state of

Ordinance No.17.

An Ordinance Annexing Certain Lots and Blocks to the Village of Cohasset,
Itaca, County, Minnesota.

The Village Council of the Village of Cohasset do Ordain as Follows:Section 1. That the following described Lots and Blocks of land,
towit: Out-Lots No. One and wwo; Lots 1, 2, 3, 4 and 5 of Block 1 and
all of Blocks 2, 3, 4, 5, 6, 7, 8, 9, 10 and 11 of couth Cohasset, according to the plat of South Cohasset, on file in the office of the
Register of meeds of Itasca sounty, State of Minnesota, be and the same
are hereby annexed to such village as effectually as if they had been
originally a part thereof.

This ordinance shall take effect and be in force from and after its passage and publication.

Adopted and passed this 2nd day of March, A. D. 1911.

Attest; M. M. Jouls Recorder.

President of the Jouncil

State of minnesota

ន ន

County of Itasca

I, M. H. Jones, Pecorder of the Village of Cohasset, county of Itasca, State of Minnesota, do hereby certify that the foregoing is a true and correct copy of the original Ordinance No. 17, duly passed and published, according to law.

Subscribed and Sworn to Before Me this day of March, 1911.

Recorder.

HOUlights hotary Public

my commesson uppins Septias Ling

また ないので Nove 1

京西事 地名美国比尔米

記事 大学 ないない

5 J 2 4 J

1...

\$... ***

少妻は 事以皇 一年山大東

(1) 10 mm (1)

7

ではなるで

大 関節になるとなると

不是一个人,就是一个人,也是

日本のできるとはなり、 100mm 100

STATE OF MINNESOTA, DEPT OF STATE

Filed in the office of Sperctury
of State it is good 11 1011 day
Theres (b. Islanda)

Secretary of Sivile.

SPECIIFICATIONS.

For monument to be erected on the site provided by the commission on the Woodlake Battlefield ground, Yellow Medicine County, Minn.

The contractors to provide for the transportation of all materials to this site, to assume all risk, damage to persons or property, to be responsible for the good quality of the material used and labor performed, to thoroughly cleanse the monument after it is set and leave the same in a good condition, and to remove all debris and appliances and unused materials, leaving the site free of obstructions that are not a part of the completed monument.

GUARANTEE.

The contractors hereby guarantee the completed monument to be of the best material according to the samples submitted, and the workmanship shall be so done both in the foundation and superstructure, that for a term of ten years should any defect develop in either granite or workmanship, such as the leaning of the monument, the opening of joints, cracking of the stone etc., such defect is to be remedied by the contractors at their own expense.

FOUNDATION.

Shall be built of masonry, if possible, or concrete composed of three parts crushed stone or coarse gravel, two parts fine, sharp sand, and one part cement thoroughly mixed dry and enough water added to moisten, to be shovelled into the hole in small quantities and thoroughly rammed. The top to be perfectly level so that the monument will stand thereon without spawling or artificially levelling up. The foundation to be the same size as the bottom base of the monument on the square and six feet deep or deeper, should it be necessary to make a perfectly secure and adequate foundation to permanently and safely carry the superstructure. The said foundation to be completed not less than thirty days before the granite is set thereon, in order to insure a sufficient hardening of the mass and prevent its cracking or giving.

GRANITE.

The entire monument is to be made of fine quality
Minnesota granite, according to sample submitted. Rockville
granite to be used for all, except the diewwhich is to be
of St. Cloud red granite.

WORKMANSHIP.

The entire work throughout shall be cut according The bottom bed of the bottom base shall be pointed off level with a full bearing all around on the foundation. All sections on the first, second, and third bases are to be securely anchored together with heavy bronze anchors, laid in deep channel and cemented; the space between to be filled flush with the top joint with a concrete composed of crushed gravel, sand and cement. The cement to be used in this concrete to be the best quality non-staining cement. All joints to be thoroughly calked with a composition of the same materials, mixed in a proportion of two to one, in small batches so that it may be used before the initial set has begun. The surface of the stone to be kept wet during the pointing in order to leave the clean, fine joint when completed. The guns and wreath on shaft to be carved in the granite in high relief and in an artistic manner. All letters to be raised and polished on the face and to be according to that decided upon hereafter as appropriate and satisfactory to both the commission and the contractors.

SIZES.

Design No. 1 is selected; the general dimensions being $7'-6" \times 7'-6"$ at the base and 30'-0" high from the ground to the top of the shaft.

COMPLETION.

The work to be set under the superintendency of a competent man in the employ of the contractor, and to be completed on or before the 15th day of September, 1910, unless delayed by strikes or accidents beyond the control of the contractor, in which event a sufficient length of time shall be granted to complete the contract without unusual expense.

CONTRACT.

This agreement made this 23rd day of June, 1910, between the Twin City Granite Works, St. Paul, Minn., herein before designated as the contractor, and L. W. Collins, E. T. Champlin, and Mathias Holl, constituting Woodlake Battlefield Commission, herein after designated as the owner; witnesseth that said contractors hereby agree to build and set complete upon the site provided by the owners, on or before September 15, 1910, one