This document is made available electronically by the Minnesota Legislative Reference Library as part of an ongoing digital archiving project. http://www.leg.state.mn.us/lrl/lrl.asp WEST **SEGMENT EAST SEGMENT**  Target Field Station Golden Valley **Royalston Station** Van White Station Penn Station 21st Street Station St. Louis Park Minneapolis **Beltline Station** West Lake Station Wooddale Station Louisiana Station Hopkins Blake Station Downtown Hopkins Station Shady Oak Station Edina Minnetonka Glen Lake **Opus Station** City West Station Eden Prairie Golden Triangle Station

**Eden Prairie Town** 

Center Station





# WEST-VOLUME 3 (SYSTEMS)

PRELIMINARY ENGINEERING (SEPTEMBER 2014)

## INDEX

#### **GENERAL DRAWINGS**

COVER SHEET & INDEX OF DRAWINGS

ABBREVIATIONS

LEGEND, SYMBOLS AND GENERAL NOTES

#### PLAN SHEET LAYOUTS

SHEET LAYOUT INDEX SEGMENT W1A 10 - 18 19 - 34 SEGMENT W1 SEGMENT W2

55 - 71 SEGMENT W3 72 - 74 SEGMENT OME

## SYSTEMWIDE ELECTRICAL

75 - 79 **DETAILS & TECHNICAL SHEETS** 

#### TRACTION POWER SYSTEM

SYMBOLS, LEGEND AND GENERAL NOTES SECTIONALIZING DIAGRAM 81 - 89 SUBSTATION DETAILS 90 - 101 SUBSTATION SITE PLANS

#### **OVERHEAD CONTACT SYSTEM**

SYMBOLS, LEGEND, AND GENERAL NOTES

TYPICAL ARRANGEMENTS AND ASSEMBLIES MASTER OVERLAP CHART 127 - 131

## SIGNAL SYSTEM

SYMBOLS, LEGEND AND GENERAL NOTES SYMBOLS & LEGEND ROUTE & ASPECT CONTROL LINE DIAGRAM ROUTE AND ASPECT CONTROL LINES TYPICAL ROUTE AND LOCKING TABLE TYPICAL SIGNAL EQUIPMENT DETAILS

158 - 167 GRADE CROSSING ARRANGEMENT & DETAILS PED CROSSING ARRANGMENT & DETAILS

SWITCH HEATER ARRANGMENT & DETAILS SWITCH MACHINE DETAILS 177 - 179

SIGNAL HOUSE DETAIL 180 - 181 TYPICAL CABLE PLANS 182 - 185

#### COMMUNICATIONS SYSTEM


SYMBOLS, LEGEND AND GENERAL NOTES SYSTEM WIDE BLOCK DIAGRAMS SINGLE LINE DIAGRAMS NETWORK AND CABLE PLAN 198 -201


TUNNEL SYSTEM

**AECOM** 

Mitchell Station

Southwest Station





:	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	
-		•					
2							
20							
ŧ							
20							
2		•					
, 7							
, Inc							

PRELIMINARY ENGINEERING





WEST-VOLUME 3 (SYSTEMS)			
GENERAL	2		
SEGMENT KEY MAP	OF		


202

SYS-GEN-KEY SYSTEMS

```
CONTINUED
                                                                                             F CONTINUED
                                                                                                                                                                                          P CONTINUED
<u>A</u>
                                                                                                                                                                                                                                             CONTINUED
                                                                                                                                                                                                                                                SINGLE WIRE AUTO TENSION
SINGLE WIRE FIXED TERMINATION
                                                                                                                                           LA
LB
LB/FT
                                                                                                                                                                                          PED
                                                                                                                                                                                                  PEDESTRIAN
                                                                                                                                                                                                                                         SWAT
        AMPERE
                                              CLF
                                                                                             FS
                                                       CHAIN LINK FENCE
                                                                                                                                                                                          ΡF
ΔR
        ANCHOR BOLT
                                                       CLEARANCE, CLEAR
                                                                                                     FEET, FOOT
                                                                                                                                                                                                  POINT OF FROG
                                                                                                                                                   POUNDS PER FOOT
                                                                                                                                                                                                                                         SWH
                                                                                                                                                                                                                                                 SWITCH HEATER
                                                                                                                                                                                                  PEDESTRIAN FLASHER
        ABANDON, ABANDONED
ARD
                                               COMM
                                                      COMMUNICATIONS
                                                                                             F TO
                                                                                                    FACE TO FACE
                                                                                                                                                                                                                                                SWITCH HEATER CABINET
                                                                                                                                           LC
LF
                                                                                                                                                   LINE CURRENT
                                                                                                                                                                                                  PVC COATED GRSC
ARUT
        ARUTMENT
                                                                                                     FIXED TERMINATION (FT)
                                               COMPT
                                                       COMPARTMENT
                                                                                                                                                                                                                                         SWHT
                                                                                                                                                                                                                                                SWITCH HEATER TRANSFORMER
                                                                                                                                                   LINEAR FEET
ARV
        ABOVE
                                               CONC
                                                       CONCRETE
                                                                                             FTG
                                                                                                     FOOTING
                                                                                                                                           LED
                                                                                                                                                                                                                                         S/E
                                                                                                                                                   LIGHT EMITTING DIODE
                                                                                                                                                                                                                                                SUPERELEVATION
                                                                                                                                                                                                  POINT OF INTERSECTION
        ALTERNATING CURRENT
                                               COND
                                                       CONDUCTOR
                                                                                             <u>G</u>
                                                                                                                                                    LONG, LENGTH
                                                                                                                                           LG
LTG
                                                                                                                                                                                                  POINT OF INTERSECTION OF TURNOUT
                                                                                                                                                                                          PITO
        AMERICAN CONCRETE INSTITUTE ALUMINUM CONDUCTOR, STEEL
ACI
                                               CONST
                                                       CONSTRUCTION
                                                                                                                                                   LIGHTING
                                                       CONTINUATION, CONTINUOUS
ACSR
                                                                                             GALV
                                                                                                     GALVANIZED
                                                                                                                                                                                                  PLATE
                                                                                                                                           LOC
                                                                                                                                                   LOCATION
                                                                                                                                                                                                  PROPERTY LINE
        REINFORCED
                                                       CONTRACTOR
                                                                                             GB
G/L
                                                                                                     GROUND BUS
                                                                                                                                                                                                                                                 TAP BOX, TERMINAL BLOCK
                                                                                                                                                                                                                                         TB
                                                                                                                                           LPT
                                                                                                                                                   LOW POINT
                                                                                                                                                                                          PLAT
                                                                                                                                                                                                  PLATFORM
        ADJACENT
                                                       CONDUIT
                                                                                                     GROUND LINE
                                                                                                                                                   LIGHT RAIL TRANSIT
LUMP SUM/LINE SECTION/LINE
                                                                                                                                                                                                                                         TBD
                                                                                                                                                                                                                                                 TO BE DETERMINED
                                                                                                                                           LRT
                                              CR
CT
                                                                                                                                                                                          POS
                                                                                                                                                                                                  POSITIVE
        AUDIO FREQUENCY
                                                       CONDUIT RISER
                                                                                             GND
                                                                                                     GROUND
                                                                                                                                                                                                                                                 TO BE REMOVED
                                                                                                                                                                                                                                         TBR
                                                                                                                                           LS
                                                                                                                                                                                          PRF-C
                                                                                                                                                                                                  PRF-CAST CONCRETE
        AUDIO FREQUENCY OVERLAY
                                                       CURRENT TRANSFORMER
                                                                                             GRD
                                                                                                     GROUNDING DEVICE
                                                                                                                                                                                                                                         ΤE
                                                                                                                                                                                                                                                 TRACTION ELECTRIFICATION
                                                                                                                                                    SEGMENT
                                                                                                                                                                                          PROP
                                                                                                                                                                                                  PROPOSED
                                               CS
        AT GRADE
                                                       CURVE-TO-SPIRAL
                                                                                             GRS
                                                                                                     GALVANIZED RIGID STEEL
                                                                                                                                                                                                                                         TEL
                                                                                                                                                                                                                                                 TELEPHONE
                                                                                                                                           LT
                                                                                                                                                   LIGHT OR LEFT
                                                                                                                                                                                          PS
                                                                                                                                                                                                  POINT OF SWITCH
                                              CSO
        AHFAD
                                                       CONDUIT STUB OUT
                                                                                             GRSC
                                                                                                     GALVANIZED RIGID STEEL CONDUIT
                                                                                                                                                                                                                                                 TEMPERATURE
                                                                                                                                                                                                                                         TFMF
                                                                                                                                           LTS
                                                                                                                                                                                                  POUNDS PER SQUARE FEET
                                                                                                                                                                                          PSF
AISC
        AMERICAN INSTITUTE OF STEEL
                                              CSU
                                                       CONDUIT STUB UP
                                                                                             GC
                                                                                                     GRADE CROSSING
                                                                                                                                                                                                                                                 TEMPORARY
                                                                                                                                                                                                                                         TEM
                                                                                                                                           LV
                                                                                                                                                   LOW VOLTAGE
                                                                                                                                                                                                  POLINDS PER SQUARE INCH
        CONSTRUCTION
                                              CT
                                                                                             GTE
                                                                                                                                                                                          PSI
                                                       CONDUIT TIES
                                                                                                     GENERAL TELEPHONE ELECTRIC
                                                                                                                                                                                                                                                 TERMINAL, TERMINATION
                                                                                                                                                                                                                                         TERM
                                                                                                                                                                                                  POINT OF TANGENT
                                                                                                                                           <u>M</u>
        ALUMINUM
                                              CTR
                                                       CENTER
                                                                                                                                                                                                                                                 AXEL COUNTER
                                                                                                                                                                                                  POCKET TRACK
        APPROACH
                                              CU
                                                       COPPER
                                                                                                                                                                                                                                         THK
T/F
T/G
                                                                                                                                                    METER (DISTANCE)
                                                                                                                                                                                          PUC
                                                                                                                                                                                                  PUBLIC UTILITY COMMISSION
APPROX APPROXIMATE
                                                       CONTACT WIRE
                                                                                             HD
                                                                                                     HARD DRAWN
                                                                                                                                                                                                                                                 TOP OF FOUNDATION
                                                                                                                                                   MAXIMUM
                                                                                                                                                                                                  POLYVINYL CHLORIDE COUNDUIT (PVCC) OR POINT OF VERTICAL
                                                                                                                                                                                          PVC
        AUXILIARY POWER TRANSFORMER
                                              CY
                                                       CUBIC YARD
                                                                                             HDG
                                                                                                     HOT DIPPED GALVANIZED AFTER
                                                                                                                                                                                                                                                 TOP OF GROUND LINE
                                                                                                                                            M/W
                                                                                                                                                    MESSENGER WIRE
       AMERICAN RAILWAY ENGINEERING &
AREMA
                                                                                                     FABRICATION
                                                                                                                                                                                                                                                 TENSION LENGTH OR TRACK LIGHTING
                                                                                                                                                                                                                                         TL
T/LR
                                                                                                                                            MC
                                                                                                                                                    MOTOR CONTROL
        MAINTENANCE OF WAY ASSOCIATION
                                                                                                     HIGH DENSITY POLYETHYLENE
                                              \overline{D}
                                                                                                                                                                                                                                                 TOP OF LOW RAIL
                                                                                                                                                                                          PWR
                                                                                                                                           MCM
                                                                                                                                                   THOUSAND CIRCULAR MILS
        (FORMERLY AREA)
                                                                                             HEX
                                                                                                     HEXAGONAL
                                                                                                                                                                                                  PEDESTRIAN CROSSING
                                                                                                                                                                                                                                         TO
                                                                                                                                                                                                                                                 TURNOUT
                                                                                                                                                                                          PΧ
                                                                                                                                                   MILLIHENRY
                                                                                                     HANDHOLE
HIAWATHA LRT (HLRT)
                                                                                                                                            mH
        AMMETER SWITCH
                                              D
                                                                                                                                                                                                                                         TOC
TOLR
                                                                                             НН
                                                                                                                                                                                                                                                 TOP OF CONCRETE
                                                                                                                                           МН
                                                                                                                                                   MANHOLF
                                                                                                                                                                                          Q
                                                                                                                                                                                                                                                 TOP OF LOW RAIL
ASSY
        ASSEMBLY
                                                       DIRECT BURIAL
                                                                                             HIA
                                                                                                                                            MIN
                                                                                                                                                   MINIMUM
ASTM
        AMERICAN SOCIETY OF TESTING &
                                                       DIRECT CURRECT
                                                                                             HID
                                                                                                     HIGH INTENSITY DISCHARGE
                                                                                                                                                                                                                                                 TOP OF RAIL
                                                                                                                                                                                                                                         TOR
                                                                                                                                                                                          QTY
                                                                                                                                                                                                  QUANTITY
                                                                                                                                           MISC
M/L
                                                                                                                                                   MISCELLANEOUS
        MATERIALS
AUTO TENSION ( A.T.)
                                                                                             НΟ
                                                                                                     HAND OPERATED
                                                                                                                                                                                                                                         TORW
                                                                                                                                                                                                                                                 TOP OF RETAINING WALL
                                                                                                                                                   MAIN LINE
                                                                                                                                                                                          \mathbb{R}
                                                       DIRECT FIXATION
                                                                                             HORIZ
                                                                                                     HORIZONTAL
                                                                                                                                                                                                                                                 TRACTION POWER
                                                                                                                                           MNDO
                                                                                                                                                   MINNESOTA DEPARTMENT OF
        ALONG TRACK MOVEMENT
                                              DTL
                                                                                             HPS
                                                                                                                                                                                                                                         TPSS
ATM
                                                      DFTAIL
                                                                                                     HIGH PRESSURE SODUIM
                                                                                                                                                                                                                                                 TRACTION POWER SUBSTATION
                                                                                                                                                                                                  RADIUS
                                                                                                                                                    TRANSPORTATION
        ABOVE TOP OF RAIL
ATR
                                              DGA
                                                       DOWN GUY ANCHOR
                                                                                             HRL
                                                                                                                                                                                                                                                 TRACTION POWER CONTROLLER
                                                                                                     HIGH RAIL LEVEL
                                                                                                                                                                                                                                         TPT
                                                                                                                                                                                                  RAIL ACCESS BOX
                                                                                                                                            MOP
                                                                                                                                                    MOTOR OPERATED
                                                                                                                                                                                          RAR
                                                       DIAMETER, Ø
        AUTOMATIC TRAIN STOP
ATS
                                              DIA
                                                                                             H-SPAN HEAD SPAN
                                                                                                                                                                                                                                         TRAC
                                                                                                                                                                                                                                                 TRACTION
                                                                                                                                                                                                  RUNNING EDGE OF RAIL
                                                                                                                                                    MILE POST - MORE PERMISSIVE SPEED
                                                                                                                                                                                          RF
                                                       DIMENSION ( DIM)
AVG
        AVERAGE
                                               DIM
                                                                                             HS
                                                                                                     HANDHOLF SIGNAL
                                                                                                                                                                                                                                         TRANSF TRANSFORMER, TRANSFER
                                                                                                                                            MPA
                                                                                                                                                   MID POINT ANCHOR
                                                                                                                                                                                          RFC1
                                                                                                                                                                                                  RECTIFIER
        AMERICAN WIRE GAUGE
                                                      DISCONNECT
AWG
                                              DISC
                                                                                             HSS
                                                                                                     HIGH STRENGTH STEEL
                                                                                                                                                                                                                                         TRK
                                                                                                                                                                                                                                                 TRACK
                                                                                                                                                                                          RFF
                                                                                                                                            MPH
                                                                                                                                                   MILES PER HOUR
AWS
        AMERICAN WELDING SOCIETY
                                               DISC
                                                   SW DISCONNECT SWITCH
                                                                                                     HEIGHT
                                                                                                                                                                                                   REVISE/REVISION
                                                                                                                                                                                                                                                 TANGENT TO SPIRAL
                                                                                                                                                                                                                                         TS
                                                                                                                                                                                          REV
                                                                                                                                            MS
                                                                                                                                                   MANHOLE SIGNAL
                                                                                             HTR
                                                                                                     HEATER
                                              DIST
                                                      DISTRIBUTION
<u>B</u>
                                                                                                                                                                                                                                         TTC
                                                                                                                                                                                                                                                 TELEPHONE TERMINAL CABINET
                                                                                                                                                                                          REOD
                                                                                                                                                                                                  REQUIRED
                                                                                                                                           MTG
                                                                                                                                                   MOUNTING
                                                                                                     HIGH VOLTAGE
                                              DI GI
                                                      DOME LIGHT
                                                                                             ΗV
                                                                                                                                                                                                                                         TVM
                                                                                                                                                                                                                                                 TICKET VENDING MACHINE
                                                                                                                                                                                          RPZ
                                                                                                                                                                                                  RUNWAY PROTECTION ZONE
                                                                                                                                           MT
                                                                                                                                                    METRO TRANSIT
RK
                                                                                                     HEATING VENTILATION AIR
        RACK
                                                       DEGREE OF CURVATURE
                                              DOC
                                                                                             HVAC
                                                                                                                                                                                                                                         TWA
                                                                                                                                                                                                                                                 TIF WIRE ANCHOR
                                                                                                                                           MVA
                                                                                                                                                   MEGAVOLT AMPERE
RARR
        BARRIER
                                              DS
                                                       DOOR SWITCH
                                                                                                     CONDITIONING
                                                                                                                                                                                                  REMOTE TERMINAL UNIT
                                                                                                                                                                                                                                         TWC
                                                                                                                                                                                                                                                 TRAIN-TO-WAYSIDE
                                                                                                                                                                                          RTU
                                                                                                                                                   MILLIVOLT
                                                                                                                                            m۷
        BATTERY
                                              DWG
                                                      DRAWING
                                                                                             HWY
                                                                                                     HIGHWAY
                                                                                                                                                                                                                                                 COMMUNICATIONS, TWC LOOP
                                                                                                                                                                                          RR
                                                                                                                                                                                                  RAII ROAD
                                                                                                                                           MW
                                                                                                                                                   MEGAWATT
        BACK TO BACK
                                                                                             Hz
                                                                                                     HERTZ
                                              <u>E</u>
                                                                                                                                                                                                                                         TYP
                                                                                                                                                                                                                                                 TYPICAL
                                                                                                                                                                                          RRX
                                                                                                                                                                                                  RAILROAD GRADE CROSSING
                                                                                                                                            MW
                                                                                                                                                    MESSENGER WIRE
\mathsf{BC}
        BOLT CIRCLE/BATTERY CHARGER
                                                                                                                                           N
                                                                                                                                                                                          RW
                                                                                                                                                                                                  RETAINING WALL
        BY-PASS FEEDER ANCHOR
                                                                                                                                                                                          ROW
                                                                                                                                                                                                  RIGHT OF WAY
        BASIC INSULATION LEVEL
                                              ΕA
                                                       EACH
                                                                                                     INTERLOCK
                                                                                                                                                                                                                                                UNDERGRADE, UNDERGROUND
                                                                                                                                                    NORTH, NEUTRAL
                                                                                                                                                                                                                                         UG
UGB
                                                                                                                                           N
N/A
                                                                                                                                                                                          <u>S</u>
                                              EΒ
                                                       EASTBOUND
        BREAKER
                                                                                             ΙB
                                                                                                     IMPEDANCE BONDS
                                                                                                                                                                                                                                                UNDERGRADE BRIDGE
                                                                                                                                                   NOT APPLICABLE
                                                                                                                                                                                                                                        U/S
UTIL
                                              Ea
BLDG
        BUILDING
                                                       SUPERELEVATION IN INCHES
                                                                                                     INSTRUMENT CASE
                                                                                                                                                                                                                                                 UNDERSIDE
                                                                                                                                           NB
                                                                                                                                                    NORTH BOUND
                                                                                                                                                                                                  SOUTH
        BASELINE
                                              EHS
                                                       EXTRA HIGH STRENGTH
                                                                                             ID
                                                                                                     INSIDE DIAMETER
                                                                                                                                                                                                                                                UTILITY ( UTIL)
                                                                                                                                           NBR
                                                                                                                                                   NON-BRIDGING
                                                                                                                                                                                                  SURGE ARRESTER
        BOTTOM OF BASEPLATE
                                              ELEC
                                                       ELECTRICAL
                                                                                             IEEE
                                                                                                     INSTITUTE OF ELECTRICAL AND
                                                                                                                                           NC
                                                                                                                                                    NORMALLY CLOSED
                                                                                                                                                                                                  SUBSTATION ALARM PANEL
        BOTTOM OF STEEL
                                              ELEV
                                                      ELEVATION
                                                                                                     ELECTRONIC ENGINEERS
BOS
                                                                                                                                            NEC
NEG
                                                                                                                                                   NATIONAL ELECTRICAL CODE
                                                                                                                                                                                                  SOUTHBOUND OR SPLICE BOX
                                                                                                                                                                                          SB
ВМ
                                                       ELECTROMAGNETIC INTERFERENCE
                                                                                                                                                                                                                                         V
        BFAM
                                                                                                     LINE CURRENT
                                                                                                                                                                                                                                                 VOL T
                                                                                                                                                                                                  SIGNAL/COMMUNICATION
                                              EPR
                                                      ETHYLENE PROPYLENE RUBBER
                                                                                            ĬĴ
                                                                                                                                                                                                                                                 VOLT AMPS
BR
        BRIDGE
                                                                                                     INSULATED JOINT
                                                                                                                                                                                                                                         VA
                                                                                                                                            NESC
                                                                                                                                                   NATIONAL ELECTRICAL SAFETY CODE
                                                                                                                                                                                                  SUPERVISORY CONTROL AND DATA
BRKT
        BRACKET
                                                       FOLIAL
                                                                                                     INCH. INCHES
                                                                                                                                                                                                                                                 VERTICAL
                                                                                             INI
                                                                                                                                           NIC
                                                                                                                                                   NOT IN CONTRACT
                                              EQN
                                                      EQUATION
        BAR SIGNAL FOUNDATION
BSF
                                                                                             INC
                                                                                                     INCOMING
                                                                                                                                                                                                                                                 VERSINE
                                                                                                                                                   NORMALLY OPEN
                                                                                                                                           NO
                                                                                                                                                                                                  SIMPLE CATENARY AUTO TENSION
                                                       EQUIPMENT ( EQUIP)
                                              EQP
                                                                                                     INCLUDE. INCLUDING
                                                                                                                                                                                                                                                 VOLTMETER SWITCH
B-SPAN BODY SPAN
                                                                                             INCL
                                                                                                                                                                                                                                         VS
                                                                                                                                                   NUMBER
                                                                                                                                           No.
                                                                                                                                                                                                  SIMPLE CATENARY FIXED TERMINATION
                                                                                                                                                                                          SCFT
                                                       EXTRA STRENGTH
                                              ES
BTM
        BOTTOM
                                                                                             INSUL
                                                                                                     INSULATION
                                                                                                                                                                                                                                         <u>W</u>
                                                                                                                                            NOM
                                                                                                                                                   NOMINAL
                                                                                                                                                                                          SECT
                                                                                                                                                                                                  SECTION
                                                                                                    INTERFACE PHASE TRANSFORMER IN RUNNING (RIDING CONTACT WIRE)
        BETWEEN
                                              FT
                                                       ELEMENT OF TES DEVICES
                                                                                             IPT
I/R
                                                                                                                                           NR
                                                                                                                                                    NOT REGISTERED
                                                                                                                                                                                          SI
                                                                                                                                                                                                  SECTION INSULATOR
                                                                                                                                                                                                                                                 WATT, WIDTH OR WIRE
                                              ETC
                                                      FT CETERA
                                                                                                                                                                                                                                         W
        BALANCE WEIGHT
                                                                                                                                                    NEGATIVE RETURN
                                                       EMERGENCY TRIP STATION
                                                                                                                                                                                          SIG
                                                                                                                                                                                                  SIGNAL
                                                                                                                                                                                                                                         W/
BWA
        BALANCE WEIGHT ANCHOR
                                              ETS
                                                                                                                                                                                                                                                 WITH
                                                                                                                                            NS
                                                                                                                                                    NEAR SIDE
                                                                                                                                                                                                  SET OUT POINT
                                                                                                                                                                                          SOF
                                              EXIS:
                                                      EXISTING
                                                                                                                                                                                                                                         WB
                                                                                                                                                                                                                                                 WESTBOUND
ΒZ
        BRONZE
                                                                                                                                            NS
                                                                                                                                                    NOT SUPPORTED
                                                                                                                                                                                          SD
                                                                                                                                                                                                  SURGE PROTECTION
                                              FXF
                                                       EXPANSION
                                                                                                                                                                                                                                        WI
W/O
                                                                                                                                                                                                                                                 WEIGHT - WROUGHT IRON
                                                                                                                                            NSR
                                                                                                                                                   NOT SUPPORTED OR REGISTERED
                                                                                                                                                                                          SPEC
                                                                                                                                                                                                  SPECIFICATION
                                              EXT
                                                      EXTERNAL
                                                                                             JΒ
                                                                                                     JUNCTION BOX
                                                                                                                                                                                                                                                 WITHOUT
                                                                                                                                            NTS
                                                                                                                                                   NOT TO SCALE
                                                                                                                                                                                          SPS
                                                                                                                                                                                                  SMALL PART STEELWORK
                                                                                             JCT
        CELSIUS
                                                                                                     JUNCTION
                                                                                                                                                                                                                                                 WIDE FLANGE
                                              E
                                                                                                                                           0
                                                                                                                                                                                          SPST
                                                                                                                                                                                                  SINGLE POLE SINGLE THROW
                                                                                                                                                                                                                                         WWF
                                                                                                                                                                                                                                                 WELDED WIRE FABRIC
CAR
        CABINET
                                                                                                     (2) JUMPERS
                                                                                                                                                                                          SQ
                                                                                                                                                                                                  SQUARE
                                                                                                                                           OC
OCS
OD
                                                                                             ĴΤ
CANT
        CANTILEVER
                                                       FAHRENHEIT
                                                                                                     JUNCTION BOX TIES
                                                                                                                                                    ON CENTER
                                                                                                                                                                                                                                         X
                                                                                                                                                                                                  SQUARE FEET
                                                                                                                                                                                          Sq Ft
        CATENARY (CAT.)
CAT
                                              FΑ
                                                       FIXED ANCHOR
                                                                                                                                                   OVERHEAD CONTACT SYSTEM
                                                                                             <u>K</u>
                                                                                                                                                                                          Sq In
                                                                                                                                                                                                  SQUARE INCHES
                                              FAC
        CIRCUIT BRÈAKEŔ
                                                                                                                                                                                                                                         ΧB
                                                                                                                                                                                                                                                 CROSS BOND.
CB
                                                       FACILITY
                                                                                                                                                    OUTSIDE DIAMETER
                                                                                                                                                                                          S-SPAN STEADY SPAN
        CENTRAL CORRIDOR LRT
                                                       FOUNDATION
                                                                                                                                                                                                                                                 TRANSFORMER
CCLR1
                                              FDN
                                                                                                                                           \mathsf{OH}
                                                                                                                                                                                                                                         XFMR
                                                                                                                                                   OVERHEAD
                                                                                                                                                                                                  STAINLESS STEEL
SPIRAL TO TANGENT, STREET
                                                                                                                                                                                          SST
        CLOSED CIRCUIT TELEVISION
                                              FDR
                                                                                                                                                                                                                                                CROSSING
                                                       FFFDFR
                                                                                                                                           OHB
O/L
CCTV
                                                                                                     THOUSAND CIRCULAR MILS
                                                                                                                                                   OVERHEAD BRIDGE
                                                                                                                                                                                                                                         X-ING
                                                                                             KCMII
                                                       FOUNDATION TRAFFIC
                                                                                                                                                   OVERLAP
OUT OF RUNNING (NON-RIDING
CONTACT WIRE)
                                                                                                                                                                                          ST
STA
                                                                                                                                                                                                                                         XOVER
                                                                                                                                                                                                                                                CROSSOVER
        CLIRIC FEET
                                                                                                     KII OAMPERE
                                                                                                                                                                                                  STATION, STATIONING
                                              FFJ
                                                                                                                                           O/R
                                                       FULL FEEDING JUMPER
                                                                                                                                                                                                                                                CROSS PASSAGE
CHAM
        CHAMFER
                                                                                                                                                                                                                                         XPASS
                                                                                             ΚN
                                                                                                     KNUCKLE
                                                                                                                                                                                                  STANDARD
                                                                                                                                                                                          STD
                                                       FEEDER JUMPER
                                                                                                                                                                                                                                         X-SECT CROSS SECTION
CHGR
        CHARGER
                                              FJ
                                                                                                                                           <u>P</u>
                                                                                             k۷
                                                                                                     KILOVOL1
                                                                                                                                                                                          STRUCT
                                                                                                                                                                                                  STRUCTURE
                                              FΜ
CIP
        CAST-IN-PLACE
                                                       FRICTION MODIFIER
                                                                                                                                                                                                                                         X-SPAN CROSS SPAN
                                                                                             kVA
                                                                                                     KILOVOLT AMPERE
                                                                                                                                                                                          SU
                                                                                                                                                                                                  STUB-UP
                                                                                                                                           PAN
                                                                                                                                                   PANTOGRAPH
CKT
        CIRCUIT
                                              FOF
                                                       FACE OF POLE
                                                                                             KSF
                                                                                                     KIPS PER SQUARE FOOT
                                                                                                                                           РΒ
                                                                                                                                                                                          SUSP
                                                                                                                                                                                                  SUSPENDED
        CENTERLINE
                                              FOS
                                                       FACTOR OF SAFETY
                                                                                                                                                   PULLBOX
                                                                                                     KIPS PER SQUARE INCH
                                                                                             KSI
                                                                                                                                           PC
PD
PE
                                                                                                                                                                                          SW
                                                                                                                                                                                                  SWITCH
  TO & CENTERLINE TO CENTERLINE
                                                                                                                                                    POINT OF CURVE
                                                       FEEDER POLE
                                                                                                                                                                                                                                                 YARD
                                                                                             kW
                                                                                                     KII OWATT
                                                                                                                                                                                                  SINGLE WIRE ANCHOR
                                                                                                                                                                                          SWA
                                                                                                                                                   POWER DISTRIBUTION PANEL
CISP
        CAST IRON SEWER PIPE
                                              FREQ
                                                      FREQUENCY
                                                                                                                                                                                                                                         YL
                                                                                                                                                                                                                                                 YARD LEAD
                                                                                                                                                   PHOTOELECTRIC CELL
                                                                                                                                                                                                                                        ZBOND IMPEDANCE BOND
NO. DATE BY CHECK DESIGN REVISION / SUBMITTAL
                                                                                                                                                                                                                                                                            SHEET
                                                                                                                                                                                                                   WEST-VOLUME 3 (SYSTEMS)
                                                                                                                                                                                                                                                                               3
                                                                                                                                                                                                                                 GENERAL
                                                                                                                                                                                                                                                                              OF
```







SYS-GEN-002

PRELIMINARY ENGINEERING


**SYSTEMS** 

202

### SYSTEMS LEGEND & GENERAL NOTES


## LAYOUT PLAN SYMBOLS: SC MANHOLE $\Box$ TE MANHOLE SC HANDHOLE SNOW MELTER CASE Д TPSS FENCE MAINLINE SC DUCTBANK MAINLINE TE DUCTBANK INTRUSION DETECTION MC DUCTBANK COMM CABINET TPSS BUILDING (TPSS-SW-##) SIGNAL OR INTERMEDIATE OR PLATFORM OR XING OR TUNNEL HOUSE OR ANY COMBINATION OF THESE OCS FEEDER POLE OCS POLE/FOUNDATION POLE WITH SINGLE CANTILEVER DOWN GUY ANCHOR SECTION INSULATOR, BRIDGING TYPE GRADE CROSSING GATE AND FLASHER BALANCE WEIGHT ANCHOR, SINGLE CONTACT WIRE POLE WITH TWIN CANTILEVER CROSSING CONTACT BRIDGE NEW POLE WITH WIRE PULL-OFF FOR TWO WIRES FIXED TERMINATION - FISH TAIL STYLE SINGLE CONTACT WIRE EXISTING DOWN GUY ANCHOR

### LAYOUT PLAN SYMBOLS CONT:



## **GENERAL NOTES:**

- 1. ITEMS SHOWN SCREENED ARE EITHER NOT-IN-CONTRACT OR ARE PART OF ANOTHER DESIGN PACKAGE.
- 2. DEPTH OF CONDUITS MAY VARY SLIGHTLY IN ORDER TO ACHIEVE ADEQUATE DRAINAGE INTO MANHOLES, HANDHOLES AND PULLBOXES. SEE SPECIFICATIONS.
- 3. ALL HANDHOLES AND MANHOLES SHALL BE LOCATED WITH LONG SIDE PARALLEL TO TRACKS UNLESS OTHERWISE NOTED
- COORDINATE INSTALLATION OF DUCTBANKS AT TRACK DRAINS AND BELOW TRACK SLABS.
- 5. LOCATION OF KNOWN EXISTING UNDERGROUND UTILITIES IS INDICATED ON UTILITY DRAWINGS. FIELD VERIFY LOCATIONS OF EXISTING UTILITIES PRIOR TO BEGINNING INSTALLATION OF



2								
<u></u>	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL		
	.							
E E								
37								
02:		•						
4	.							
2014	•							
56		•						
'n.								





**WEST-VOLUME 3 (SYSTEMS) GENERAL** LEGEND, SYMBOLS **AND GENERAL NOTES** 

OF


SHEET


DISCIPI INF SYSTEMS SYS-GEN-003


PRELIMINARY ENGINEERING


202


NEW DOWN GUY ANCHOR



















































































































































































































.lin. 26 2014 11:52 om V:\3200 PFC-W\CAD\OVERALI\SHFTS\SYSTEMS\DFTAHS\WO-S\



- 1. INSTALL SIX CABLE RACKS WITH TWELVE INSULATORS PER MANHOLE.
- 2. USE ROUND ACCESS RISERS (30" MAX) TO ACHIEVE FINAL ELEVATION.







**WEST-VOLUME 3 (SYSTEMS)** SYSTEMWIDE ELECTRICAL **DETAILS & TECHNICAL SHEETS MANHOLE TYPE TE** 

OF 202

SHEET


76

PRELIMINARY ENGINEERING


DISCIPLINE: **SYSTEMS** 

SECTION

SWE-DTL-102



- 1. INSTALL EIGHT CABLE RACKS WITH SIXTEEN INSULATORS PER MANHOLE.
- 2. USE RISER EXTENSIONS TO ACHIEVE FINAL ELEVATION.
- 3. COVERS SHALL BE DESIGNED TO WITHSTAND AASHTO HL-93 WHEEL LOADINGS. SUITABLE FOR USE IN OFF STREET LOCATIONS.



•	•	•	•	
	-	-		
	-	-		
	-	-		
	-	-		
	-	-		
	-	-		

PRELIMINARY ENGINEERING





**WEST-VOLUME 3 (SYSTEMS)** SYSTEMWIDE ELECTRICAL **DETAILS & TECHNICAL SHEETS MANHOLE TYPE SC** 

SHEET


77


OF

202

DISCIPLINE

**SYSTEMS** SWE-DTL-103





NOTES:

- 1. CONDUITS SHOWN ARE FOR EXAMPLE ONLY. ADDITIONAL CONDUITS MAY BE REQUIRED AS SHOWN ON THE PLAN SHEETS.
- 2. SEE SPECIFICATIONS REGARDING HOLD-DOWN BOLTS FOR COVERS.
- 3. CONDUITS SHALL EXTEND INTO THE HANDHOLE A MAXIMUM OF 1" FROM THE INSIDE WALL AND TERMINATE WITH BELL END FITTINGS.
- 4. INSTALL GROUND ROD CAUTIOUSLY TO AVOID DAMAGE TO POSSIBLE UTILITY
- 5. ADJUST CONDUIT ENTRY INTO THE HANDHOLE TO CREATE POSITIVE CONDUIT DRAINAGE AND TO ENTER CENTER OF HANDHOLE.
- 6. ADJUST DEPTH OF HANDHOLE TO ASSURE THAT COVER IS FLUSH WITH FINISHED GRADE. FOR LOCATIONS ON BRIDGES AND LAND BRIDGES TOP OF HANDHOLE IS TO BE AT THE SAME ELEVATION AS TOP OF RAIL.
- 7. LOCATE DRAIN HOLE ON LOWER END OF HANDHOLE AND PROVIDE STAINLESS STEEL SNAP-IN TYPE GRATE.
- 8. HANDHOLE MANUFACTURER IS SYNERTECH, MODEL NO. S3660C60FA OR APPROVED FQUAL.
- 9. SPECIAL HANDHOLE TYPES MAY BE REQUIRED AT SOME LOCATIONS.
- 10. HANDHOLE OFFSET DIMENSION IS VARIABLE. FINAL PLACEMENT OF HANDHOLE SHALL ASSURE THAT HANDHOLE TOP DOES NOT CONFLICT WITH TRACK CONSTRUCTION.

<u>~</u>	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	
	•	•					
an	•	•					
52	•	•					
11:		•					
4	•	•					
2014		•					
26							
lun,							





**WEST-VOLUME 3 (SYSTEMS)** SYSTEMWIDE ELECTRICAL **DETAILS & TECHNICAL SHEETS HANDHOLE TYPE TE** 

DISCIPLINE **SYSTEMS** SWE-DTL-104


202


SHEET

78

OF

PRELIMINARY ENGINEERING





DEVICE WITH ANSI FUNCTION/NUMBER (52) QUANTITY SHOWN OUTSIDE DEVICE CIRCLE

5	EMERGENCY TRIP STATION
26R1	RECTIFIER OVERTEMP ALARM (1ST. STAGE)
26R2	RECTIFIER OVERTEMP ALARM (2ND. STAGE)
	AC UNDERVOLTAGE RELAY
	BATTERY CHARGER UNDERVOLTAGE
30	ANNUNCIATOR/SUPERVISORY REVERSE POWER RELAY
32 33A 33D 33N	AC EQUIPMENT REAR DOOR OPEN
33D	DC EQUIPMENT REAR DOOR OPEN
33N	NEGATIVE CUBICLE DOOR SWITCH
33R	RECTIFIER DOOR SWITCH
33T	TRANSFORMER DOOR SWITCH
47	PHASE SEQUENCE RELAY
48	INCOMPLETE SEQUENCE RELAY
49T1	TRANSFORMER OVERTEMP ALARM (1ST STAGE)
4912	TRANSFORMER OVERTEMP TRIP (2ND STAGE)
50N	PHASE INSTANTANEOUS TIME OVER CURRENT RELAY GROUND INSTANTANEOUS TIME OVER CURRENT RELAY
50N 51	PHASE TIME DELAY OVER CHERENT RELAY
51N	INCOMPLETE SEQUENCE RELAY TRANSFORMER OVERTEMP ALARM (1ST STAGE) TRANSFORMER OVERTEMP TRIP (2ND STAGE) PHASE INSTANTANEOUS TIME OVER CURRENT RELAY GROUND INSTANTANEOUS TIME OVER CURRENT RELAY PHASE TIME DELAY OVER CURRENT RELAY GROUND TIME DELAY OVER CURRENT RELAY
52	AC CIRCUIT BREAKER
58AX	DIODE FUSE MONITOR, 1ST STAGE ALARM
58TX	DIODE FUSE MONITOR, 2ND STAGE TRIP
64/164	FRAME FAULT RELAY
64Ý	DC NEGATIVE TO GROUND VOLTAGE MONITOR
59	AC OVER VOLTAGE RELAY FRAME FAULT HOT STRUCTURE MONITORING RELAY FRAME FAULT GROUNDED STRUCTURE MONITORING RELAY RAIL TO GROUND VOLTAGE RELAY DC CIRCUIT BREAKERS DC DIRECT ACTING OVERCURRENT TRIP DEVICE TRANSFER TRIP RELAY TRANSFER TRIP RELAY(LOCKOLT)
6405	FRAME FAULT CONTINUED STRUCTURE MONITORING RELAT
64V	RAIL TO GROUND VOLTAGE RELAY
72/172	DC CIRCUIT BREAKERS
76/176	DC DIRECT ACTING OVERCURRENT TRIP DEVICE
85 <sup>°</sup>	TRANSFER TRIP RELAY
OOL	TIVITOTE EN TIME NEEM (EGGNOGT)
86	AC LOCKOUT RELAY
89	AC POWER DISCONNECT SWITCH
89N	NEGATIVE DISCONNECT SWITCH BATTERY CHARGER FAILURE ALARM
95A	BATTERY CHARGER FAILURE ALARM

150/150R DC RATE OF RISE AND OVERCURRENT RELAY 159<sup>°</sup> DC OVER VOLTAGE RELAY 159A 125 VDC CONTROL VOLTAGE SHORTED WITH 750VDC NEGATIVE TO EARTH POTENTIAL RELAY 164N DC LOAD MEASUREMENT AND RECLOSING RELAY 182 183 RECLOSING RELAY

RECTIFIER DIODE FAILURE ALARM (1ST STAGE)

RECTIFIER DIODE FAILURE ALARM (2ND STAGE) RECTIFIER DC SURGE SUPPRESSION FUSE FAILURE

DC LOCKOUT RELAY SMOKE DETECTOR RELAY SDR UX GROUND SENSING (VOLTAGE) GROUND SENSING (CURRENT)

DISCIPI INF

127/27DC DC FEEDER UNDERVOLTAGE RELAY LOSS OF AC CONTROL VOLTAGE

BATTERY UNDERVOLTAGE

LOSS OF DC CONTROL VOLTAGE

98R1 98R2

127A

127B 127C

AECOM LTK Engineering Services





**WEST-VOLUME 3 (SYSTEMS)** TRACTION POWER SYSTEM SYMBOLS, LEGEND AND **GENERAL NOTES** 


OF


SHEET


**SYSTEMS** 


TPS-GEN-001


PRELIMINARY ENGINEERING


























#### ANSI DEVICE LEGEND:

EMERGENCY STOP PUSHBUTTON
RECTIFIER DIODE OVERTEMPERATURE, 1ST STEP
RECTIFIER DIODE OVERTEMPERATURE, 2ND STEP AC SUPPLY UNDERVOLTAGE 27 BATC BATTERY CHARGER UNDERVOLTAGE
30 ANNUNCIATOR/SUPERVISORY REVERSE CURRENT INSTANTANEOUS RELAY RECTIFIER DOOR POSITION SWITCH
RECTIFIER TRANSFORMER DOOR POSITION SWITCH
PHASE SEQUENCE AND UNDERVOLTAGE RELAY PHASE SEQUENCE AND UNDERVOLIAGE RELAY
INCOMPLETE SEQUENCE RELAY
TRANSFORMER WINDING OVERTEMPERATURE, 1ST STEP
TRANSFORMER WINDING OVERTEMPERATURE, 2ND STEP
PHASE FAULT TIME OVERCURRENT RELAY W/INSTANTANEOUS ELEMENT
GROUND FAULT TIME OVERCURRENT RELAY W/INSTANTANEOUS ELEMENT
AC CIRCUIT BREAKER
PLOOF FUEL MONITOR 1CT STACE ALADM. 50/51 50/51N 52 58AX DIODE FUSE MONITOR, 1ST STAGE ALARM 58AX DIODE FUSE MONITOR, 2ND STAGE ALARM
58TX DIODE FUSE MONITOR, 2ND STAGE TRIP
64HS/GS FRAME FAULT RELAY
64V DC NEGATIVE TO GROUND VOLTAGE MONITOR
72 DC MAIN BREAKER
85 TRANSFER TRIP
85L TRANSFER TRIP
85L TRANSFER TRIP
86 AN LOCKOUT AC LOCKOUT RELAY, HAND RESET AC POWER DISCONNECT SWITCH NEGATIVE DISCONNECT SWITCH BATTERY CHARGER FAILURE ALARM

RECTIFIER DC SURGE SUPPRESSION FUSE FAILURE

DC FEEDER DIRECT ACTING TRIP DEVICE
DC FEEDER LOAD MEASURING AND VOLTAGE SENSING

DC FEEDER RATE OF RISE RELAY DC OVER VOLTAGE RELAY DC FFEDER BREAKER

DC LOCKOUT RELAY, HAND RESET SMOKE DETECTOR ALARM

RECLOSING RELAY

- 1. KEY INTERLOCK SHALL PREVENT OPENING OF 89N DEVICE UNLESS 72 DEVICE IS OPEN.
- 2. PROTECTIVE DEVICES AND INSTRUMENTS FOR FEEDER 2 IS IDENTICAL TO FEEDER 1.
- CURRENT AND POTENTIAL TRANSFORMERS AND UTILITY METER ARE PROVIDED BY THE UTILITY.
- 4. CONNECT TO SUBSTATION GROUND GRID.
- 5. SEPARATE DRIVEN RODS LOCATED AT CATENARY FEEDER POLE.
- NOTE NOT USED.
- ONE 3-PHASE SOLID STATE OVERCURRENT RELAY PROGRAMMED TO FOLLOW NEMA RI-9 EXTRA HEAVY DUTY TRACTION OVERLOAD PROFILE.
- GROUND-MOUNTED DC FEEDER DISCONNECT SWITCHES RATED AT 2KA, 1000VDC LOCATED ADJACENT TO TRACTION POWER SUBSTATION.

NO.	DAIL	01	CHILCK	DESIGN	REVISION / SUBMITTAE
•					
		•		-	
	•			-	
	•			-	
				-	
•					

AECOM LTK Engine

PRELIMINARY ENGINEERING





## **WEST-VOLUME 3 (SYSTEMS)** TRACTION POWER SYSTEM **SUBSTATION DETAILS MAINLINE TPSS-- ONE LINE DIAGRAM**

TPS-OLD-001

DISCIPLINE: **SYSTEMS** 

90 OF

202

SHEET

#### **REAR** AC PANELBOARD-LIGHT-FIRE EXTINGUISHER-DC PANELBOARD RATTERY EXHAUST — CHARGER & FYF-\_DC TEST FAN HOOD RECTIFIER -LIGHT WASH CABINET FIRE EXTINGUISHER-CONCRETE PAD-PHONE COMM RACK FOLD BATTERY DOWN TABLE RAIL TO AC TEST EMERGENCY-GROUND -LOWER LIGHT GROUND BUS UPPER: GROUND BUS SMOKE-LIGHT-OVERHEAD-DIELECTRIC, RED EPOXY FLOOR (TYP) -SMOKE LIGHT RIGHT HEAT. (TYP) DETECTOR CPT & FUSE DETECTOR KNOX BOX-LEFT DRAWER INCOMING CIRCUIT AC WITH BLUE LIGHT BREAKER DISCONNECT FEEDER FEEDER CONCRETE NEGATIVE SWITCH BREAKER RECTIFIER SECTION BREAKER PADFEEDER BREAKER **SECTION** SWITCH TRANSFORMER F2 FEEDER UTILITY BREAKER 1/4" GLASTIC-F3 METERING F1 **BARRIER** -METER SOCKET RECTIFIER IPT UPPER-GROUND BUS -LIGHT REMOVABLE PANELS -LIGHT NOTE 14 40' BASE FRAME

**FRONT** 

- 1. PROVIDE PREFABRICATED BUILDING AND EQUIPMENT UNDER THIS CONTRACT
- 2. EQUIPMENT DIMENSIONS ARE APPROXIMATE. SUBMIT FINAL DIMENSIONS TO THE C.A.R. FOR APPROVAL
- 3. MOUNT ROOF VENTILATORS TO PREVENT INCURSION OF WATER UNDER ALL CONDITIOINS
- 4. SIZE AND LOCATION OF DC CABLE ENTRANCES TO BE DETERMINED BY CONTRACTOR
- 5. PROVIDE ELECTRICAL INSULATION ON WALLS AND FLOOR IN AREAS SHOWN
- 6. PROVIDE GLASTIC BARRIER BETWEEN RECTIFIER TRANSFORMER AND RECTIFIER. EXTEND GLASTIC 1'-6" BEYOND RECTIFIER TRANSFORMER AS SHOWN. PROVIDE AN INSULATED FINISHED EDGE ON EXPOSED GLASTIC EDGE. ALSO, INSTALL GLASTIC BARRIER BETWEEN EACH DC FEEDER BREAKER, AND DC MAIN BREAKER AND NEGATIVE DISCONNECT SWITCH
- 7. SPACE DC SWITCHGEAR AND RECTIFIER 2 INCHES OFF REAR WALL
- PROVIDE WALL MOUNTED HINGED WORK TABLE WITH SUPPORTS.
- PROVIDE DRAW OUT FUSE TRUNNION WITH MECHANICAL INTERLOCK TO L.V. MAIN AC C.B. PANELS
- 10. BLUE LIGHT, ETEL, CARD READER, KNOX BOX, CAMERA, AND ACCESS CONTROLLER PANEL ONLY LOCATED ON ONE END OF TPSS. CONSULT WITH C.A.R. REGARDING LOCATION OF THIS EQUIPMENT ON PER SITE
- 11. FRONT OF COMMUNICATION RACK TO FACE WORK BENCH
- 12. GROUND BUS BAR MUST BE SILVER PLATED. REFER TO SPECIFICATIONS FOR DETAILED REQUIREMENTS. EQUIPMENT GROUNDS MUST ALSO BE SILVER PLATED BUS BAR.
- 13. INSULATED COVERS MUST BE FURNISHED WITHIN THE FLOOR.
- 14. PROVIDE REMOVABLE PANELS TO ALLOW REMOVAL OF TRANSFORMERS.
- 15. INSTALL ACS READER, ETEL, AND CAMERA AT MAIN DOOR OF TPSS.

_					
Ε	•	-	•	•	
ā	•	•			
39	•	•			
10:	•	•			
4	•	•			
201	•				
56					
'n	-				

NO. DATE BY CHECK DESIGN REVISION / SUBMITTAL

AECOM LTK Engineering Services





**WEST-VOLUME 3 (SYSTEMS)** TRACTION POWER SYSTEM **SUBSTATION DETAILS** MAINLINE TPSS EQUIPMENT LAYOUT PLAN


**SYSTEMS** 

TPS-DTL-101

91 OF 202

SHEET

PRELIMINARY ENGINEERING




PRELIMINARY ENGINEERING

202


TPS-DTL-102

**SYSTEMS** 



#### NOTES:

- 1. INSTALL VPD RECEIVERS IN DC FEEDER CONTROL CABINET OR PROVIDE A SEPARATE NEMA 4 PVC ENCLOSURE FOR VPD INSTALLATION IF REQUIRED.
- 2. REFER TO MANUFACTURERS REQUIREMENTS FOR CONTROL POWER VOLTAGE.
- 3. VPD HOT AND FAULT STATUS TO BE MONITORED AND INDICATED BY LCMS HMI AND CENTRAL CONTROL SYSTEM.
- 4. EXISTING AC PANELBOARD IN TPSS. PROVIDE A 10/1 POLE BREAKER TO FEED VPD POWER SUPPLY.
- 5. FURNISH AND INSTALL ISOLATION TRANSFORMER, 300 WATT 120V AC TO 24V DC POWER SUPPLY IN A NON-METALLIC ENCLOSURE WITH MOUNTING PANEL TO BE USED TO POWER THE VPD EQUIPMENT.
- 6. PROVIDE A SET OF FUSED TERMINAL BLOCKS IN THE ENCLOSURE WITH FUSES AND WIRING TO FEED EQUIPMENT AS



AECOM LTK Engineering Services





## **WEST-VOLUME 3 (SYSTEMS)** TRACTION POWER SYSTEM **SUBSTATION DETAILS** MAINLINE VOLTAGE PRESENCE DETECTOR

TPS-DTL-103

SHEET

93


OF

202


PRELIMINARY ENGINEERING


**SYSTEMS** 

INTERMEDIATE SPACER



BASE SPACER (BASE SPACER PROVIDES 3" SEPERATION BETWEEN THE BOTTOM ROW OF DUCTS AND THE TRENCH FLOOR)








- 1. DUCTBANK SECTION VIEWS ARE INDICATED ON TYPICAL SUBSTATION LAYOUT PLAN.
- 2. DEPTH OF DUCTBANKS SHALL BE AS FOLLOW:
  - \* GENERAL: 30 INCHES BELOW GRADE
  - \* UNDER TRACKS: 50 INCHES BELOW BOTTOM OF TIE

NOT TO SCALE

3. SPARE CONDUITS SHALL BE TERMINATED AT RESPECTIVE MANHOLES WHEN INDICATED ON SITE PLAN. IF NO MANHOLE IS INDICATED, SPARE CONDUITS SHALL BE CAPPED 5 FEET BEYOND THE SUBSTATION









SECTION A MEDIUM VOLTAGE CABLES

SECTION B NEGATIVE TRACTION POWER CABLES




POSITIVE TRACTION POWER CABLES





SECTION E LOW VOLTAGE (UNDER 600VAC) DISTRIBUTION CABLES








## **WEST-VOLUME 3 (SYSTEMS)** TRACTION POWER SYSTEM **SUBSTATION DETAILS** TYPICAL DUCTBANK CONFIGURATIONS

DISCIPLINE: **SYSTEMS** TPS-DTL-104


PRELIMINARY ENGINEERING

"TYPE 1" TYPICAL POWER BONDING CONNECTION SINGLE RETURN RAIL IN CROSSOVER




TYPICAL NEGATIVE RETURN CONNECTION
AC TRACK CIRCUIT TERRITORY WITH DOUBLE
IMPEDANCE BONDS AND I.J.'S ON BOTH TRACKS

## "TYPE 2"




TYPICAL CROSSBONDING CONNECTION
AC TRACK CIRCUIT TERRITORY WITH DOUBLE
IMPEDANCE BONDS AND I.J.'S ON BOTH TRACKS

"TYPE 3"




TYPICAL NEGATIVE RETURN CONNECTION
AC TRACK CIRCUIT TERRITORY WITH DOUBLE
IMPEDANCE BONDS AND I.J.'S ON BOTH TRACKS

## "TYPE 4"




### "TYPE 5"




TYPICAL CROSSBONDING CONNECTION SINGLE RETURN RAIL TO DOUBLE RETURN RAIL TRANSITION

# "TYPE 6"




TYPICAL NEGATIVE RETURN CONNECTION SINGLE RETURN RAIL TO DOUBLE RETURN RAIL TRANSITION

## <u>"TYPE 7"</u>



TO SUBSTATION NEGATIVE BUS TYPICAL NEGATIVE RETURN CONNECTION SINGLE RETURN RAIL TO DOUBLE RETURN RAIL TRANSITION

## "TYPE 8"



NEGATIVE BUS TYPICAL NEGATIVE RETURN CONNECTION UNSIGNALED RETURN RAIL TO DOUBLE RETURN RAIL TRANSITION

## "TYPE 9"

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	Г
	•					
		•		-		
	•					
	-		-	-		
-						

AECOM LTK Engine





**WEST-VOLUME 3 (SYSTEMS)** TRACTION POWER SYSTEM **SUBSTATION DETAILS** TYPICAL RAIL RETURN BONDING DETAILS

> **SYSTEMS** TPS-DTL-105


PRELIMINARY ENGINEERING

202

SHEET

95

OF



	•	•	•	
,	•	•	•	
	•			
:	•			
.	•			
	•			
	•			
,				
5				

AECOM LTK LTK Engineering Services





**WEST-VOLUME 3 (SYSTEMS)** TRACTION POWER SYSTEM **SUBSTATION DETAILS TYPICAL GROUND GRID DETAILS** 


OF

96

PRELIMINARY ENGINEERING

DISCIPLINE: **SYSTEMS** 

TPS-DTL-106



AECOM LTK Engine

PRELIMINARY ENGINEERING






**WEST-VOLUME 3 (SYSTEMS)** TRACTION POWER SYSTEM **SUBSTATION DETAILS OMF - ONE LINE DIAGRAM - SHOP** 


OF 202

SHEET

97

DISCIPLINE: **SYSTEMS** TPS-OLD-003





- 1. SEE SECTIONALIZING DIAGRAM FOR ADDITIONAL INFORMATION ON NUMBERING
- 2. COORDINATE METERING REQUIREMENTS WITH XCEL ENERGY
- 3. CT SIZE SUBJECT TO C.A.R. APPROVAL. POWER METER CTS TO BE REVENUE METERING ACCURACY
- 4. PROVIDE SURGE ARRESTER IN SEPARATE ENCLOSURE WITHIN TRANSFORMER ENCLOSURE.
- 5. PROTECTIVE DEVICES TYPICAL FOR ALL BREAKERS

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	
						1
•						1
•						1
•						1
						1
•	-		-	-		
						1

AECOM LTK Engine





**WEST-VOLUME 3 (SYSTEMS)** TRACTION POWER SYSTEM **SUBSTATION DETAILS** 

OF 202

SHEET


99

DISCIPLINE: **SYSTEMS** 

TPS-OLD-004

PRELIMINARY ENGINEERING

**OMF - ONE LINE DIAGRAM - YARD** 



**FRONT** 

- 1. PROVIDE PREFABRICATED BUILDING AND EQUIPMENT UNDER THIS CONTRACT
- 2. EQUIPMENT DIMENSIONS ARE APPROXIMATE. SUBMIT FINAL DIMENSIONS TO THE C.A.R. FOR APPROVAL
- 3. MOUNT ROOF VENTILATORS TO PREVENT INCURSION OF WATER UNDER ALL CONDITIOINS
- 4. SIZE AND LOCATION OF DC CABLE ENTRANCES TO BE DETERMINED BY CONTRACTOR
- 5. PROVIDE ELECTRICAL INSULATION ON WALLS AND FLOOR IN AREAS SHOWN
- 6. PROVIDE GLASTIC BARRIER BETWEEN RECTIFIER TRANSFORMER AND RECTIFIER. EXTEND GLASTIC 1'-6" BEYOND RECTIFIER TRANSFORMER AS SHOWN. PROVIDE AN INSULATED FINISHED EDGE ON EXPOSED GLASTIC EDGE. ALSO, INSTALL GLASTIC BARRIER BETWEEN EACH DC FEEDER BREAKER, AND DC MAIN BREAKER AND NEGATIVE DISCONNECT SWITCH
- 7. SPACE DC SWITCHGEAR AND RECTIFIER 2 INCHES OFF REAR WALL
- 8. PROVIDE WALL MOUNTED HINGED WORK TABLE WITH SUPPORTS.
- PROVIDE DRAW OUT FUSE TRUNNION WITH MECHANICAL INTERLOCK TO L.V. MAIN AC C.B. PANELS
- 10. BLUE LIGHT, ETEL, CARD READER, KNOX BOX, CAMERA, AND ACCESS CONTROLLER PANEL ONLY LOCATED ON ONE END OF TPSS. CONSULT WITH C.A.R. REGARDING LOCATION OF THIS EQUIPMENT ON PER SITE
- 11. GROUND BUS BAR MUST BE SILVER PLATED. EQUIPMENT GROUNDS MUST ALSO BE SILVER PLATED BUS BAR.
- 12. INSTALL ACS READER, ETEL, AND CAMERA AT MAIN DOOR OF TPSS.

- 1	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL
- 1	•	•	•		-	
ı		•				
ı		•				
ı	•	•	•		-	
ı	•	•	•	-	-	
ı					-	
I					-	
I						
I		•				

AECOM LTK Engineering Services

PRELIMINARY ENGINEERING





**WEST-VOLUME 3 (SYSTEMS)** TRACTION POWER SYSTEM **SUBSTATION DETAILS OMF - EQUIPMENT LAYOUT - YARD** 


OF 202

SHEET

100

DISCIPLINE **SYSTEMS** 

TPS-DTL-301



- 1. ALL STEEL TO CONFORM TO ASTM A36
- 2. ALL WELDING TO CONFORM TO AWS D1.1
- 3. HOT DIP GALVANIZED PER ASTM A123/A123-97A AFTER MACHINING AND WELDING
- 4. 4" PVC CONDUIT EXPOSED FROM BOTTOM OF SWITCH BOX TO PVC CONDUIT COUPLING PROJECTING 3" ABOVE CONCRETE ENCASEMENT
- 5. ALL SWITCHES ARE RATED 2KA, 1000VDC
- 6. ALL CONDUITS TO TRACK ARE 4" PVC-80, CONCRETE
- 7. STUB AND CAP SPARE CONDUITS 6" ABOVE TOP OF
- 8. PROVIDE SWITCH STATUS DEVICE AND HARDWARE IN CABINET FOR EACH SWITCH TO INDICATE SWITCH
- PROVIDE CONTROL CABLE FROM SWITCH STATUS DEVICE TO TPS FOR INDICATION TO LOMS AND COS. ALSO, PROVIDE VPD FIBER OPTIC CABLE AND NEGATIVE REFERENCE CABLE BACK TO TPSS.
- 10. SS #10 SHIMS PLACED UNDER BASEPLATE TO LEVEL FRAME
- 11. PROVIDE CONDUIT TO SWITCH ENCLOSURE USING INSULATED HARDWARE. SEAL AROUND PENETRATIONS. SURGE ARRESTER TO BE CONNECTED ON LOAD SIDE OF DISCONNECT SWITCH.
- 12. VOLTAGE PRESENCE DETECTOR IS MOUNTED BESIDE THE SURGE ARRESTER, AS SHOWN IN THE PLAN VIEW. WELD CHANNEL BRACKET OR PLATE ACROSS CHANNEL FOR MOUNTING ENCLOSURES.

AECOM LTK LTK Engineering Services

PRELIMINARY ENGINEERING





**WEST-VOLUME 3 (SYSTEMS)** TRACTION POWER SYSTEM **SUBSTATION DETAILS** TPSS FEEDER DISCONNECT SWITCHES


OF 202

SHEET

101

**SYSTEMS** 

TPS-DTL-401



PRELIMINARY ENGINEERING

**SYSTEMS** 

TPS-SW11-GSP

### LAYOUT PLAN SYMBOLS CONT.

BALANCE WEIGHT ANCHOR, SINGLE CONTACT WIRE

POLE WITH TWIN CANTILEVER

CROSSING CONTACT BRIDGE

AERIAL FEEDER WIRE PARALLEL TO TRACK

NEW POLE WITH WIRE PULL-OFF FOR TWO WIRES

STRING LINE OFFSET OF RAIL AT MIDSPAN

IN SPAN JUMPER

POLE, JOINT USE WITH SINGLE CANTILEVER AND STREET LIGHT

FIXED TERMINATION - FISH TAIL STYLE SINGLE CONTACT WIRE

EXISTING DOWN GUY ANCHOR

NEW DOWN GUY ANCHOR

PASSENGER STATION

TRACTION POWER SUBSTATION

TURNBUCKLE

STATION

 $\bowtie$ 

---

BWA XXXI

FA XXX

XXXXXX

246 (6)

<sup>b</sup>SA

SURGE ARRESTOR

POLE MOUNTED SINGLE DISCONNECT SWITCH

POLE MOUNTED DOUBLE DISCONNECT SWITCHES

BALANCE WEIGHT ANCHOR LABEL XXX-LENGTH IN FEET FROM BALANCE WEIGHT ANCHOR TO FIXED ANCHOR OR TO MID-POINT

FIXED ANCHOR LABEL XXX—LENGTH IN FEET FROM FIXED ANCHOR TO BALANCE WEIGHT ANCHOR

MID POINT ANCHOR LABEL XXX-HALF TENSION LENGTH IN FEET FROM MID-POINT TERMINATION TO BALANCE WEIGHT ANCHOR

TENSION LENGTH IDENTIFICATION NUMBER

STEADY SPAN STRUCTURE (NO SUPPORT)

LAYOUT PLAN SYMBOLS CONT.

HEADSPAN SUPPORT STRUCTURE WITHOUT STEADY SPAN REGISTRATION

PORTAL STRUCTURE

NEW POLE WITH BACK-TO-BACK CANTILEVERS

POLE, JOINT USE WITH BACK-TO-BACK OCS CANTILEVERS AND STREET LIGHTS

TWO TRACK CANTILEVER - HINGED SUPPORT

SINGLE CONTACT WIRE BRIDLE SUPPORT AND REGISTRATION ASSEMBLY

POTENTIAL EQUALIZING JUMPER

POLE WITH BACK-TO-BACK DOUBLE CANTILEVERS

INSULATOR CUT INTO OUT-OF-RUNNING C/W

FULL CURRENT JUMPER

\_\_p\_\_

HEADSPAN SUPPORT STRUCTURE WITH STEADY SPAN REGISTRATION

SPRING TENSIONER - SINGLE CONTACT WIRE

BALANCE WEIGHT ANCHOR SIMPLE CATENARY SYSTEM

OUT OF RUNNING CONTACT WIRE

FIXED TERMINATION - SIMPLE CATENARY SYSTEM

HEADSPAN STRUCTURE ATTACHED TO BUILDING ANCHORS

TUNNEL OR BRIDGE SUPPORT

TUNNEL OR BRIDGE SUPPORT AND REGISTRATION

POLE WITH WIRE PULL OFF FOR ONE WIRE

	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	Γ
	•	•					l
,	•	•					l
	•						l
	•						l
	•	-	•	•	-		
:							
-	•				-		
							1





**WEST-VOLUME 3 (SYSTEMS) OVERHEAD CONTACT SYSTEM GENERAL** 

SHEET

103

OF


202

SYMBOLS, LEGEND, AND GENERAL NOTES

**SYSTEMS** SYS-OCS-GEN-001

PRELIMINARY ENGINEERING

### NON O.C.S. CONDUCTOR CLEARANCES ABOVE CONTACT WIRE



VEHICLE EXCEEDING

8 FT HEIGHT

OCS WIRE CLEARANCES ABOVE GROUND OR RAILS


PUBLIC STREETS BUT NOT

OVERHANGING ROADWAY

- 1. ALL CLEARANCES SHALL COMPLY WITH NATIONAL ELECTRIC SAFETY CODE
- 2. ALL CLEARANCES ARE MINIMUM VALUES
- 3. VERTICAL CLEARANCES APPLY TO CONTACT WIRES UNDER THE FOLLOWING CONDITIONS:
  - A. CONDUCTOR TEMPERATURE OF 60° F. NO ICE. NO WIND. WITH FINAL SAG IN THE WIRE. OR CONDUCTOR TEMPERATURE OF 32° F, ICE (OPERATING CONDITIONS) NO WIND, WITH FINAL SAG IN THE WIRE, WHICHEVER IS GREATER
  - B. SPAN LENGTHS NOT GREATER THAN THE FOLLOWING:

AUTO TENSIONED SIMPLE CATENARY - 220 FT

- 4. VERTICAL CLEARANCES APPLY TO NON-OCS CONDUCTORS ABOVE OCS CONTACT WIRES OR SPAN WIRE WITH NO ICE OR UNDER THE FOLLOWING CONDITIONS:
- A. CONDUCTOR SAG AT 120° F
- B. OR MAXIMUM CONDUCTOR TEMPERATURE IS GREATER THAN 120° F
- C. OR 32° F WITH RADIAL ICE OF 0.25 INCHES WHICHEVER PRODUCES THE LARGEST SAG AND O.C.S. CONTACT WIRES, AND SPAN WIRE WITH NO ICE
- 5. FOR VOLTAGES EXCEEDING 22KV (UP TO 470KV) THE CLEARANCE SHALL BE INCREASED BY 0.4 INCHES FOR EACH 1KV, OR FRACTION THEREOF, IN EXCESS OF 22KV



OVERHEAD BRIDGE OR TUNNEL OCS CONTACT WIRE CLEARANCES ABOVE RAIL INCLUDING ICE LOADING

SHEET

104

OF

202

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL
•					
	•				
				-	
				-	
				-	
				-	

RAILROADS USING OVER-

HEAD CONDUCTOR.)

AECOM LTK Engineering Services

PRELIMINARY ENGINEERING

ANY VEHICLE EXCEEDING 8

FT HEIGHT





RESTRICTED TO RIDERS ON

HORSES, ANIMALS, AND VEHICLES LESS THAN 8 FT HEIGHT

## **WEST-VOLUME 3 (SYSTEMS) OVERHEAD CONTACT SYSTEM - DETAILS VERTICAL ELECTRICAL CLEARANCE REQUIREMENTS**

DISCIPI INF **SYSTEMS** 

OCS-DTL-101

### DESIGN CRITERIA

1. CLIMATIC PARAMETERS

**TEMPERATURE** OPEN ROUTE

NORMAL AMBIENT 60°F MINIMUM AMBIENT -40°F MAXIMUM CONTACT WIRE 120°F

OPEN ROUTE

1/4" RADIAL 1/2" RADIAL 1/2" RADIAL 1/2" RADIAL **OPERATING** NON-OPERATING

OPEN ROUTE OPERATING (ICE) 40mph OPERATING (NO ICE) 55mph NON OPERATING (NÓ ICE) 90mph

2. ELECTRICAL CLEARANCES

STATIC 4 INCHES **PASSING** 3 INCHES

3. CATENARY SYSTEM PARAMETERS

CATENARY SYSTEM PARAMETERS		SCAT	SWFT
ITEM	UNITS	MAINLINE	YARD
WIRE SIZE: CONTACT MESSENGER	KCMIL KCMIL	350 500	350 -
TENSION AT DESIGN TEMP (60'F) CONTACT WIRE MESSENGER WIRE	LB LB	3000 5000	1750 –
NORMAL CONTACT WIRE HEIGHT	FEET	18.5	18.5
MAXIMUM WIRE HEIGHT	FEET	22.3	22.3
NORMAL SYSTEM HEIGHT	FEET	4.0	ı
MAXIMUM SPAN	FEET	220	80
MAXIMUM STAGGER	INCHES	9	9
MAXIMUM 1/2 TENSION LENGTH	FEET	2650	_
CONTACT WIRE MAXIMUM WEAR	PERCENT	30	30
POLE DEFLECTION AT CWH (MAXIMUM)	INCHES	2	2
MAX LIVE LOAD POLE DEFLECTION AT CONTACT WIRE HEIGHT	INCHES	1	1
FOUNDATION ROTATION (MAXIMUM)	DEGREES	0.50	0.50
MAX CONTACT WIRE GRADIENT (30mph) CONSTANT GRADIENT (30mph) CHANGE OF GRADIENT	RATIO RATIO	1 in 150 1 in 300	1 in 150 1 in 300

4. TOLERANCES AND RELATED INFORMATION:

A. TRACK

EMBEDDED/DF OPEN ROUTE YARD

DIRECT FIXATION BALLASTED BALLASTED **VERTICAL** 0.125 INCHES 0.50 INCHES 1.00 INCHES 0.50 INCHES HORIZONTAL 0.50 INCHES 0.50 INCHES GROSS LEVEL 0.125 INCHES/GAUGE 0.125 INCHES/GAUGE 0.25 INCHES/GAUGE 0.125 INCHES -0.125 TO  $\pm 0.25$  INCHES 0.125 INCHES

1.81 INCHES

2.00 INCHES

32.43 FEET

11.56 FEET

4.00 DEGREES

8.7 - 8.8 FFFT

90 - 94 FEET 5.91 TO 6.23 FEET

B. VEHICLE (ARTICULATED)

LATERAL DISPLACEMENT (EACH SIDE) ROLL TO EACH SIDE - MAXIMUM BOUNCE - MAXIMUM TRUCK CENTER WIDTH (OVER SIDE SHEETS) LENGTH (OVER COUPLERS) TRUCK CENTER TO COUPLER FACE

C. PANTOGRAPH

OVERALL WIDTH 6.50 FEET CARBON WIDTH 3.50 FEET MAXIMUM CARBON WEAR 0.75 INCHES MAX LOCKDOWN HEIGHT 12.70 FEET ABOVE RAIL MINIMUM PANTOGRAPH HEIGHT MAXIMUM DEFLECTION RELATIVE 1.50 INCHES TO EACH SIDE

D. OVERHEAD CONTACT SYSTEM UNITS INSTALLATION TOLERANCES

STRUCTURE FOUNDATION FEET  $\pm 5.0$ LOCATION ALONG TRACK: TANGENT & CURVE > 500 FT RADIUS

TRACK CURVE LESS THAN 500 FT FEET  $\pm 2.00$ 

ADJACENT TO SPECIAL  $\pm 2.00$ TRACKWORK

MAX SPAN CHANGE BETWEEN TWO FEET  $\pm 5.00$ ADJACENT STRUCTURES

STRUCTURE FOUNDATION LOCATION ACROSS TRACK

- OUTSIDE POLES INCHES -0 +1.0- CENTER POLES INCHES ±1.00 FOUNDATION ELEVATION INCHES ±1.00

POLE BASEPLATE ELEVATION INCHES ±1.00 HANGER SPACING INCHES ±3.00

CONDUCTOR HEIGHT AT SUPPORTS (SEE NOTE 1)

**SUPPORTS** 

OPEN ROUTE INCHES ±1.00 INCHES ±0.50 - TUNNEL UNDER & BRIDGES STAGGER AT SUPPORTS

MESSENGER & CONTACT WIRE INCHES ±2.00 STAGGER DIFFERENCE AT

INCHES ±1.00

POUNDS ±50 WIRE TENSION

5. MINIMUM CONTACT WIRE HEIGHT TRACK VERTICAL TOLERANCE 0.5 VEHICLE HEIGHT ABOVE RAIL LEVEL 12 PANTOGRAPH LOCKDOWN ABOVE VEHICLE 0 PANTOGRAPH LOCKDOWN TO MINIMUM 0 OPERATING HEIGHT CONTACT WIRE ERECTION TOLERANCE 0.5 VEHICLE VERTICAL BOUNCE

MINIMUM CONTACT WIRE HEIGHT 13 6.5 6. DESIGN MINIMUM CONTACT WIRE HEIGHT FT IN

EXCLUSIVE R.O.W. ROAD GRADE CROSSING
"HIGH & WIDE" GRADE CROSSING 18 IN STREET (NOT DOWNTOWN) 18 DOWNTOWN TUNNEL SECTIONS 13 10 18 YARD

#### NOTE:

- 1. THE TOLERANCE GIVEN AT THE SUPPORTS FOR THE CONDUCTOR HEIGHT IS ONLY APPLICABLE PROVIDED THE CONDUCTOR GRADIENT IS ACCEPTABLE
- 2. FOR PANTOGRAPH CLEARANCE ENVELOPE SEE SHEET 106
- 3. ALL MINIMUM CONTACT WIRE HEIGHTS SHALL NOT BE EXCEEDED BY DROOP DUE TO ICE LOADING.

NO. DATE BY CHECK DESIGN REVISION / SUBMITTAL





**WEST-VOLUME 3 (SYSTEMS) OVERHEAD CONTACT SYSTEM - DETAILS** PARAMETERS, TOLERANCES AND **WIRE HEIGHTS** 

**SYSTEMS** OCS-DTL-102

PRELIMINARY ENGINEERING

SHEET 105

OF

DISCIPI INF





TABLE	1: DIMENS	ION TABLE
AS-BUILT	DIMENSION	A INCHES
CW HT	EMBEDDED	BALLASTED
	TRACK	TRACK
22'-0"	65.6	69.3
18'-6"	62.4	65.7
16'-0"	60.0	63.1
13'-10"	58.0	60.8

SCALE: NTS SUPER ELEVATED TRACK 2 CLEARANCE ENVELOPE FOR PANTOGRAPHS-REFER TO DESIGN CRITERIA FOR COMPLETE CLEARANCE ENVELOPE-TOP OF RAIL

SIMPLIFIED PANTOGRAPH CLEARANCE ENVELOPE FOR AS—BUILT CONDITIONS

#### NOTES:

- 1. THIS DRAWING PROVIDES A SIMPLIFIED PANTOGRAPH CLEARANCE ENVELOPE FOR USE WITH AS BUILT OCS EQUIPMENT. TRACK AND POLES, MASONRY WALLS AND STRUCTURES. THE DIMENSIONS ARE TO BE MEASURED RELATIVE TO THE SUPERELEVATED TRACK.
- 2. OBSTRUCTIONS NOT CLEARING THIS OUTLINE MAY BE FURTHER EXAMINED AGAINST THE CONDITIONS AND MINIMUM CLEARANCES OF SHEETS 107, 108 & 109. SEE DETAIL 3.
- 3. FOR VALUES OF CONTACT WIRE HEIGHT BETWEEN THOSE LISTED IN TABLE 1, USE LINEAR INTERPOLATION TO DETERMINE A VALUE FOR DIMENSION A.
- 4. MINIMUM CLEARANCES FOR USE PRIOR TO CONSTRUCTION ARE TO BE CALCULATED USING ALLOWANCES SHOWN ON SHEETS 107, 108 & 109.
- 5. MINIMUM CLEARANCES BETWEEN LIVE WIRES OR FITTINGS AND OTHER FIXED INFRASTRUCTURE SHALL BE DETERMINED FROM NATIONAL ELECTRIC SAFETY CODE (N.E.S.C)
- 6. FOR STRUCTURAL MEMBERS THE VERTICAL CLEARANCE IS TO BE INCREASED TO 11.25".



RELATED MINIMUM CLEARANCE DETAIL

:	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	П
	•						1
5	•						1
7	•						1
į	•		•		-		
t	•						
2	•						
,							
,				•	-		
, III,							1

PRELIMINARY ENGINEERING





**WEST-VOLUME 3 (SYSTEMS) OVERHEAD CONTACT SYSTEM - DETAILS** SIMPLIFIED PANTOGRAPH **CLEARANCE ENVELOPE** 

DISCIPI INF **SYSTEMS** 


OCS-DTL-103

SHEET

106


OF

TABLE 2: CLEARANCE DIMENSIONS SEE NOTE 5					
AS-BUILT	DIMENSION A INCHES				
CW HT	EMBEDDED	BALLASTED			
CW III	TRACK	TRACK			
22'-0"	62.1	64.3			
18'-6"	58.9	60.7			
16'-0"	56.5	58.1			
13'-10"	54.5	55.8			



### EXTRACT FROM PANTOGRAPH DYNAMIC ENVELOPE

SUPERELEVATION PANTOGRAPH CLEARANCE FOR DESIGN - INSIDE OF CURVE **ELECTRICAL** PASSING CLEARANCE TRACK -(RUNNING CONSTRUCTION CLEARANCE) AND OFFSET DUE TO MAINTENANCE **SUPER TOLERANCE** ELEVATION = ENVELOPE 0S EMBEDDED, 1.0" (SEE TABLE 1) DIRECT FIXATION=0.5" 3" BALLASTED DYNAMIC TRACK=2" AS BUILT FACE OF POLE, STRUCTURE, OR EQUIPMENT SUPERELEVATED VEHICLE DYNAMICENVELOPE VEHICLE CLEARANCE EN FOR DESIGN C STRUCTURE OR




MINIMUM HORIZONTAL CLEARANCE TO OBJECTS ON THE INSIDE OF CURVE FROM A PANTOGRAPH

MINIMUM HORIZONTAL CLEARANCE TO OBJECTS ON THE OUTSIDE OF CURVE FROM A PANTOGRAPH

#### NOTES:

- 1. THIS DRAWING PROVIDES DETAILED RELATIONSHIPS AND DIMENSIONS FOR DETERMINATION OF MINIMUM CLEARANCES BETWEEN A PANTOGRAPH AND ADJACENT FIXED INFRASTRUCTURE. THESE CLEARANCES MAY BE FURTHER REDUCED ONLY FOR THOSE CASES LISTED IN NOTE 2
- 2. FOR THE PURPOSE OF DETERMINATION OF CLEARANCES TO A PANTOGRAPH, AN OCS FITTING SHALL BE CONSIDERED LIVE WHERE IT IS SEPARATED FROM GROUNDED POLES OR LIVE WIRING OF ADJACENT TRACKS. BY AT LEAST ONE LEVEL OF SYSTEM RATED INSULATION
- FOR IN-RUNNING LIVE STEADY ARMS, SEE SHEET 109
- FOR OTHER LIVE OCS EQUIPMENT. SEE SHEET 108
- ALL OTHER STRUCTURES, POLES OR EQUIPMENT REQUIRE PANTOGRAPH CLEARANCES DETERMINED FROM THIS DRAWING
- 3. FOR OBJECTS DIAGONALLY SEPARATED, BOTH HORIZONTAL AND VERTICAL CLEARANCES ARE TO BE APPLIED. RUNNING CLEARANCES COMPONENTS MAY BE MEASURED RADIALLY
- 4. MINIMUM CLEARANCES BETWEEN LIVE WIRES OR FITTINGS AND OTHER FIXED INFRASTRUCTURE SHALL BE DETERMINED FROM NATIONAL ELECTRIC SAFETY CODE (N.E.S.C.) AND SHEET 104
- 5. VEHICLE DYNAMIC ENVELOPE DETERMINED FOR SUPERELEVATION = 0" FROM CLEARANCE REQUIREMENTS OF DESIGN CRITERIA
- 6. SUPERELEVATION OFFSET (OS) IS TO BE CONSIDERED WHEN MEASUREMENTS ARE TAKEN FROM VERTICAL TRACK CENTERLINE
- 7. COLLECTOR HEAD TILT TO BE CONSIDERED ONLY WHERE ALL IN-RUNNING CONTACT WIRES ARE STAGGERED TO THE FAR SIDE OF THE SUPERELEVATED VEHICLE CENTERLINE



MINIMUM VERTICAL CLEARANCE TO OBJECTS ABOVE THE TRACK FROM A PANTOGRAPH

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL
•					
•					
•	•	•	•		
•	•	•	•	-	
•	•	•	•	-	
•	-				
•	-	•		-	
•			•		

PRELIMINARY ENGINEERING





### **WEST-VOLUME 3 (SYSTEMS) OVERHEAD CONTACT SYSTEM - DETAILS** PANTOGRAPH CLEARANCE TO GROUNDED ITEMS

DISCIPI INF **SYSTEMS** 

OCS-DTL-104

SHEET

107


OF

	SEE NOTE 5				
AS-BUILT	DIN	MENSION	A INCHES		
CW HT	EMBEDDED	TRACK	BALLASTED TRACK		
22'-0"	62.1		64.3		
18'-6"	58.9		60.7		
16'-0"	56.5		58.0		
13'-10"	54.5		55.8		

SUPER ELEVATED VEHICLE DYNAMIC ENVELOPE

TRACK CONSTRUCTION


TABLE 2: CLEARANCE DIMENSIONS



### EXTRACT FROM PANTOGRAPH DYNAMIC ENVELOPE SEE NOTE 5

SUPERELEVATION CLEARANCE NO **TRACK** 9 CONS-CONSTRUCTION RUNNING AND OFFSET DUE TO MAINTENANCE SUPER OCS ENVELOPE ELEVATION=OS **TOLERANCE** EMBEDDED, (SEE TABLE 1) DIRECT FIXATION=0.5" BALLASTED DYNAMIC TRACK=2" SUPERELEVATED VEHICLE DYNAMICENVELOPE VEHICLE

MINIMUM HORIZONTAL CLEARANCE TO LIVE FITTINGS ON THE INSIDE OF CURVE FROM A PANTOGRAPH



MINIMUM HORIZONTAL CLEARANCE TO LIVE FITTINGS ON THE OUTSIDE OF CURVE FROM A PANTOGRAPH

#### NOTES:

- 1. THE DRAWING PROVIDES RELATIONSHIPS AND DIMENSIONS FOR DETERMINATION OF MINIMUM CLEARANCES BETWEEN A PANTOGRAPH AND ADJACENT LIVE OCS, FITTINGS, EXCEPTING FOR IN-RUNNING STEADY ARMS.
- 2. FOR THE PURPOSE OF DETERMINATION OF CLEARANCES TO A PANTOGRAPH, AN OCS FITTING SHALL BE CONSIDERED LIVE ONLY WHERE IT IS SEPARATED FROM GROUNDED POLES OR LIVE WIRING OF ADJACENT TRACKS, BY AT LEAST ONE LEVEL OF SYSTEM RATED INSULATION.
- FOR IN-RUNNING STEADY ARM, SEE SHEET 109
- CLEARANCES FOR OTHER LIVE OCS FITTINGS TO BE DETERMINED FROM THIS DRAWING
- ALL OTHER STRUCTURES, POLES OR EQUIPMENT REQUIRE CLEARANCES DETERMINED
- 3. FOR OBJECTS DIAGONALLY SEPARATED, BOTH HORIZONTAL AND VERTICAL CLEARANCES ARE TO BE APPLIED. RUNNING CLEARANCE COMPONENTS MAY BE MEASURED RADIALLY.
- 4. MINIMUM CLEARANCES BETWEEN LIVE WIRES OR FITTINGS AND OTHER FIXED INFRASTRUCTURE SHALL BE DETERMINED FROM NATIONAL ELECTRIC SAFETY CODE (N.E.S.C.) AND SHEET 104
- 5. VEHICLE DYNAMIC ENVELOPE DETERMINED FROM CLEARANCE REQUIREMENTS OF DESIGN
- 6. SUPERELEVATION OFFSET (OS) IS TO BE CONSIDERED WHEN MEASUREMENTS ARE TAKEN FROM VERTICAL TRACK CENTÉRLINE.
- 7. COLLECTOR HEAD TILT TO BE CONSIDERED ONLY WHERE ALL IN-RUNNING CONTACT WIRES ARE STAGGERED TO THE FAR SIDE OF THE SUPERELEVATED VEHICLE CENTERLINE.

PANTOGRAPH CLEARANCE ENVELOPE FOR DESIGN OF OCS LIVE FITTINGS LIVE FITTING CLEARANCE MAX PANTOGRAPH (RUNNING CLEARANCE) OPERATING HEIGHT CARBON COLLECTOR WEAR 0.75" MAX CONTACT WIRE HEIGHT DYNAMIC PANTOGRAPH 3.0" UPLIFT CONTACT WIRE WEAR 0.25" AS BUILT CONTACT WIRE HEIGHT 1" CONSTRUCTION TOLERANCE 0.5" DESIGNED CONTACT DESIGNED CONTACT WIRE HEIGHT UNDER WIRE HEIGHT - OPEN BRIDGE OR TUNNEL ROUTE

> MINIMUM VERTICAL CLEARANCE FROM A PANTOGRAPH TO LIVE FITTINGS

ı	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL
ı	•					
ı	•					
ı	•					
ı	•					
ı	•					
ı	•	•	•	•	-	
I	•	-			-	
ı					-	
ı						

PRELIMINARY ENGINEERING





**WEST-VOLUME 3 (SYSTEMS) OVERHEAD CONTACT SYSTEM - DETAILS** PANTOGRAPH CLEARANCE TO LIVE OCS FITTINGS

SHEET


108

OF

202

DISCIPI INF **SYSTEMS** 

OCS-DTL-105



	NO.	DAIL	BY	CHECK	DESIGN	REVISION / SUBMITTAL
ı						
ı						
ı						
ı						
ı						
ı						
ı						

CW LEVEL - STATIC CONDITIONS

AREA "M" SEE NOTE 5-

AECOM LTK LTK Engineering Services

PRELIMINARY ENGINEERING

-- PANTOGRAPH DYNAMIC ENVELOPE

TRACK WITH UP TO 6" SUPERELEVATION

SCALE: NOT TO SCALE



STAGGER



CW HEIGHT

└3" UPLIFTED CONTACT HEIGHT

NOTE:

# **WEST-VOLUME 3 (SYSTEMS) OVERHEAD CONTACT SYSTEM - DETAILS** STEADY ARM CLEARANCE SHAPES AND DIMENSIONS

SHEET

109

OF

202

DISCIPLINE:


**SYSTEMS** OCS-DTL-106

SIMPLE	CATENARY AU	TO-TENSIONED (SCAT)	
CONDUCTOR PARTICULARS	LINUTO	CONDUC	CTOR
(UNWORN CONDITION)	UNITS	CONTACT	MESSENGER
CONDUCTOR TYPE	-	350 KCMIL SOLID GROOVED	500 KCMIL 19 STRAND
MATERIAL	-	HARD DRAWN COPPER	HARD DRAWN COPPER
DIAMETER	IN	0.620	0.811
CROSS SECTIONAL AREA	SQ IN	0.2758	0.3926
WEIGHT OF CONDUCTOR	LB/FT	1.063	1.544
WEIGHT OF SYSTEM	LB/FT	2.654	
RADIAL THICKNESS OF ICE (0)	IN.	0.25	0.50
WEIGHT OF ICE (O)	LB/FT	0.270	0.815
WEIGHT OF SYSTEM WITH ICE (O)	LB/FT	3.739	)
RADIAL THICKNESS OF ICE (NO)	IN	0.50	0.50
WEIGHT OF ICE (NO)	LB/FT	0.696	0.815
WEIGHT OF SYSTEM WITH ICE (NO)	LB/FT	4.165	
CONDUCTOR BREAKING LOAD	LB	11810	21590
MAXIMUM SPAN	FT	22	20
CONDUCTOR TENSIONS AT:			
60°F NO WIND	LB	3000	5000
120°F NO WIND	LB	3000	5000
-40°F WIND & ICE (0)	LB	3962	6707
-40°F WIND & ICE (NO)	LB	4038	7052
CONDUCTOR SAG ON MAXIMUM SPAN AT:			
60°F NO WIND	FT	0	3.211
120°F NO WIND	FT	0	3.211
-40° NO WIND ICE (O)	FT	0.162	3.373
-40°F NO WIND ICE (NO)	FT	0.362	3.573
SYSTEM HEIGHT	FT	4.0 (NOR	MAL)
CONTACT WIRE HEIGHT AT 60°F	FT	18.50 (NOF	RMAL)
LOWER LIMIT OF AUTO TENSIONING	<b>°</b> F		20
UPPER LIMIT OF AUTO TENSIONING	<b>°</b> F	12	
MODULUS OF ELASTICITY	PSI	16x10 <sup>6</sup>	16x10 <sup>6</sup>
COEFFICIENT OF THERMAL EXPANSION	-/ <b>°</b> F	9.4x10 <sup>-6</sup>	9.4×10 <sup>-6</sup>
MINIMUM FACTOR OF SAFETY	_	2.92	3.06

SIMPLE CATENARY AUTO-TENSIONED (SCAT)									
CONDUCTOR PARTICULARS	UNITS	CONDUCTOR							
(WORN CONDITION)	UNITS	CONTACT	MESSENGER						
PERMISSIBLE WEAR	% OF AREA	30.00	_						
WEIGHT OF SYSTEM	LB/FT	2.335	j						
WEIGHT OF SYSTEM WITH ICE (O)	LB/FT	3.383							
WEIGHT OF SYSTEM WITH ICE (NO)	LB/FT	3.772	)						
CONDUCTOR TENSION AT:	_								
-40'F WIND & ICE (NO)	LB	3727	_						
CONDUCTOR BREAKING LOAD	LB	8267	_						
MINIMUM SAFETY FACTOR	_	2.22	- -						

### NOTE:

- 1. ICE (O) OPERATING CONDITION IS WITH 1/2" RADIAL ICE ON THE MESSENGER WIRE AND 1/4" RADIAL ICE ON THE CONTACT WIRE
- ICE (NO) NON OPERATING CONDITION IS WITH 1/2" RADIAL ICE ON BOTH MESSENGER & CONTACT WIRES
- 3. SYSTEM WEIGHTS SHOWN ARE FOR DESIGN PURPOSES AND CONSIST OF CONDUCTOR WEIGHTS PER FOOT, WHICH WERE TAKEN FROM MANUFACTURERS INFORMATION TABLES



THE ORIGINAL CROSS SECTIONAL AREA

NOOM!	LTK	
	LTK LTK Engineering Services	



WEST-VOLUME 3 (SYSTEMS)
<b>OVERHEAD CONTACT SYSTEM - DETAILS</b>
SCAT - CONDUCTOR
PARTICUL ARS

SHEET NAME: DISCIPLINE: **SYSTEMS** OCS-DTL-107

NO. DATE BY CHECK DESIGN REVISION / SUBMITTAL

SHEET 110 OF

202




TABLE 1: MAXIMUM MID-SPAN STATIC OFFSET

MAXIMUM CONSTRUCTED SPAN - CURVED TRACK

18'-6" CONTACT WIRE HEIGHT

STATIC

OFFSET [IN]

14.880

14.780

14.640

14.460

14.240

13.980

13.680

13.340

12.960

12.540

12.080

11.580

11.040

10.460

9.840

9.180

8.480

7.740

6.960

6.140

5.280

BLOW-OFF

[FT]

0.007

0.015

0.027

0.042

0.060

0.082

0.107

0.135

0.167

0.202

0.240

0.282

0.327

0.375

0.427

0.482

0.540

0.602

0.667

0.735

0.807

MIN. CURVE

RADIUS [FT]

22

50

90

142

206

283

374

479

601

740

897

1075

1276

1503

1758

2047

2373

2743

3165 3647

4201

MAX

26.880

26.640

26.460

26.240

25.980

25.680

25.340

24.960

24.540

24.080

23.580

23.040

22.460

21.840

21.180

20.480

19.740

18.960

18.140

17.280

VERSINE [IN]

SPAN [FT]

20

30

40

50

60

70

80

90

100

110

120

130

140

150

160

170

180

190

200

210

220

### NOTES:

- 1. MAXIMUM STRUCTURE SPACINGS FOR SPANS WHOLLY OVER CONSTANT RADIUS TRACK CURVE, ARE TO BE DETERMINED FROM THE GRAPHS AND RELATED NOTES. FOR ALL OTHER HORIZONTAL ALIGNMENT COMBINATIONS, SPACING MUST SATISFY MAXIMUM STATIC MIDSPAN OFFSET CRITERIA APPLIED TO STAGGERED CONTACT WIRE.
- 2. THE MAXIMUM STATIC MIDSPAN OFFSET IS THE VALUE THE CONTACT WIRE CAN BE FROM THE CENTER LINE OF A STATIC PANTOGRAPH UNDER STILL AIR CONDITIONS MEASURED AT MID-SPAN.
- 3. WHERE AS-BUILT STATIC MIDSPAN OFFSET EXCEEDS THE MAXIMUM VALUE LISTED IN TABLE 1, FURTHER CONSTRUCTION MAY ONLY CONTINUE AFTER SITE SPECIFIC
- 4. THE SPACINGS SHOWN ARE THE ABSOLUTE MAXIMUM FOR EACH CONTACT WIRE HEIGHT AND TRACK TYPE CONDITION. FOR DESIGN PURPOSES THE MAXIMUM SPAN SHALL BE REDUCED BY 5 FEET TO CATER FOR SITE ADJUSTMENTS IF OBSTRUCTIONS ARE ENCOUNTERED.
- 5. MAXIMUM CONTACT WIRE STAGGER = 9".
- 6. INSTALLED CONTACT WIRE SPANS MAY BE ACCEPTED WITH 1 INCH OF ADDITIONAL MIDSPAN OFFSET CONSTRUCTION TOLERANCE ABOVE THE MAXIMUM VALUES LISTED.
- 7. THE CONDITIONS FOR THE STRUCTURE SPACING CHART AND THE TABLES ARE 60° F WITH A WIND SPEED OF 55

MIN. RADIUS OF CURVATURE (FEET)

MAXIMUM STRUCTURE SPACING

SEE NOTE 4

NO. DATE BY CHECK DESIGN REVISION / SUBMITTAL

AECOM LTK LTK Engineering Services





**WEST-VOLUME 3 (SYSTEMS) OVERHEAD CONTACT SYSTEM - DETAILS SCAT - STRUCTURE SPACING** 

SHEET

111

OF

202

PRELIMINARY ENGINEERING

**SYSTEMS** 

DISCIPLINE

OCS-DTL-108

- (VE) INDICATES MOVEMENT TOWARD MID POINT ANCHOR

+ (VE) INDICATES MOVEMENT AWAY FROM MID POINT ANCHOR


ALONG TRACK MOVEMENT IS IN INCHES

## ALONG TRACK MOVEMENT - AUTO-TENSIONED O.C.S.

ALONG TRACK MOVEMENT [IN]				(	CANTILEV	ÆR REA	CH (DIM	ENSION	R FEET-	-INCHES]	)			
[114]	6'-0"	6'-6"	7'-0"	7'-6"	8'-0"	8'-6"	9'-0"	9'-6"	10'-0"	10'-6"	11'-0"	11'-6"	12'-0"	12'-6"
2	0.03	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.01	0.01	0.01
4	0.11	0.10	0.10	0.09	0.08	0.08	0.07	0.07	0.07	0.06	0.06	0.06	0.06	0.05
6	0.25	0.23	0.21	0.20	0.19	0.18	0.17	0.16	0.15	0.14	0.14	0.13	0.13	0.12
8	0.45	0.41	0.38	0.36	0.33	0.31	0.30	0.28	0.27	0.25	0.24	0.23	0.22	0.21
10	0.70	0.64	0.60	0.56	0.52	0.49	0.46	0.44	0.42	0.40	0.38	0.36	0.35	0.33
12	1.01	0.93	0.86	0.80	0.75	0.71	0.67	0.63	0.60	0.57	0.55	0.52	0.50	0.48
14	1.37	1.27	1.17	1.10	1.03	0.97	0.91	0.86	0.82	0.78	0.74	0.71	0.68	0.65
16	1.80	1.66	1.54	1.43	1.34	1.26	1.19	1.13	1.07	1.02	0.97	0.93	0.89	0.86
18	2.29	2.11	1.95	1.82	1.70	1.60	1.51	1.43	1.36	1.29	1.23	1.18	1.13	1.08
20	2.83	2.61	2.42	2.25	2.11	1.98	1.87	1.77	1.68	1.60	1.52	1.46	1.40	1.34
22	3.44	3.17	2.93	2.73	2.55	2.40	2.26	2.14	2.03	1.94	1.85	1.76	1.69	1.62
24	4.12	3.78	3.50	3.26	3.05	2.86	2.70	2.55	2.42	2.31	2.20	2.10	2.01	1.93

# STAGGER CHANGE - AUTO-TENSIONED O.C.S.

STAGGER CHANGE VALUES IN INCHES



M=ALONG TRACK MOVEMENT

X=STAGGER CHANGE

R=DISTANCE FROM FACE OF POLE TO CONDUCTOR

 $M = \sim LT$ 

L = DISTANCE FROM MID POINT ANCHOR

T = TEMPERATURE RANGE


 $X=R-\sqrt{R^2-M^2}$ 

WHERE R=CANTILEVER REACH M=ALONG TRACK MOVEMENT

B-V	STAGGER DIFFERENCE(S) [IN]											
[IN]	2	4	6	8	10	12	14	16	18			
2	0.13	0.50	1.13	2.00	3.13	4.50	6.13	8.00	10.13			
4	0.06	0.25	0.56	1.00	1.56	2.25	3.06	4.00	5.06			
6	0.04	0.17	0.38	0.67	1.04	1.50	2.04	2.67	3.38			
8	0.03	0.13	0.28	0.50	0.78	1.13	1.53	2.00	2.53			
10	0.03	0.10	0.23	0.40	0.63	0.90	1.23	1.60	2.03			
12	0.02	0.08	0.19	0.33	0.52	0.75	1.02	1.33	1.69			
14	0.02	0.07	0.16	0.29	0.45	0.64	0.88	1.14	1.45			
16	0.02	0.06	0.14	0.25	0.39	0.56	0.77	1.00	1.27			
18	0.01	0.06	0.13	0.22	0.35	0.50	0.68	0.89	1.13			
20	0.01	0.05	0.11	0.20	0.31	0.45	0.61	0.80	1.01			

# STAGGER EFFECT - ALL O.C.S. STYLES

STAGGER EFFECT VALUES IN INCHES



S = STAGGER DIFFERENCE

S1 & S2 = STAGGER AT EACH SUPPORT

V = VERSINE OF CURVE BETWEEN SUPPORTS

P = CONTACT WIRE MIDSPAN OFFSET

B = CONTACT WIRE BLOW OFF

E = STAGGER EFFECT

STAGGER DIFFERENCE (S) = S1-S2

STAGGER EFFECT (E) =

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL
				l	

AECOM LTK Engineering Services

PRELIMINARY ENGINEERING





**WEST-VOLUME 3 (SYSTEMS) OVERHEAD CONTACT SYSTEM - DETAILS SCAT - RISE & FALL AND** ALONG TRACK MOVEMENT

OCS-DTL-109

SHEET

112

OF

202

DISCIPI INF **SYSTEMS** 




# € SUPPORT

# € SUPPORT € SUPPORT € SUPPORT "L<sub>2</sub>" SPAN STAGGER

RADIAL LOAD (R) AT SUPPORT  $R = R_1 + R_2 \\ \text{RADIAL LOAD IS BASED ON 9" STAGGER AT SUPPORTS}$ 

### NOTE:

1. L = SUM OF THE DISTANCE TO THE LOW POINT OF THE MESSENGER WIRE ON BOTH SIDES OF THE SUPPORT



TO DETERMINE RADIAL LOAD, MEASURE ANGLE 0 AND USE TABLE TO DETERMINE LOAD FOR CONDITION REQUIRED.

# VERTICAL LOADING

	SPAN		TION AND LOAD LUE (V) (LB)		
	(FEET)	BARE	ICE (NO)	ICE (O)	
Γ	40	106.16	166.60	149.56	
Γ	50	132.70	208.25	186.95	
Γ	60	159.24	249.90	224.34	
	70	185.78	291.55	261.73	
	80	212.32	333.20	299.12	
	90	238.86	374.85	336.51	
	100	265.40	416.50	373.90	
	110	291.94	458.15	411.29	
	120	318.48	499.80	448.68	
	130	345.02	541.45	486.07	
	140	371.56	583.10	523.46	
	150	398.10	624.75	560.85	
	160	424.64	666.40	598.24	
	170	451.18	708.05	635.63	
	180	477.72	749.70	673.02	
	190	504.26	791.35	710.41	
	200	530.80	833.00	747.80	
	210	557.34	841.64	785.19	
	220	583.88	916.30	822.58	

# WIND LOADING

		CON	DITION A	ND FORCE	(WIND LOADING) (LB)				
	BARE	WIRE	BARE	WIRE	1/2'	'ICE	1/2"	1/2" ICE MW	
SPAN (FFFT)	90 MPI	H WIND	55 MPH WIND		MW a	& CW	1/4" ICE CW		
(FEET)	(N,	/0)	((	O)	40 MP	H WIND	40 MP	H WIND	
	` ′	,	,	,	(N	/0)	((	O)	
	CW	MW	CW	MW	CW	MW	CW	MW	
40	42.8	56.0	16.0	20.8	22.0	24.8	15.2	24.8	
50	553.5	70.0	20.0	26.0	27.5	31.0	19.0	31.0	
60	64.2	84.0	24.0	31.2	33.0	37.2	22.8	37.2	
70	74.9	98.0	28.0	36.4	38.5	43.4	26.6	43.4	
80	85.6	112.0	32.0	41.6	44.0	49.6	30.4	49.6	
90	96.3	126.0	36.0	46.8	49.5	55.8	34.2	55.8	
100	107.0	140.0	40.0	52.0	55.0	62.0	38.0	62.0	
110	117.7	154.0	44.0	57.2	60.5	68.2	41.8	68.2	
120	128.4	168.0	48.0	62.4	66.0	74.4	45.6	74.4	
130	139.1	182.0	52.0	67.6	71.5	80.6	49.4	80.6	
140	149.8	196.0	56.0	72.8	77.0	86.8	53.2	86.8	
150	160.5	210.0	60.0	78.0	82.5	93.0	57.0	93.0	
160	171.2	224.0	64.0	83.2	88.0	99.2	60.8	99.2	
170	181.9	238.0	68.0	88.4	93.5	105.4	64.6	105.4	
180	192.6	252.0	72.0	93.6	99.0	111.6	68.4	111.6	
190	203.3	266.0	76.0	98.8	104.5	117.8	72.2	117.8	
200	214.0	280.0	80.0	104.0	110.0	124.0	76.0	124.0	
210	224.7	294.0	84.0	109.2	115.5	130.2	79.8	130.2	
220	235.4	308.0	88.0	114.4	121.0	136.4	83.6	136.4	

# RADIAL LOAD TANGENT TRACK

	CON	NOITID	ID RADIAL LOAD (LB) (R1 AND R2)				
SPAN	60	) <b>°</b> F	OPERATI	NG 40°F	NON-OPERATING		
(FEET)	NO	WIND	40	MPH	-40°F,	40 MPH	
(1 == 1)	NO ICE	NO ICE	1/4" ICE	1/2" ICE	1/2" ICE	1/2" ICE	
	CW	MW	CW	MW	CW	MW	
40	224.84	374.74	296.94	502.67	302.64	528.53	
50	179.92	299.87	237.61	402.24	242.17	422.93	
60	149.95	249.92	198.04	335.25	201.84	352.49	
70	128.54	214.24	169.76	287.38	173.02	302.16	
80	112.48	187.47	148.55	251.47	151.40	264.40	
90	99.99	166.64	132.05	223.54	134.58	235.03	
100	89.99	149.98	118.85	201.19	121.13	211.54	
110	81.81	136.35	108.04	182.90	110.12	192.31	
120	74.99	124.99	99.04	167.66	100.94	176.29	
130	69.23	115.38	91.42	154.77	93.18	162.73	
140	64.28	107.14	84.90	143.71	86.52	151.11	
150	60.00	100.00	79.24	134.13	80.76	141.03	
160	56.25	93.75	74.28	125.75	75.71	132.22	
170	52.94	88.23	69.91	118.35	71.26	124.44	
180	50.00	83.33	66.03	111.78	67.30	117.53	
190	47.37	78.94	62.56	105.90	63.76	111.34	
200	45.00	75.00	59.43	100.60	60.57	105.78	
210	42.86	71.43	56.60	95.81	57.68	100.74	
220	40.91	68.18	54.03	91.46	55.06	96.16	

# RADIAL LOAD BY ANGLE

		CONDI	TION AND RADIAL LOAD (LB)					
ANGLE	60	)°F	OPERATI	NG 40°F	NON-OF	PERATING		
(DEGREES)	NO	WIND	40	MPH	-40°F, 40 MPH			
Θ	NO ICE	NO ICE	1/4" ICE	1/2" ICE	1/2" ICE	1/2" ICE		
	CW	MW	CW	MW	CW	MW		
0.5	26.18	43.63	34.57	58.53	35.24	61.54		
1	52.36	87.27	69.14	117.06	70.48	123.08		
1.5	78.54	130.90	103.72	175.58	105.71	184.62		
2	104.71	174.52	138.29	234.11	140.95	246.15		
2.5	130.89	218.15	172.86	292.62	176.18	307.68		
3	157.06	261.77	207.43	351.14	211.41	369.20		
4	209.40	348.99	276.54	468.14	281.85	492.22		
5	261.72	436.19	345.64	585.11	352.27	615.21		
6	314.02	523.36	414.71	702.03	422.67	738.15		
7	366.29	610.49	483.75	818.91	493.03	861.03		
8	418.54	697.56	552.75	935.71	563.35	983.85		
9	470.75	784.59	621.71	1052.45	633.64	1106.59		
10	522.93	871.56	690.62	1169.11	703.87	1229.24		
11	575.07	958.46	759.48	1285.67	774.05	1351.81		
12	627.17	1045.28	828.28	1402.14	844.17	1474.27		
13	679.22	1132.03	897.02	1518.51	914.23	1596.62		
14	731.22	1218.69	965.69	1634.76	984.22	1718.85		
15	783.16	1305.26	1034.29	1750.88	1054.13	1840.94		

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL

PRELIMINARY ENGINEERING





# **WEST-VOLUME 3 (SYSTEMS) OVERHEAD CONTACT SYSTEM - DETAILS SCAT - VERTICAL WIND** & RADIAL LOADS

DISCIPLINE: **SYSTEMS** 

OCS-DTL-110


SHEET

113

OF


SINGLE WRE FIXED TERMINATED (SWFT)							
CONDUCTOR PARTICULARS	UNITS	CONDUCTOR					
(UNWORN CONDITION)		CONTACT					
CONDUCTOR TYPE	_	350 MCM SOLID GROOVED					
MATERIAL	_	HARD DRAWN COPPER					
DIAMETER	IN	0.620					
CROSS SECTIONAL AREA	SQ IN	0.2758					
WEIGHT OF CONDUCTOR	LB/FT	1.063					
WEIGHT OF SYSTEM	LB/FT	1.063					
RADIAL THICKNESS OF ICE (O)	IN	0.25					
WEIGHT OF ICE (O)	LB/FT	0.270					
WEIGHT OF SYSTEM WITH ICE (O)	LB/FT	1.333					
RADIAL THICKNESS OF ICE (NO)	IN.	0.50					
WEIGHT OF ICE (NO)	LB/FT	0.696					
WEIGHT OF SYSTEM WITH ICE (NO)	LB/FT	1.759					
CONDUCTOR BREAKING LOAD	LB	11810					
MAXIMUM CONSTRUCTED SPAN	FT	80					
CONDUCTOR TENSIONS AT:	_						
60°F NO WIND	LB	1750					
165°F NO WIND	LB	604					
-40°F 40 MPH WIND & ICE (0)	LB	5538					
-40°F 40 MPH WIND & ICE (NO)	LB	5592					
CONDUCTOR SAG (80 FT SPAN) AT:							
60°F NO WIND	FT	0.486					
-40°F NO WIND ICE (O)	FT	0.193					
120'F NO WIND	FT	1.040					
CONDUCTOR HEIGHT AT 60°F	FT	19'-0" @ SUPPORT (NORMAL)					
MODULUS OF ELASTICITY	PSI	16 X 10 <sup>6</sup>					
COEFFICIENT OF EXPANSION	-/° F	9.4 X 10 <sup>-6</sup>					
MINIMUM FACTOR OF SAFETY	_	2.11					

CONDUCTOR PARTICULARS	UNITS	CONDUCTOR
(WORN CONDITION)	UNITS	CONTACT
PERMISSIBLE WEAR	% OF AREA	30.00
WEIGHT OF CONTACT WIRE	LB/FT	0.7441
WEIGHT OF CONTACT WIRE WITH ICE (O)	LB/FT	0.977
WEIGHT OF CONTACT WIRE WITH ICE (NO)	LB/FT	1.366
CONDUCTOR TENSION AT:		
-40°F 40 MPH WIND & ICE (NO)	LB	3938
CONDUCTOR BREAKING LOAD	LB	8260
MINIMUM FACTOR OF SAFETY	_	2.10



### NOTE:

- 1. OPERATING (O) ICE CONDITION IS WITH 1/4" RADIAL ICE ON THE CONTACT
- 2. NON OPERATING (NO) ICE CONDITION IS WITH 1/2" RADIAL ICE ON CONTACT WIRE
- 3. SYSTEM WEIGHTS SHOWN ARE FOR DESIGN PURPOSES AND CONSIST OF CONDUCTOR WEIGHTS PER FOOT, WHICH WERE TAKEN FROM MANUFACTURERS INFORMATION TABLES
- 4. PERMISSIBLE WEAR IS 30% OF THE ORIGINAL CROSS SECTIONAL AREA



AECOM LTK Engineering Services





**WEST-VOLUME 3 (SYSTEMS) OVERHEAD CONTACT SYSTEM - DETAILS SWFT - CONDUCTOR PARTICULARS** 

OF 202


SHEET

114

PRELIMINARY ENGINEERING

DISCIPLINE: **SYSTEMS** 

OCS-DTL-112



MIN. RADIUS OF CURVATURE (FEET)

# MAXIMUM STRUCTURE SPACING

NO. DATE BY CHECK DESIGN REVISION / SUBMITTAL

AECOM LTK LTK Engineering Services

PRELIMINARY ENGINEERING





# **WEST-VOLUME 3 (SYSTEMS) OVERHEAD CONTACT SYSTEM - DETAILS SWFT - STRUCTURE**

**SPACING** 

DISCIPLINE **SYSTEMS** OCS-DTL-113

NOTES:

- 1. MAXIMUM STRUCTURE SPACINGS FOR SPANS WHOLLY OVER CONSTANT RADIUS TRACK CURVE, ARE TO BE DETERMINED FROM THE GRAPHS AND RELATED NOTES. FOR ALL OTHER HORIZONTAL ALIGNMENT COMBINATIONS, SPACING MUST SATISFY MAXIMUM STATIC MIDSPAN OFFSET CRITERIA APPLIED TO STAGGERED CONTACT WIRE.
- 2. THE MAXIMUM STATIC MIDSPAN OFFSET IS THE VALUE THE CONTACT WIRE CAN BE FROM THE CENTER LINE OF A STATIC PANTOGRAPH UNDER STILL AIR CONDITIONS MEASURED AT MID-SPAN.
- 3. WHERE AS-BUILT STATIC MIDSPAN OFFSET EXCEEDS THE MAXIMUM VALUE LISTED IN TABLE 1, FURTHER CONSTRUCTION MAY ONLY CONTINUE AFTER SITE SPECIFIC APPROVAL.
- 4. THE SPACINGS SHOWN ARE THE ABSOLUTE MAXIMUM FOR EACH CONTACT WIRE HEIGHT AND TRACK TYPE CONDITION. FOR DESIGN PURPOSES THE MAXIMUM SPAN SHALL BE REDUCED BY 5 FEET TO CATER FOR SITE ADJUSTMENTS IF OBSTRUCTIONS ARE ENCOUNTERED.
- 5. MAXIMUM CONTACT WIRE STAGGER = 9",
- 6. INSTALLED CONTACT WIRE SPANS MAY BE ACCEPTED WITH 1 INCH OF ADDITIONAL MIDSPAN OFFSET CONSTRUCTION TOLERANCE ABOVE THE MAXIMUM VALUES LISTED.
- 7. THE CONDITIONS FOR THE STRUCTURE SPACING CHART AND THE TABLES ARE 60' F WITH A WIND SPEED OF 55 MPH.

TABLE1: MAXIMUM MID-SPAN STATIC OFFSET

MAXIMUM CONSTRUCTED SPAN - CURVED TRACK

19'-0" CONTACT WIRE HEIGHT

STATIC

14.403

14.326

14.231

14.120

13.991

13.846

13.683

13.503

13.306

13.091

12.860

12.611

12.346

VERSINE [IN] OFFSET [IN]

27.903

27.826

27.731

27.620

27.346

27.183

27.003

26.806

26.591

26.360

26.111

25.846

SPAN [FT]

20

25

30

35

40

45

50

55

60

65

70

75

80

BLOW-OFF | MIN. CURVE

[FT]

0.011

0.018

0.026

0.035

0.046

0.058

0.071

0.086

0.103

0.121

0.140

0.161

0.183

RADIUS [FT]

22

34

49

67

87

111

138

168

201

238

279

323


371

115 OF


202


SHEET

1. L = SUM OF THE DISTANCE TO THE LOW POINT OF THE CONTACT WIRE ON BOTH SIDES OF THE SUPPORT.




V = VERTICAL LOAD





RADIAL LOAD (R) AT SUPPORT  $R = R_1 + R_2$  RADIAL LOAD IS BASED ON 9" STAGGER AT SUPPORTS



TO DETERMINE RADIAL LOAD, MEASURE ANGLE 0 AND USE TABLE TO DETERMINE LOAD FOR CONDITION REQUIRED.

# VERTICAL LOADING

SPAN (FEET)	CONDITION AND LOAD VALUE (V) (LB)					
( (   (	BARE	ICE (NO)	ICE (O)			
20	21.26	35.18	26.66			
25	26.58	43.98	33.33			
30	31.89	52.77	39.99			
35	37.21	61.57	46.66			
40	42.52	70.36	53.32			
45	47.84	79.16	59.99			
50	53.15	87.95	66.65			
55	58.47	96.75	73.32			
60	63.78	105.54	79.98			
65	69.10	114.34	86.65			
70	74.41	123.13	93.31			
75	79.73	131.93	99.98			
80	85.04	140.72	106.64			

# WIND LOADING

	CONDITION AND FORCE (WIND LOADING) (LB)									
SPAN (FEET)	BARE WIRE	NO ICE	1/2" ICE	1/4" ICE						
(	90 MPH WIND	55 MPH WIND	40 MPH WIND	40 MPH WIND						
	(N/O)	(0)	(N/O)	(0)						
20	21.4	8.0	11.0	7.6						
25	26.8	10.0	13.8	9.5						
30	32.1	12.0 16.5		11.4						
35	37.5	14.0	19.3	13.3						
40	42.8	16.0	22.0	15.2						
45	48.2	18.0	24.8	17.1						
50	53.5	20.0	27.5	19.0						
55	58.9	22.0	30.3	20.9						
60	64.2	24.0	33.0	22.8						
65	69.6	26.0	35.8	24.7						
70	74.9	28.0	38.5	26.6						
75	80.3	30.0	41.3	28.5						
80	85.6	32.0	44.0	30.4						

# RADIAL LOAD TANGENT TRACK

	CONDITION	AND RADIAL LOAD	(LB) (R1 AND R2)
SPAN	60 <b>°</b> F	OPERATING 40°F	NON-OPERATING
(FEET)	NO WIND	40 MPH WIND	-40°F, 40 MPH WIND
	NO ICE	1/4" ICE	1/2" ICE
20	261.76	828.37	836.45
25	209.62	663.37	669.84
30	174.78	553.11	558.50
35	149.86	474.25	478.87
40	131.16	415.06	419.11
45	116.60	369.00	372.59
50	104.95	332.13	335.37
55	95.42	301.96	304.90
60	87.47	276.81	279.51
65	80.75	255.53	258.02
70	74.98	237.29	239.60
75	69.99	221.48	223.64
80	65.61	207.64	209.66

# RADIAL LOAD BY ANGLE

ANGLE	CONDITION AND RADIAL LOAD (LB)					
(DEGREES) Θ	60°F NO WIND	OPERATING 40°F 40 MPH	NON-OPERATING -40°F, 40 MPH			
	NO ICE	1/4" ICE	1/2" ICE			
0.5	15.27	48.33	48.80			
1	30.54	96.66	97.60			
1.5	45.81	144.98	146.39			
2	61.08	193.30	195.19			
2.5	76.35	241.62	243.98			
3	91.62	289.94	292.76			
4	122.15	386.55	390.32			
5	152.67	483.13	487.84			
6	183.18	579.67	585.33			
7	213.67	676.17	682.77			
8	244.15	772.62	780.16			
9	274.61	869.01	877.49			
10	305.05	965.34	974.75			
11	335.46	1061.59	1071.94			
12	365.85	1157.76	1169.05			
13	396.21	1253.84	1266.06			
14	426.54	1349.82	1362.99			
15	456.84	1445.71	1459.80			

:	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL
١.						

PRELIMINARY ENGINEERING





**WEST-VOLUME 3 (SYSTEMS) OVERHEAD CONTACT SYSTEM - DETAILS SWFT - VERTICAL WIND** & RADIAL LOADS


SHEET

116

OF

202

DISCIPLINE: **SYSTEMS** OCS-DTL-114



シー							
.	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	
5							1
2							
j							
٠							
2							
,							
,							





	WEST-VOLUME 3 (SYSTEMS)
	OVERHEAD CONTACT SYSTEM
•	TYPICAL ARRANGEMENTS AND ASSEMBLIES
	SCAT STRUCTURE-CENTER POLE
	DISCIPLINE: SHEET NAME:


SYSTEMS

202 OCS-TAA-003

SHEET

117

OF



ンコ							
:	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	
ā							1
23							
:i							
4							
701							
97							
Jun,							






WEST-VOLUME 3 (SYSTEMS)	SHEET
OVERHEAD CONTACT SYSTEM	118
TYPICAL ARRANGEMENTS AND ASSEMBLIES	05
SCAT STRUCTURE-SIDE POLE	OF

202

DISCIPLINE: SYSTEMS OCS-TAA-004



AECOM LTK LTK Engineering Services





WEST-VOLUME 3 (SYSTEMS)
OVERHEAD CONTACT SYSTEM
TYPICAL ARRANGEMENTS AND ASSEMBLIES
SCAT HEADSPAN

OCS-TAA-005

SHEET


119

OF

202

PRELIMINARY ENGINEERING

DISCIPLINE: SYSTEMS



140.	DAIL	 OHLOR	DEGIGIT	REVIOION / CODMITTAL






**WEST-VOLUME 3 (SYSTEMS) OVERHEAD CONTACT SYSTEM** TYPICAL ARRANGEMENTS AND ASSEMBLIES **SWFT PULL-OFF & PUSH-OFF STRUCTURE** 

OF 202 OCS-TAA-006

SHEET

120

SYSTEMS



TUNNEL SUPPORT ASSEMBLY

	NO.	DAIL	Bī	CHECK	DESIGN	REVISION / SUBMITTAL
ı						
ı						
ı						
ı						
ı						
ı						
ı						
ı						
ı						





WEST-VOLUME 3 (SYSTEMS)
OVERHEAD CONTACT SYSTEM
TYPICAL ARRANGEMENTS AND ASSEMBLIES
SCAT BRIDGE & TUNNEL ATTACHMENT


202 OCS-TAA-007

SHEET

PRELIMINARY ENGINEERING

121 OF

DISCIPLINE: SYSTEMS







WEST-VOLUME 3 (SYSTEMS)
OVERHEAD CONTACT SYSTEM
TYPICAL ARRANGEMENTS AND ASSEMBLIES
SCAT SCISSORS CROSSOVER

**SYSTEMS** 


OCS-TAA-009


PRELIMINARY ENGINEERING


SHEET

122

OF







H' = ADJUSTED HANGER LENGTH (IN) HS = NORMAL HANGER LENGTH (IN) AS = STANDARD SYSTEM HEIGHT (IN)AL, AR = ADJUSTED SYSTEM HEIGHT (IN) X = DISTANCE TO HANGER (FT)L = SPAN LENGTH (FT)

ADJUSTMENTS FOR NON-STANDARD SYSTEM HEIGHTS






**WEST-VOLUME 3 (SYSTEMS) OVERHEAD CONTACT SYSTEM** TYPICAL ARRANGEMENTS AND ASSEMBLIES SIMPLE CATENARY SPAN DISCIPLINE:


**SYSTEMS** OCS-TAA-011


SHEET


124


OF














AECOM LTK Engine





**WEST-VOLUME 3 (SYSTEMS) OVERHEAD CONTACT SYSTEM MASTER OVERLAP CHART** STA. 2416+31 TO STA. 2450+21.71


130 OF


202

SHEET

DISCIPLINE: **SYSTEMS** 

OCS-MOC-304





NAME	ASPECT	ASPECT	INDICATION
DIVERGING APPROACH	RED OVER FLASHING YELLOW	• - - - - - -	PROCEED ON DIVERGING ROUTE AT PRESCRIBED SPEED THROUGH TURNOUT. BE PREPARED TO STOP AT NEXT SIGNAL / ENTER DARK TERRITORY.  (SEE NOTE 1)
DIVERGING RESTRICTING	RED OVER FLASHING LUNAR		PROCEED ON DIVERGING ROUTE AT RESTRICTED SPEED THROUGH TURNOUT, ENTER EITHER AN OCCUPIED BLOCK OR YARD LIMITS  (SEE NOTE 1)
RESTRICTING	LUNAR		PROCEED AT RESTRICTED SPEED INTO AN OCCUPIED BLOCK, WITHIN YARD LIMITS
VERTICAL BAR	LUNAR VERTICAL BAR	1	PROCEED THROUGH ROADWAY INTERSECTION
FLASHING VERTICAL BAR	LUNAR FLASHING VERTICAL BAR		PREPARE TO STOP AT INTERSECTION LIMIT
HORIZONTAL BAR	LUNAR HORIZONTAL BAR		STOP AT INTERSECTION LIMIT
FLASHING HORIZONTAL BAR	LUNAR FLASHING HORIZONTAL BAR	<b>*</b>	STOP. THE OPERATOR WILL SOUND TWO SHORT BLASTS OF HORN PRIOR TO MOWNG, REGARDLESS OF ANY HORN PROHIBITION. WHEN IT IS TRAINS TURN, PROCEED SLOWLY IN THE INTERSECTION UNTIL THE TRAIN FULLY OCCUPIES THE CROSSING, RING BELL CONTINUOUSLY THROUGH THE ENTIRE CROSSING.  INDICATES A FOUR—WAY STOP.  THE FIRST TRAIN TO ENCOUNTER SHOULD NOTIFY THE RCC.

- 1. WHERE PROVIDED, SIGNALS WITH MULTIPLE ASPECTS AND MULTIPLE DIVERGING DESTINATIONS WILL HAVE AN LED NUMBER INDICATOR ATTACHED TO PROVIDE ADDITIONAL DESTINATION INFORMATION.
- 2. HEAVY LINE INDICATES DISPLAY WITH SYSTEM AT REST.
- 3. FLASHING SIGNAL DISPLAY SHOWN BY DASHED LINE.
- 4. STEADY SIGNAL DISPLAY SHOWN BY SOLID LINE.


LEGEND:							
$\infty$	TRAIN TO WAYSIDE LOOP (TWC)	ABBREVIATIONS:					
	XING BELL (DC)	MPH E1-201	MILES PER HOUR  EAST SEGMENT 1, TRACK 2 CURVE #1 (PER CIVIL PLAN)				
+	IMPEDANCE BOND (SINGLE)	VC	VERTICAL CURVE UPGRADE GOING EAST				
1T	TRACK CIRCUIT LEADS	0.6%	DOWNGRADE GOING EAST GRADE PERCENTAGE				
	TRACK CIRCUIT JUMPER	AVG TBD	AVERAGE TO BE DETERMINED				
	NEGATIVE RETURN JUMPER	XING	CROSSING				
⊏.	POWER OPERATED SWITCH MACHINE (DUAL CONTROLLED)						
	SNOW MELTER CASE (HS)						
	SIGNAL BUNGALOW/PLATFORM HOUSE 10	)' X 30'					
	CROSSING HOUSE (6' X 8' TYP)						
STATION	STATION PLATFORM						
<del></del>	INSULATED JOINT						
	SIGNAL RAIL (DOUBLE LINE TRACK PLAN	1)					
	NEGATIVE RETURN RAIL (DOUBLE LINE T	RACK PLAN)					
	GRADE CROSSING GATE AND FLASHERS						
1E   <del></del>	TRACK 1 EASTBOUND INTERLOCKING SIG	NAL (COLOR	LIGHT)				
1W  —	TRACK 1 WESTBOUND INTERLOCKING SIG	NAL (COLOR	LIGHT)				
2541E —	TRACK 1 EASTBOUND AUTOMATIC SIGNA STATIONING 2540+XX (TRK 1 - ODD NU	L (COLOR LIG JMBER)	БНТ)				
2540W —	TRACK 2 WESTBOUND AUTOMATIC SIGNA STATIONING 2540+XX (TRK 2 - EVEN N		GHT)				
	HIGHWAY GRADE CROSSING						



OVERLAY TRACK CIRCUIT



PEDESTRIAN FLASHERS WITH SECOND TRAIN WARNING



PARSONS BRINCKERHOFF





# **WEST-VOLUME 3 (SYSTEMS) SIGNAL SYSTEM GENERAL**

SYMBOLS, LEGEND AND GENERAL NOTES

**SYSTEMS** 


OF 202

SHEET

PRELIMINARY ENGINEERING

SIG-GEN-001

# INTERLOCKING SIGNAL (COLOR LIGHT)



# SYMBOLS:

 $\infty$ TRAIN TO WAYSIDE LOOP (TWC)

 $\Box$ TRAIN

STATION STATION PLATFORM

INSULATED JOINT

HIGHWAY GRADE CROSSING

# SIGNAL ASPECTS:

GREEN (CLEAR) FLASHING YELLOW

YELLOW (APPROACH)

(APPROACH DIVERGING)

RED (STOP)

LUNAR (RESTRICTING)

RED OVER FLASHING GREEN (DIVERGING CLEAR)

RED OVER FLASHING YELLOW (DIVERGING APPROACH) R/FY

RED OVER FLASHING LUNAR (DIVERGING RESTRICTING)

TRACK CC	DE ASSIGNMENT OF ELECTRONIC TRACK CIRCUITS
TRACK CODE	ASSIGNMENT
C1	TRACK CIRCUIT - DETECTION CODE
C2	APPROACH ASPECT CONTROL CODE
C3	NOT USED
C4	APPROACH DIVERGING CONTROL CODE
C5	NON VITAL MULTIPURPOSE CODE
C6	TRAFFIC TUMBLE DOWN CODE INITIATED WHEN ROUTE ESTABLISHED AT INTERLOCKING
C7	CLEAR ASPECT CONTROL CODE
C8	NOT USED

# AUTOMATIC SIGNAL (COLOR LIGHT)



# ABBREVIATIONS:

MPH

XING

2500+00	STATIONING
XXXX E	EASTWARD SIGNAL NUMBER
XXXX W	WESTWARD SIGNAL NUMBER
XXXX T	TRACK CIRCUIT NAME
EQ→	EQUATED DISTANCE EAST
<b>→</b> EQ	EQUATED DISTANCE WEST
VC	VERTICAL CURVE
1	UPGRADE GOING EAST
•	DOWNGRADE GOING EAST
.5%	PERCENTAGE OF GRADE
TBD	TO BE DETERMINED
MPHS	MILES PER HOUR PER SECONE

MILES PER HOUR

# EQUATED DISTANCE FORMULA:

EQUATED DISTANCE (ASCENDING) = ACTUAL DISTANCE  $\times \frac{(4+G)}{4}$ 

EQUATED DISTANCE (DESCENDING) = ACTUAL DISTANCE  $\times (4-G)$ 

	NO.	DATE	BT	CHECK	DESIGN	REVISION / SUBMITTAL
	•		•			
ı	•					
	•					
ı	•					
ı	•					
ı						
ı						
I	•	•				



PRELIMINARY ENGINEERING









WEST-VOLUME 3 (SYSTEMS)
SIGNAL SYSTEM
GENERAL
SAMBOLE & LEGEND BOLLE & VOD


**SYMBOLS & LEGEND ROUTE & ASPECT SYSTEMS** SIG-GEN-002 SHEET


133


OF












































- NOTE 1: NORMAL YARD OPERATION AND SWITCH POSITIONING WILL BE PERFORMED BY THE RCC. NO ROUTES AUTOMATIC OR OTHERWISE ARE REQUIRED.
- NOTE 2: ALL SWITCHES IN THE OPERATIONS AND MAINTENANCE FACILITY SHALL BE POWERED AND PROVIDED WITH TRAILABLE, ELECTRIC, DUAL CONTROL SWITCH OPERATING MECHANISMS.
- NOTE 3: ALL SWITCHES SHALL BE PROVIDED WITH NORMAL AND REVERSE POINT DETECTION AND SHALL BE EQUIPPED WITH COLOR LIGHT SWITCH POSITION INDICATORS.
- NOTE 4: DETECTOR LOCKING SHALL BE REQUIRED FOR ALL POWERED YARD SWITCHES.
- NOTE 5: TWC LOOPS WILL BE INSTALLED ON ALL ARRIVAL AND DEPARTURE TRACKS FROM THE YARD AS WELL AS ENTRANCES AND EXITS TO MAINTENANCE FACILITIES.

:	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	
-							
5							]
ò							
9							1
t							1
2							
5							
,							1
3							1





**WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM **CONTROL LINE DIAGRAM OMF** 


OF 202


SHEET


PRELIMINARY ENGINEERING


DISCIPLINE: **SYSTEMS** 


SIG-CLD-016




















SIGNAL ROUTES	ENTRANCE SIGNAL	EXIT SIGNAL	ASPECTS	OPPOSING/	SWITCHES LOCKED		5	TRACKS UNOCCUPIED	C	ONTROL MO	DDE	TIME LOCKING	OPERATIONAL NOTES
ROUTES	SIGNAL	SIGNAL		CONFLICTING ROUTES		)= REV.		UNOCCUPIED	AUTO	TWC	MANUAL	TIME SETTINGS	NOTES
1EA	1E	1W	G, FY, Y	2EB, 1WA, 1WB, 2WB	1 A		3A	1AT, 3AT, 1-EAT	1	/ x \	X	TBD	1
1EB		2W	R/FG, R/FY, R/FL	2EA, 2EB, 1WA, 1WB, 2WA, 2WB	(1A)	(1B)	3B	1AT, 1BT, 3BT, 2-EAT	_	\	) x	TBD	1
2EA	2E	2W	G, FY, Y	1EB, 1WB, 2WA, 2WB	1B		3B	1BT, 3BT, 2-EAT	Х	( x <	X	TBD	1
2EB		1W	R/FG, R/FY, R/FL	1EA, 1EB, 1WA, 1WB, 2WA, 2WB	1B	(3B)	(3A)	1BT, 3BT, 3AT, 1-EAT	-	> x /	Х	TBD	1
1WA	1 W	1E	G, FY, Y	2WB, 1EA, 1EB, 2EB	3A		1A	3AT, 1AT, 1-WAT	Х	( x )	Х	TBD	1
1WB		2E	R/FG, R/FY, R/FL	2WA, 2WB, 1EA, 1EB, 2EA, 2EB	(3A)	(3B)	1B	3AT, 3BT, 1BT, 2-WAT	-	/ x /	Х	TBD	1
2WA	2W	2E	G, FY, Y	1WB, 1EB, 2EA, 2EB	3B		1B	3BT, 1BT, 2-WAT	-	/ x )	Х	TBD	1
2WB		1E	R/FG, R/FY, R/FL	1WA, 1WB, 1EA, 1EB, 2EA, 2EB	3B	(1B)	(1A)	3BT, 1BT, 1AT, 1-WAT	_	( x \	Х	TBD	1
		-	•	•	-						•		
											V— NOTE	2	

LAMP OUT DOWNGRADES									
SIGNALS	ASPECT	LAMP OUT	DOWNGRADE						
1E, 2E, 1W, 2W	G	TOP G	Y						
1E, 2E, 1W, 2W	Y	TOP Y	R						
1E, 2E, 1W, 2W	FY	TOP Y	R						
1E, 2E, 1W, 2W	R/FG	BOTTOM G	R/FY						
1E, 2E, 1W, 2W	R/FY	воттом у	R						
1E, 2E, 1W, 2W	R/FL	ВОТТОМ L	R						
1E, 2E, 1W, 2W	R/FG, R/FY, R/FL	TOP R	D/D						
1E, 2E, 1W, 2W	R	TOP R	D						

NOTE: ALL SIGNAL LIGHT ASPECTS (E.G. G,Y,R) DISPLAY ON "A" HEAD WITH "B" HEAD DARK.

## NOTES:

- SIGNALS CAN BE CONTROLLED VIA RCC, TWC OR LOCAL CONTROL PANEL TWC ROUTING CODES TO BE ASSIGNED IN FINAL DESIGN TRACK CIRCUIT NAMES OUTSIDE THE LIMITS OF THE INTERLOCKING SHALL FOLLOW METRO TRANSIT STANDARD NAMING CONVENTION

:	NO.	DATE	BT	CHECK	DESIGN	REVISION / SUBMITTAL
=						
-						
20						
Ö.						
ŧ	٠					
20						
2						
5						

PARSONS BRINCKERHOFF

PRELIMINARY ENGINEERING





## **WEST-VOLUME 3 (SYSTEMS) SIGNAL SYSTEM EQUIPMENT DETAILS** TYPICAL ROUTE AND LOCKING TABLE


SHEET

157

OF

202

DISCIPLINE: **SYSTEMS** SIG-RLT-001




## POWER BONDING KEY


- (A) 1-250 KCM MECHANICAL RAIL CONNECTION
- 1-500 KCM MECHANICAL RAIL CONNECTION
- (C) 2-500 KCM MECHANICAL RAIL CONNECTION
- (D) 2-250 KCM MECHANICAL RAIL CONNECTION
- (E) NOT REQUIRED FOR WELDED JOINTS

### NOTES:

- 1. CROSS BONDING SHALL NOT BE COMBINED WITH NEGATIVE RETURN AT SUBSTATION.
- 2. ALL RAIL CONNECTIONS WILL BE MADE WITH MECHANICAL FASTENERS SUCH AS CEMBRE AR60 OR APPROVED EQUAL.
- ACTUAL RAIL COMPONENT LENGTH AND TIE SPACING MAY VARY FROM THOSE SHOWN ON THIS DRAWING.
- 4. RIGHT HAND TURNOUT DETAILS SHALL BE OPPOSITE TO THAT SHOWN.
- 5. DRESS CABLES CLOSE TO RAIL WITHIN GAGE.
- 6. 250 KCMIL BOND CABLE AND 500 KCMIL BOND CABLE SHALL BE TYPE "EXTRA FLEX", "ROPELAY" TYPE OR APPROVED EQUAL.
- 7. RAIL CONNECTION SHALL BE PLACED AS CLOSE AS POSSIBLE TO THE INSULATED JOINT BAR, TYPICALLY NO MORE THAN 24 INCHES AWAY FROM THE ACTUAL JOINT, TO PROVIDE BROKEN RAIL PROTECTION
- 8. TRACK INSTALLATION SHOWN SCREENED FOR CLARITY.
- 9. JOINT IS DESIGNED TO ACCOMMODATE 30" OF EXPANSION / CONTRACTION. DESIGN CABLE LENGTH FOR BONDS ACCORDINGLY.



RAIL EXPANSION JOINT RETURN POWER BONDING



SCALE: NTS

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL

PARSONS BRINCKERHOFF

PRELIMINARY ENGINEERING






## **WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM **EQUIPMENT DETAILS**

**TYPICAL RAIL BONDING DETAIL - JOINTED SYSTEMS** SIG-DTL-001


SHEET

158

OF



- 1. RAIL BONDING SHALL BE ACCOMPLISHED WITH MECHANICAL CONNECTORS, SUCH AS CEMBRE AR60D OR APPROVED EQUAL.
- 2. THE CONTRACTOR SHALL PROVIDE BONDING PLANS FOR EACH SWITCH POINT LOCATION FOR APPROVAL BY THE CAR.
- 3. ARRANGEMENT SHOWN IS GENERAL AND IS PROVIDED TO SHOW TYPICAL ARRANGMENTS OF TRACK CIRCUITS, BONDS AND RETURN RAIL CONFIGURATIONS.
- 4. ALL 500 KCM CABLES ARE ROPELAY
- 5. CROSS BONDING SHALL NOT BE COMBINED WITH NEGATIVE RETURN AT SUBSTATION.



## SIGNAL AND POWER BONDING KEY

- A 1-#6 BOND STRAND
- (B) 3-500 KCM MECHANICAL RAIL CONNECTION
- (C) 2-250 KCM MECHANICAL RAIL CONNECTION
- (D) 2-500 KCM MECHANICAL RAIL CONNECTION

INSULATED JOINT — NEGATIVE RETURN RAIL - SIGNAL RAIL

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL

PARSONS BRINCKERHOFF





**WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM **EQUIPMENT DETAILS RAIL BONDING DETAIL - DIAMOND XOVER** 

202 SIG-DTL-002


SHEET

159


OF

PRELIMINARY ENGINEERING

**SYSTEMS** 



- 1. RAIL BONDING SHALL BE ACCOMPLISHED WITH MECHANICAL CONNECTORS, SUCH AS CEMBRE AR60D OR APPROVED
- 2. THE CONTRACTOR SHALL PROVIDE BONDING PLANS FOR EACH SWITCH POINT LOCATION FOR APPROVAL BY THE CAR.
- 3. ARRANGEMENT SHOWN IS GENERAL AND IS PROVIDED TO SHOW TYPICAL ARRANGMENTS OF TRACK CIRCUITS, BONDS AND RETURN RAIL CONFIGURATIONS.
- 4. ALL 500 KCM CABLES ARE ROPELAY
- 5. CROSS BONDING SHALL NOT BE COMBINED WITH NEGATIVE RETURN AT SUBSTATION.



## SIGNAL AND POWER BONDING KEY

- 1-#6 BOND STRAND (TRACK CIRCUIT JUMPER)
- 3-500 KCM MECHANICAL RAIL CONNECTION
- C 2-250 KCM MECHANICAL RAIL CONNECTION
- D 2-500 KCM MECHANICAL RAIL CONNECTION

→ INSULATED JOINT - NEGATIVE RETURN RAIL - SIGNAL RAIL

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL

PARSONS BRINCKERHOFF

PRELIMINARY ENGINEERING






## **WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM **EQUIPMENT DETAILS** SINGLE RAIL TRACK CIRCUIT RAIL BONDING

**SYSTEMS** 

SIG-DTL-003

160 OF

SHEET



- 1. TRANSIT SIGNALS TO BE USED ONLY IN YARDS, TUNNELS, AT STATION PLATFORMS, AND IN URBAN EMBEDDED TRACK ENVIRONMENTS WHERE MOUNTING SPACE IS A CONCERN. ALL OTHER SIGNALS TO BE HIGH
- 2. DOUBLET SIGNAL LENSES, 6-3/8" CLEAR OUTER, 5-1/2" COLORED INNER, UNLESS LEDs SPECIFIED.
- 3. METAL HOODS TO BE 4" LONG.
- 4. HEADS TO BE PAINTED FLAT BLACK.
- 5. MAST AND JB TO BE ALUMINUM (NOT PAINTED).

- 6. LAMPS TO BE 10V/18W, SINGLE FILAMENT, UNLESS LEDs SPECIFIED.
- 7. PRE-CAST CONCRETE FOUNDATION.
- 8. SIGNAL NUMBER PLATES SHALL MEET AREMA
- 9. ALL SIGNALS TO BE MIN. 76" FROM CENTERLINE OF TANGENT TRACK, EXCEPT WHERE SIGNAL IS LOCATED AT END OF PLATFORM.
- 10. TRANSIT SIGNALS SHALL USE 4" ALUMINUM MAST.
- 11. DRAWING NOT TO SCALE.

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL

**PARSONS BRINCKERHOFF** 






**WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM **EQUIPMENT DETAILS** TRANSIT SIGNALS

161 OF

SHEET

DISCIPLINE: **SYSTEMS** 


202 SIG-DTL-004



- HIGH SIGNALS TO BE USED AS BLOCK AND INTERLOCKING SIGNALS ON MAINLINE TRACKAGE WHERE HIGHER SPEEDS AND VISIBILITY ARE A CONCERN. TO BE USED AT ALL LOCATIONS OTHER THAN THOSE FOR WHICH TRANSIT SIGNALS ARE SPECIFIED.
- DOUBLET SIGNAL LENSES, 8-3/8" CLEAR OUTER, 5-1/2" COLORED INNER, UNLESS LEDs SPECIFIED.
- 3. SNOW HOODS, BACKGROUNDS, LADDERS, AND PLATFORMS SHALL BE PROVIDED.
- 4. HEADS TO BE PAINTED FLAT BLACK.
- 5. MAST AND JB TO BE ALUMINUM (NOT PAINTED).

- 6. LAMPS TO BE 10V/18W, SINGLE FILAMENT, UNLESS LEDs SPECIFIED.
- 7. PRE-CAST CONCRETE FOUNDATION.
- 8. SIGNAL NUMBER PLATES SHALL MEET AREMA
- ALL SIGNALS TO BE MIN. 76" FROM CENTERLINE OF TANGENT TRACK, EXCEPT WHERE SIGNAL IS LOCATED AT END OF PLATFORM.
- 10. HIGH SIGNALS SHALL USE 5" ALUMINUM MAST.
- 11. DRAWING NOT TO SCALE.

- (; □	NO.	DATE	BY CH	ECK DES	IGN REVISION / SUBMITTAL		1470714		SHEET
´_ [							WEST-VO	LUME 3 (SYSTEMS)	SIILLI
ğ				.   .			A CI	NAL SYSTEM	
5						A <b>ECOAA</b> PARSONS	310	NAL STOTEW	162
ë						<b>AECOM</b> PARSONS BRINCKERHOFF	EQUI	MENT DETAILS	
4				.   .		A=CUIVI BRINCKERHOFF	STATE OF THE STATE		OF
50				.   .		METROPO	Green Line LRT Extension WAYS	E HIGH SIGNALS	∣ <b>∵</b>
ဖွ				.   .					
٠ <u>٠</u> ـ				.   .		PRELIMINARY ENGINEERING	DISCIPLINE: SYSTEMS	SIG-DTL-005	202
ä				.   .		FRELIMINART ENGINEERING	SISIEMS	310-011-005	



BY CHECK DESIGN REVISION / SUBMITTAL

PARSONS BRINCKERHOFF





**WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM **EQUIPMENT DETAILS** TYP LOCAL CONTROL PANEL FACEPLATE


**SYSTEMS** SIG-DTL-006

PRELIMINARY ENGINEERING

SHEET

163

OF



	NO.	DAIL	BY	CHECK	DESIGN	REVISION / SUBMITTAL
!						






**WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM **EQUIPMENT DETAILS** TYP INTERLOCKING LCP NOMENCLATURE SHEET


164


OF


202

SIG-DTL-007 **SYSTEMS** 









PLAN VIEW



- 1. TWC LOOP ANTENNAS SHALL BE 3'x16' FOR MAINLINE INSTALLATIONS.
- 2. LOOP ANTENNA CONSTRUCTION SHALL BE OF FIBERGLASS AND WOOD
- 3. METAL COMPONENTS ARE NOT PERMITTED. OTHER THAN TWC CLIPS & LAG BOLTS
- 4. TOTAL WEIGHT SHALL NOT EXCEED 200 LBS FOR THE 16' LOOP
- 5. THE LOOP ANTENNA ASSEMBLY SHALL BE ABLE TO SUPPORT 1000 LBS IN A 3' OUTSIDE SUPPORTED
- 6. TOP SHALL BE MOLDED WITH AN AGGRESSIVE NON-SKID TEXTURE, AS APPROVED BY ENGINEER
- 7. TOP TO INCLUDE 1/4" CROWN ALONG THE LONG AXIS OF THE LOOP
- 8. OUTSIDE FINISH SHALL BE GRAY GELCOAT OR EQUIVALENT, AS APPROVED BY ENGINEER. FINISH THICKNESS SHALL BE 20 THOUSANDS OF ONE INCH
- 9. A JUNCTION BOX CAVITY TO BE MOLDED INTO LOOP ASSEMBLY. A 1/8" THICK COVER PLATE SHALL COVER JUNCTION BOX CAVITY ATTACHED BY EIGHT (8) SS SCREWS. COVER PLATE SHALL HAVE KNOCKOUT TO ALLOW 3/4" LIQUID-TITE FLEX CONDUIT ATTACHMENT
- 10. LOOP WIRE TO BE PLACED 2" OFFSET FROM OUTSIDE EDGE OF ASSEMBLY. LOOP WIRE TO CROSS AT CENTER AND TERMINATE AT JUNCTION BOX CAVITY WITH 120" OF EXTRA LEAD. LEADS TO BE TWISTED FROM LOOP CLOSING TO JUNCTION BOX
- 11. LOOP WIRE SHALL BE AWG #12 XHHW POLYETHYLENE JACKETED TRAFFIC SIGNAL LOOP WIRE
- 12. SUPPORT RAILS SHALL BE MOLDED INTO ASSEMBLY OUTER EDGES. SUPPORT PADS TO ALLOW FOR FIELD INSTALLATION OF TWO 5/8" LAG BOLTS PLACED A MINIMUM OF 2" EITHER SIDE OF WIDTH CENTERLINE AND 6" FROM OUTSIDE EDGE
- 13. CURRENTLY THE USE OF LAG BOLTS AND WOOD TIMBER IS NOT ALLOWED WITHOUT PRIOR APPROVAL FROM THE RESIDENT ENGINEER

	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL
I						
I						
I						
Ī						
Ī						
I						
Ī						
Ī						
ı						

**PARSONS BRINCKERHOFF** 





**WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM **EQUIPMENT DETAILS** TWC LOOP ANTENA

165 OF


SHEET


DISCIPLINE

SIG-DTL-008

PRELIMINARY ENGINEERING

**SYSTEMS** 





NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL
		T .			

PRELIMINARY ENGINEERING





## **WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM **EQUIPMENT DETAILS IMPEDANCE BOND MOUNTING - PLINTH**

NOTES:

INSTALLATIONS.

OF CLEARANCE BELOW.

1. CONCRETE PLINTHS ARE ARRANGED TO ALLOW THE MOUNTING OF STANDARD RAIL IMPEDANCE BONDS

2. THE 6" PLINTH HEIGHT ACCOMMODATES A TYPICAL

IMPEDANCE BOND DEPTH AND AN ADDITIONAL 2"


SIMILAR TO STANDARD TIE MOUNTED


202 **SYSTEMS** SIG-DTL-009

SHEET

166

OF





- 1. EQUIPMENT DETAILS SHALL BE SUBMITTED FOR APPROVAL
- 2. EXCAVATION FOR BOOTLEG AND JUNCTION BOX INSTALLATION WILL REQUIRE REMOVAL OF BALLAST, SUB-BALLAST AND NATIVE SOIL OR BACKFILL MATERIALS. THESE MATERIALS MUST BE KEPT SEPARATED
- 3. THE CONTRACTOR SHALL EQUIP EACH JUNCTION BOX PROVIDED WITH A COMPLETE SET OF GOLD NUT TEST LINKS AND APPROPRIATE STRAPS FOR ALL TERMINALS.

USED FOR MAINLINE SWITCH MACHINES

# 36-WAY BOOTLEG JUNCTION BOX DETAIL

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL

PARSONS BRINCKERHOFF





**WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM **EQUIPMENT DETAILS BOOTLEG JUNCTION BOX INSTALLATION** 


OF 202

PRELIMINARY ENGINEERING

**SYSTEMS** 

SIG-DTL-010

SHEET



PRELIMINARY ENGINEERING

SHEET

168

OF


202

SIG-DTL-101

**ARRANGEMENT & INSTALLATION DETAILS** 


**SYSTEMS** 


DISCIPLINE



- THE BILL OF MATERIALS ONLY INCLUDES THE MAJOR ITEMS AND DOES NOT INCLUDE ALL REQUIRED ITEMS FOR A COMPLETE INSTALLATION.
- 2. THIS CROSSING WARNING SIGNAL ASSEMBLY SHALL BE DOUBLE-SIDED, WITH EACH ACTIVE AND PASSIVE SIGNAL VIEWABLE FOR EACH DIRECTION.
- 3. EACH FLASHING UNIT SHALL INCLUDE A "MOTORMANS" SIDELIGHT BUILT INTO THE SIGNAL HOUSING UNIT. THE "MOTORMAN" SIDELIGHTS SHALL BE LOCATED TO PROVIDE A VISUAL INDICATION TO THE LRV OPERATOR THAT THE CROSSING WARNING DEVICE IS ACTIVE.
- 4. THE 2-SIDED LED SECOND TRAIN SIGN SHALL BE MANUFACTURED IN ACCORDANCE WITH ALL APPLICABLE SYSTEMS SPECIFICATIONS.
- 5. THE 2-SIDED LED SECOND TRAIN SIGN SHALL BE CONFIGURED SO THAT EACH LED PANEL CAN BE REPLACED WITHOUT REPLACING THE ENTIRE DEVICE, USING A DISCRETE POWER SUPPLY AND CABLING TO ENSURE THAT A SINGLE FAILURE WILL NOT DISABLE BOTH SIDES OF THE ACTIVE WARNING SIGN.
- 6. DRILL FLANGE FOR CONNECTION OF GROUND STUD TO
- 7. MANUFACTURERS SHALL BE SUBMITTED FOR APPROVAL BY THE CAR.
- THE SIZE FOR THE STANDARD R15-8 SHALL BE REDUCED TO 12" X 24", SCALED FOR THE PEDESTRIAN SPECIFIC CROSSING DEVICE.
- THE SIGN SHALL BE CONSTRUCTED TO MEET THE REQURIEMENTS OF MNDOT SPECIFICATIONS FOR MATERIALS

	BILL OF MATERIALS								
ITEM	QTY	DESCRIPTION							
	1	WESTERN CULLEN HAYES MODEL WCH0777 ELECTRONIC BELL							
2	2	12" X 24" "LOOK" STATIC REFLECTIVE SIGN, MUTCD R15-8							
3	1	SIGNAL MAST, ALUMINUM, 4"							
4	1	SPLIT JUNCTION BOX BASE (NOTE 7)							
5	1	CAST IN PLACE FOUNDATION BY OTHERS (NOTE 7							
6	1	10' COPPER CLAD GROUND ROD BY OTHERS							
7	AS REQ'D	#2/0 BARE STRANDED COPPER WIRE							
8	1	GROUND LUG AMP #33467							
9	1	18" X 16" LED 2nd TRAIN APPROACHING SIGN- 2 SIDED, (NOTES 4 & 5)							
10	2	16" ALUMINUM BACKGROUND, FLAT BLACK, WITH 9" VISOR							
(11)	2	8" LED SIGNAL ROUNDEL, RAIL OR TRANSIT APPLICATION							





PEDESTRIAN FLASHER BASE PLATE DETAIL

PEDESTRIAN FLASHER POLE GROUNDING DETAIL SCALE: NTS

/							
	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	
_							
5							
2							1
j							1
t							1
201							1
. 02							1
, 4							1
5							İ

**PARSONS BRINCKERHOFF** 





**WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM PEDESTRIAN CROSSING EQUIPMENT PEDESTRIAN CROSSING BELL & FLASHER


SHEET

169

OF

202

**SYSTEMS** SIG-DTL-201



PRELIMINARY ENGINEERING

- THIS CABINET ARRANGEMENT IS INTENDED AS A GUIDE FOR EQUIPMENT ARRANGEMENT ONLY. THE CONTRACTOR SHALL FABRICATE A CABINET DESIGNED FOR THE ACTUAL EQUIPMENT CHOSEN BY THE CONTRACTOR THAT WILL MEET THE REQUREMENTS OF THE CONTRACT AND THE FUNCTIONAL REQUIREMENTS OF A PEDESTRIAN
- THE EQUIPMENT SHOWN IS FOR INFORMATION ONLY. THE ACTUAL EQUIPMENT INSTALLED SHALL BE CHOSEN BY THE CONTRACTOR TO MEET THE FUNCTIONAL NEEDS OF THE PEDESTRIAN CROSSING AND WILL BE SUBMITTED TO THE CAR FOR APPROVAL PRIOR TO FABRICATION.
- THE CABINET WILL BE STAINLESS STEEL, WITH A FRONT AND A BACK DOOR FOR ACCESSING EQUIPMENT MOUNTED ON EACH SIDE. THE 19 INCH RACK IS SHOWN CENTERED IN THE CABINET, BUT IT MAY MOVE LEFT OR RIGHT TO MEET THE INSTALLATION NEEDS OF THE EQUIPMENT ACTUALLY CHOSEN. THE RACK MAY BE ELIMINATED IF IT IS SHOWN THAT BOARD MOUNTING IS
- THE DIMENSIONS OF THE CABINET ARE SHOWN FOR REFERENCE ONLY, THE CABINET SHALL NOT BE HIGHER THAN 84 INCHES ABOVE THE SITE PAVING LEVEL. THE CONTRACTOR SHALL CHOOSE A DESIGN THAT IS COORDINATED WITH THE FOUNDATION THAT WILL BE INSTALLED AS PART OF A SEPARATE CONTRACT. ACTUAL DIMENSIONS SHALL BE SHOWN ON THE PEDESTRIAN CABINET DESIGN SUBMITTED TO THE CAR FOR APPROVAL.
- THE BATTERY REQUIREMENTS FOR THIS DESIGN WILL BE DETERMINED AFTER THE EQUIPMENT IS CHOSEN BY THE CONTRACTOR FOR FABRICATION. THE SPACE AT THE BOTTOM OF THE CABINET IS RESERVED FOR MULTI-CELL BANKS OF BATTERIES THAT WILL MEET THE REQUIREMENTS OF THE FLASHER/WARNING DEVICE, WITH AN ADDITIONAL BANK FOR THE OPERATION OF THE ELECTRONICS. THIS SPACE MAY BE ADJUSTED BY THE CONTRACTOR.
- 6. THE CONTRACTOR SHALL POST DRILL THE ANCHOR BOLTS FOR THE CABINET AT THE TIME OF INSTALLATION, USING A CHEMICAL TYPE ANCHOR DESIGNED FOR THE SPECIFIC INSTALLATION.
- FOR ADDITIONAL INFORMATION ON THE FUNCTIONAL REQUIREMENTS OF THE PEDESTRIAN CROSSING WARNING DEVICES, SEE TECHNICAL SPECIFICATION.
- THE DESIGNER SHALL UTILIZE BOTH SIDES OF THE RACK FOR WIRING AND FOR EQUIPMENT MOUNTING FOR DEVICES SUCH AS 110VAC POWER DISTRIBUTION CIRCUIT BREAKERS, DIN RAIL MOUNTED TERMINALS, BATTERY CHARGERS, LIGHTNING AND SURGE PROTECTION, ETC.

DISCIPLINE

**SYSTEMS** 


SHEET


170

OF

202

SIG-DTL-202





SECOND TRAIN WARNING SIGN

SIDE VIEW SECOND TRAIN WARNING SIGN SCALE: NTS

## NOTES:

- 1. THE 16" X 18" "SECOND TRAIN WARNING" PEDESTRIAN SIGN SHOWN IS TO BE USED FOR PEDESTRIAN CROSSINGS AND IS NOT DESIGNED FOR ROADWAY TRAFFIC.
- 2. THIS "SECOND TRAIN WARNING" PEDESTRIAN SIGN SHALL BE DOUBLE SIDED, HOUSED IN A RUGGED STAINLESS STEEL NEMA 4X CASE WITH A HINGED AND GASKETED FACE FOR ACCESS AND SERVICE. THE POLYCARBONATE PROTECTIVE COVER AND THE LED UNIT ITSELF SHALL BE EASILY SERVICED, CLEANED, REMOVED OR REPLACED AS NECESSARY FOR STANDARD MAINTENANCE THE SIGN COMPONENTS SHALL BE EASILY REMOVED FOR SERVICE OR REPLACEMENT WITH PLUG COUPLED CABLES AND EASILY ACCESSED SCREWS AND RETAINING CLIPS.
- 3. THE "SECOND TRAIN WARNING" PEDESTRIAN SIGN SHALL BE AN LED SIGN MANUFACTURED ACCORDING TO THE REQUIREMENTS OF THE FEDERAL HIGHWAY STANDARD HIGHWAY SIGN HANDBOOK. THE MANUFACTURER SHALL PROVIDE A RUGGED AND RELIABLE DEVICE DESIGNED FOR THE LOCAL ENVIRONMENT.
- 4. THE CONTRACTOR SHALL ATTACH EACH "SECOND TRAIN WARNING" PEDESTRIAN ACTIVE SIGN TO THE CROSSING EQUIPMENT ASSEMBLY. THIS INSTALLATION SHALL BE RUGGED AND WILL BE COORDINATED WITH THE NECESSARY DEVICES AND SIGNS REQUIRED ON THAT
- 5. THE EQUIPMENT SHOWN IS FOR INFORMATION ONLY. THE ACTUAL EQUIPMENT INSTALLED SHALL BE CHOSEN BY THE CONTRACTOR TO MEET THE FUNCTIONAL NEEDS OF THE PEDESTRIAN CROSSING AND WILL BE SUBMITTED TO THE CAR FOR APPROVAL PRIOR TO
- 6. THE DIMENSIONS OF THE CASE SHOWN ARE PROPOSED DIMENSIONS, ACTUAL DIMENSIONS SHALL BE SHOWN ON THE SHOP DRAWINGS AND FOR THE DESIGN SUBMITTED TO THE CAR FOR APPROVAL.

DATE BY CHECK DESIGN REVISION / SUBMITTAL

PARSONS BRINCKERHOFF

PRELIMINARY ENGINEERING






**WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM PEDESTRIAN CROSSING EQUIPMENT SECOND TRAIN WARNING PEDESTRIAN SIGN


SHEET

171

202

**SYSTEMS** SIG-DTL-203





FRONT VIEW PEDESTRIAN WARNING SIGN

PEDESTRIAN WARNING SIGN

## NOTES:

- 1. THIS "TRAIN APPROACHING" PEDESTRIAN SIGN SHALL BE SINGLE SIDED, HOUSED IN A RUGGED STAINLESS STEEL NEMA 4X CABINET WITH A GASKETED TOP ACCESS LID. THE CABINET SHALL BE NO WIDER THAN 14 INCHES TO ACCOMODATE THE AVAILABLE MOUNTING
- 2. THE FUNCTIONAL OPERATION OF THE "TRAIN APPROACHING" PEDESTRIAN SIGN SHALL BE AS DESCRIBED ON THE PEDESTRIAN CROSSING TYPICAL SITE CONFIGURATION PLAN PLAN.
- 3. THE "TRAIN APPROACHING" PEDESTRIAN SIGN SHALL BE AN LED SIGN MANUFACTURED ACCORDING TO THE REQUIREMENTS OF THE FEDERAL HIGHWAY STANDARD HIGHWAY SIGN HANDBOOK. THE MANUFACTURER SHALL PROVIDE A RUGGED AND RELIABLE DEVICE DESIGNED FOR THE LOCAL ENVIRONMENT.
- 4. THE POLYCARBONATE PROTECTIVE COVER AND THE LED UNIT ITSELF SHALL BE EASILY SERVICED, CLEANED, REMOVED OR REPLACED AS NECESSARY FOR STANDARD MAINTENANCE BY REMOVING THE TOP COVER TO ACCESS THE SIGN COMPONENTS. THE SIGN COMPONENTS SHALL BE EASILY REMOVED FOR SERVICE OR REPLACEMENT WITH PLUG COUPLED CABLES AND EASILY ACCESSED SCREWS AND RETAINING CLIPS.
- 5. THE CONTRACTOR SHALL ATTACH EACH "TRAIN APPROACHING" PEDESTRIAN ACTIVE SIGN TO THE PEDESTRIAN CROSSING STEM WALLS WITH POST DRILLED ANCHOR BOLTS FOR THE CABINET, USING A CHEMICAL TYPE ANCHOR DESIGNED FOR EACH SPECIFIC INSTALLATION. THIS INSTALLATION WILL BE COORDINATED WITH THE CONDUIT INSTALLED FOR THE OPERATION OF THE SIGN.
- 6. THE EQUIPMENT SHOWN IS FOR INFORMATION ONLY. THE ACTUAL EQUIPMENT INSTALLED SHALL BE CHOSEN BY THE CONTRACTOR TO MEET THE FUNCTIONAL NEEDS OF THE PEDESTRIAN CROSSING AND WILL BE SUBMITTED TO THE CAR FOR APPROVAL PRIOR TO
- 7. THE DIMENSIONS OF THE CABINET SHOWN ARE MAXIMUM DIMENSIONS, THE CABINET SHALL NOT BE HIGHER THAN 42 INCHES ABOVE THE SITE PAVING LEVEL. THE CONTRACTOR SHALL CHOOSE A DESIGN THAT IS COORDINATED WITH THE ARCHITECTURAL STEM WALL THAT WILL BE INSTALLED AS PART OF A SEPARATE CONTRACT. ACTUAL DIMENSIONS SHALL BE SHOWN ON THE PEDESTRIAN CABINET DESIGN SUBMITTED TO THE CAR FOR APPROVAL.
- 8. THE CONTRACTOR SHALL PROVIDE ALL CABLES AND TERMINATIONS REQUIRED FOR UP TO 4 DEVICES AT EACH PED CROSSING LOCATION. ALL CABLES SHALL BE CONTINOUS, WITHOUT SPLICES, FROM EACH DEVICE TO THE CROSSING CONTROLLER CABINET.

	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL
ı						
ı						
ı						
ı						
I						
I						
I						
ı						
ı						






PRELIMINARY ENGINEERING







SIG-DTL-204


**SYSTEMS** 


202

SHEET

172

OF





**BRINCKERHOFF** 

PRELIMINARY ENGINEERING

METROPOLITAN SOUTHWEST

**SYSTEMS** SIG-DTL-302


**WAYSIDE CONTROL CABINET** 


DISCIPLINE


SHEET

174

OF









- THE CONTRACTOR SHALL SUPPLY AND INSTALL AN OCS POLE MOUNTED SWITCH HEATER CONTROL CASE AND EQUIPMENT IF GEOGRAPHIC CONSTRAINTS PRECLUDE MOUNTING CONTROL CABINET OUTSIDE OF THE GUIDEWAY.
- CABINET MOUNTED SWITCH HEATER CONTROL EQUIPMENT WILL RECEIVE 750VDC FROM THE 750V DC OVERHEAD CONTACT WIRE ROUTED THROUGH THE "SHOE BOX" TYPE FUSED DISCONNECT.
- THE CASE WILL BE SECURED WITH HIGH-SECURITY PADLOCKS AND KEYED FOR METRO TRANSIT STANDARD TRACTION POWER MAINTENANCE PERSONNEL.
- ALL 750V DC CIRCUIT WIRING TO BE 2000 VOLT INSULATION.
- HEATER CASES AND ALL CONTROL CIRCUITS ARE SHOWN AS EXAMPLES ONLY. THE NUMBER OF CONTACTORS AND/OR FUSED BRANCH CIRCUITS PER CASE MAY VARY. THE CONTRACTOR SHALL SUBMIT A COMPLETE SWITCH HEAT CONTROLLER CASE DESIGN FOR EACH INSTALLATION WITH A DESIGN AND PRODUCT SUBMITTAL TO THE CAR FOR
- CONTRACTOR TO VERIFY SIZE AND SUITABILITY FOR ALL
- LOW VOLTAGE WIRING TO BE 14 GAUGE, 1000V, BLACK UNLESS OTHERWISE NOTED.
- GROUND WIRING TO BE 14 GA., 600V, GREEN, UNLESS OTHERWISE NOTED.
- CASE TO BE MOUNTED PARALLEL TO TRACK, NOT PERPENDICULAR.

_			
5			
5			
j			
ŧ			
20			
2			
, ,			
, Inc			

DATE BY CHECK DESIGN REVISION / SUBMITTAL









**WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM **750VDC SWTICH HEATER DETAILS** TYPICAL POLE MOUNTED CASE LAYOUT


OF 202


SHEET

175

DISCIPLINE **SYSTEMS** 

SIG-DTL-303





- NO.6 AWG, 2KV INSULATED COPPER WIRE IN ORANGE LIQUID TIGHT CONDUIT.
- JUNCTION BOX SHALL BE NON-METALLIC, U.V RESISTANT, MOUNTED SOLIDLY TO AN ADJUSTABLE PEDESTAL OR MOUNTED TO THE CONCRETE IN DIRECT FIXATION INSTALLATIONS.
- CONNECT EACH HEATER LEAD TO #6, 2KV FEED WIRE WITH COMPRESSION SLEEVES AND INSULATE WITH RUBBER TAPE, THEN COMPLETE WITH A 2KV HEAT SHRINK SLEEVE FOR ADDITIONAL PROTECTION.
- MAKE EACH CONNECTION FOR NEGATIVE SIDE OF SWITCH HEATERS TO NEGATIVE RETURN RAIL ONLY IN SINGLE RAIL TRACK CIRCUITS.
- CONNECT NEGATIVE ELEMENT LEAD TO THE RAIL WEB WITH A CEMBRE MODEL AR60D OR APPROVED EQUAL.
- ORANGE LIQUID-TIGHT OR PVC-40 CONDUIT TO HOUSE HEATER LEAD WIRES FOR THE ENTIRE RUN.
- INSTALL STAINLESS STEEL SPRING CLIPS BETWEEN RAIL BRACES, TO HOLD HEATER AND RETAINER.
- SLIDE HEATER ELEMENT THROUGH MILLED PORTION OF RAIL BRACES
- CRIB HEATERS SHALL BE INSTALLED TO EXTEND 4" PAST THE THE ENDS OF THE OPERATING RODS IN NUMBER 1 + 2 TIE SPACES TO FULLY HEAT THE ENTIRE CRIB AND ALL ASSOCIATED HARDWARE. INSTALL FULL LENGTH STAINLESS STEEL CRIB HEATER MOUNTING PANELS TO PROTECT THE TIES FOR EACH CRIB WITH A CRIB HEATER. EACH CRIB WITH AN OEPRATING SWITCH ROD SHALL HAVE A CRIB HEATING ELEMENT AND A MOUNTING PANEL INSTALLED.
- PROTECT CABLES FOR SWITCH HEAT FEEDS WITH A FLEXIBLE ORANGE LIQUID TIGHT CONDUIT AND ATTACHED TO THE JUNCTION BOX WITH STRAIN RELIEF FITTINGS.
- STAINLESS STEEL HEAT RETAINERS MOUNTED ON FIELD SIDE BETWEEN RAIL BRACES. ALL RETAINING CLIPS, PANELS AND RAIL MOUNTED SWITCH HEAT EQUIPMENT SHALL BE STAINLESS STEEL UNLESS OTHERWISE
- 12. HEATING ELEMENT TO BE 300 WATT/FOOT, WITH THE CAPACITY OF THE SYSTEM TO SUPPORT 400 WATT/FOOT AS AN OPTION.

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL

**PARSONS BRINCKERHOFF** 





## **WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM **750VDC SWTICH HEATER DETAILS BALLASTED AND DIRECT FIXATION DETAIL**


DISCIPLINE **SYSTEMS** SIG-DTL-304

202

SHEET


176


OF



ITEM#	PART NUMBER	DESCRIPTION	999550X QTY	999550-001X QTY
1	802005-001X	FRONT ROD ASSY, SWIVEL	1	1
2	840120-050-01	ROD ASSY, OPERATING	1	1
3	941153-000-01	COUPLING ASSY, GRS MODEL-5	1	1
4	890590-005X	PIN ASSEMBLY, JAW	1	1
5	950143-001-11	BASKET ASSEMBLY	1	1
6	830570-006-01X	ROD ASSY, POINT DET. NEAR POINT	1	0
7	931130-050-01	ROD ASSY, POINT DET. FAR POINT	0	1
8	920560-007X	LUG, POINT DETECTOR POINT	1	1
9	920400-001X	LUG ASSY, DROP BALL STUD	1	1
10	990330-075-02	NUT, 0.750 HVY HEX JAM Z/Y	4	4
11	910109-082-01	ROD ASSY, LOCK CONNECTING	1	1
12	920530-002-01	LUG ASSY	1	1
13	990330-100-02	NUT, 1.000 HVY HEX JAM Z/Y	4	4
14	910922-037-02	STUD ASSY, 0.750 X 10.000	2	2
15	910922-036-01	STUD ASSY, 0.750 X 11.000	2	2
16	860004-007	TIE STRAP	1	1
17	990130-500-02	SCREW, LAG 0.750 X 5.000 Z/Y	6	6
18	950794-000-01X	LATCH STAND ASSY	1	1
19	860105-008-01	PLATE ASSEMBLY, GAGE EXTENSION	2	2
20	998192	COUPLING	1	1
21	998918-003-07	BOX ASSY, JUNCTION W/PEDESTAL 36 TER.	1	1
22	998687-034	CONNECTOR, 1.500 STRAIGHT	2	2
23	998231-048	CONDUIT, 1 1/2" LIQUIDTITE	1	1







B NEAR POINT DETECTOR R	<u>:OD</u>
(6) - SCALE: NTS	
14.00	
(55.25) LOCK CONN. ROD  SCALE: NTS	

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL





WEST-VOLUME 3 (SYSTEMS)
SIGNAL SYSTEM
<b>SWITCH MACHINE DETAILS</b>
<b>5F POWER SWITCH MACHINE</b>


DISCIPLINE: **SYSTEMS** SIG-DTL-401

PRELIMINARY ENGINEERING

SHEET

177

OF



PRELIMINARY ENGINEERING


178

OF

202

SIG-DTL-402

**SYSTEMS** 



ITEM	PART NUMBER	OTY	DESCRIPTION
1	3M7005-4-7	1	BOX TERM HAND KNOB W/LOCK PLATE
2	5M801061-7	4	HOOD, AL, 3' F/SWITCH INDICATOR
3	KH99888	1	ROLL PIN, 5/16 X 2, SS
4	JR70627	4.54	GASKET CORD RD 3/8" DIA BLACK CLOSED CELL NEOPRENE
5	KA95558	4	BOLT. HH CUP PT, 1/2-13 X 1-1/2, SS
6	KB955600	16	MACH SCR, PHIL TRUSS HD, 10-32 X 3/8, SS
7	KS97467	1	SOLID ROD END, TREADED, SS, PART #625K41
8	KE97445	1	WASHER, FLAT, 1/2, SS
9	KD96158	4	NUT, HEX, 1/2-13, SS
10	5M801061-018	4	GASKET, NEOPRENE, 5.5 LED GE
11	801024-041	12	LENS CLIP FOR COLORLIGHT HOUSING
12	9A2200	4	CONNECTOR 1" CENTERS
13	9A2203	16	WASHER BYLD FLAT AAR10708 1/4" STUD
14	9A2204	16	NUT BNDG BRASS NKL PLT #14-24 AAR #10706 CROWN NUT
15	AA2125	2	TAG PERMATAGE 3/4 DIA DISC TAG 1/4 HOLE MARKED ENX
16	AA2126G	1	TAG PERMATAG GREEN 3/4" DISC TAG 1/4" HOLE
17	AA2126R	1	TAG PERMATAG 3/4" DISC TAG 1/4" HOLE MARKED RED
18	KB955670	4	MACH SCR, PHIL RD HD. 10-32 X 5/8, SS
19	KB95611	8	MACH SCR. PHIL RD HD. 4-40 X 1/4, SS
20	KB95612	12	MACH SCR, PHIL TRUSS HD, 1/4-20 X 3/8, SS
21	ZATR3GCFB501B92	2	LED ARRAY 5.5' GREEN GELCORE 10VDC W/LGT OUT
22	ZATR3RCFB501B92	2	LED ARRAY 5.5" YELLOW GELCORE 10VDC W/LGT OUT
23	5M801061-40	1	SWITCH INDICATOR WELDMENT
24	9A2230-4	2	BLOCK TERMINAL 4 POST 1º CTR W/FLAT NUT ONLY
25	KS5831	2	VENT, TYPE K 35 MESH, 3/4, BRASS

- 1. SECURE DOOR GASKET (JR70627 WITH GASKET ADHESIVE (NA70077).
- 2. CLOSE LID AND TIGHTEN KNOB. THEN OPEN AND CHECK FOR PROPER LID SEAL.
- 3. MATERIAL:
  - HOUSING, 1/4" AL 6061-T6.
  - HOODS, .063" AL 5052-H32.
- 4. HARDWARE: STAINLESS STEEL.
- 5. LIGHTS: 5.5 GE GELCORE LED 10V.
- 6. FINISH: NATURAL.
- 7. ALL PART NUMBERS LISTED REFERENCE L&W CATALOGUE NUMBERS.
- 8. THE CENTERLINE OF SWITCH INDICATOR NOT TO BE INSTALLED LESS THAN 44" FROM NEAR GAUGE. COORDINATE LOCATION BEFORE INSTALLATION.
- 9. CENTER OF LENS TO BE LEVELED TO 3" ABOVE TOP OF RAIL.
- 10. SWITCH INDICATORS SHALL DISPLAY THE GREEN ASPECT IN THE POSITION CLOSEST TO THE RAILS WHEN THE NORMAL POINT IS BOTH CLOSED AND LOCKED. THE YELLOW
  ASPECT SHALL BE DISPLAYED FURTHEST FROM THE RAILS WHEN THE REVERSE POINT IS BOTH CLOSED AND LOCKED.

	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	П
							1
5							1
3							1
j							1
- 1							1
2							]
2							]
							]
•							1





**WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM **SWITCH MACHINE DETAILS SWITCH POINT INDICATOR** 


OF 202

SHEET

179

DISCIPLINE: **SYSTEMS** 

SIG-DTL-403



PRELIMINARY ENGINEERING

PARSONS BRINCKERHOFF



SIGNAL SYSTEM SIGNAL HOUSE DETAIL **TYPICAL SIGNAL HOUSE** 

SIG-DTL-501

**SYSTEMS** 

DISCIPLINE


SHEET

OF

# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 1 A 1B 1C 1D 1F 1E 1G FARADAY CAGE LAYOUT NOTES: 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 SPARE CABLE CONDUCTORS ARE TO BE 7'0" X 35" TERMINAL BOARD (TYP) CONNECTED TO GROUND

#### NOTES:

- 1. AN IP MAINTENANCE PHONE WILL BE MOUNTED ON SIDE "A". THIS PHONE WILL BE COMPLIANT WITH THE COMMUNICATION SYSTEM USED BY THE RCC FOR METRO TRANSIT
- 2. THE ENTRANCE RACK SHALL BE CONFIGURED IN A FARADAY CAGE DESIGN TO PROVIDE LIGHTNING PROTECTION. THE DESIGN FOR THIS FARADAY CAGE WILL BE SUBMITTED TO THE CAR FOR APPROVAL PRIOR TO PROCUREMENT OR INSTALLATION.
- 3. THE CONTRACTOR SHALL PROVIDE A VENTILATION FAN AND RESISTIVE HEATER SIZED SPECIFICALLY FOR THE NEEDS OF THIS EQUIPMENT HOUSING AND FOR THIS CLIMATE. THE CLIMATE CONTROL SYSTEM WILL BE OPERATED BY A SINGLE THERMOSTAT. "OVERTEMP" AND "UNDERTEMP" ALARMS WILL BE GENERATED AND TRANSMITTED TO THE RCC VIA



PARSONS BRINCKERHOFF






**WEST-VOLUME 3 (SYSTEMS) SIGNAL SYSTEM SIGNAL HOUSE DETAIL TYPICAL 6'X8' GRADE CROSSING HOUSE** 

OF 202 SIG-DTL-502

PRELIMINARY ENGINEERING

**SYSTEMS** 

SHEET



- THIS DRAWING SHOWS PROPOSED CABLE LAYOUT AND IS INCLUDED FOR DESIGN DEVELOPMENT PURPOSES. FINAL CABLE DESIGN SELECTION WILL BE DETERMINED BY CONTRACTOR AND WILL BE IN ACCORDANCE WITH THE CONTRACT DRAWINGS AND SPECIFICATIONS.
- 2. FOR ADDITIONAL INFORMATION REGARDING COMMUNICATION CABLE, SEE COMMUNICATION SYSTEM NETWORK AND CABLE PLANS FOR TYPICAL LAYOUT.

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	
						1
						ĺ
						1
						İ

PARSONS BRINCKERHOFF






**WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM **TYPICAL CABLE PLANS INTERLOCKING** 

182 OF 202

SHEET

PRELIMINARY ENGINEERING

DISCIPLINE: **SYSTEMS** 



- THIS DRAWING SHOWS PROPOSED CABLE LAYOUT AND IS INCLUDED FOR DESIGN DEVELOPMENT PURPOSES. FINAL CABLE DESIGN SELECTION WILL BE DETERMINED BY CONTRACTOR AND WILL BE IN ACCORDANCE WITH THE CONTRACT DRAWINGS AND
- 2. FOR ADDITIONAL INFORMATION REGARDING COMMUNICATION CABLE, SEE COMMUNICATION SYSTEM NETWORK AND CABLE PLANS FOR TYPICAL LAYOUT.

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL
-					

PARSONS BRINCKERHOFF






**WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM **TYPICAL CABLE PLANS GRADE CROSSING** 

183 OF 202

SHEET

PRELIMINARY ENGINEERING

DISCIPLINE: **SYSTEMS** 



2. FOR ADDITIONAL INFORMATION REGARDING COMMUNICATION CABLE, SEE COMMUNICATION SYSTEM NETWORK AND CABLE PLANS FOR TYPICAL LAYOUT.

/							
	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	
5							1
00							1
j							1
							]
4107							]
0.7							]
							]
Jun,							1

PARSONS BRINCKERHOFF





**WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM **TYPICAL CABLE PLANS STATION PLATFORM** 


184 OF 202


SHEET

PRELIMINARY ENGINEERING

DISCIPLINE: **SYSTEMS** 







- 1. THIS DRAWING SHOWS PROPOSED CABLE LAYOUT AND IS INCLUDED FOR DESIGN DEVELOPMENT PURPOSES. FINAL CABLE DESIGN SELECTION WILL BE DETERMINED BY CONTRACTOR AND WILL BE IN ACCORDANCE WITH THE CONTRACT DRAWINGS AND SPECIFICATIONS.
- 2. FOR ADDITIONAL INFORMATION REGARDING COMMUNICATION CABLE, SEE COMMUNICATION SYSTEM NETWORK AND CABLE PLANS FOR TYPICAL LAYOUT.

.	NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL	
-							
5							
3							
5							
٠							
2							
,							
,							
3							

PARSONS BRINCKERHOFF





### **WEST-VOLUME 3 (SYSTEMS)** SIGNAL SYSTEM **TYPICAL CABLE PLANS INTERMEDIATE SIGNAL LOCATION**

OF 202

SHEET

185


PRELIMINARY ENGINEERING

DISCIPLINE: **SYSTEMS** 


AC ALTERNATING CURRENT MIN MINIMUM  ACR ACCESS CARD READER MTG MOUNTING  AFF ABOVE FINISHED FLOOR MTD MOUNTED  AFG ABOVE FINISHED GRADE NC NORMALLY CLOSED  A, AMP AMPERE NO NORMALLY OPEN OR NUMBER	
AFF ABOVE FINISHED FLOOR MTD MOUNTED AFG ABOVE FINISHED GRADE NC NORMALLY CLOSED A, AMP AMPERE NO NORMALLY OPEN OR NUMBER	
AFG ABOVE FINISHED GRADE NC NORMALLY CLOSED A, AMP AMPERE NO NORMALLY OPEN OR NUMBER	
A, AMP AMPERE NO NORMALLY OPEN OR NUMBER	
ALITO ALITOMATIC	
AUTO AUTOMATIC NTS NOT TO SCALE	
AUX AUXILIARY OB OUTBOUND	
AWG AMERICAN WIRE GAUGE OC ON CENTER	
C CONDUIT ODU OUTDOOR UNIT	
CAT6 CATEGORY 6 CABLE OL OVERLOAD	
CCTV CLOSED CIRCUIT TELEVISION PA PUBLIC ADDRESS	
CKT CIRCUIT PCC PLATFORM COMMUNICATION CABIN	ΞT
COMM COMMUNICATION(S) PH PHASE	
CPT CONTROL POWER TRANSFORMER PLC PROGRAMMABLE LOGICAL CONTROL	LER
CR CONTROL RELAY PP POWER PANEL	
CS CONTROL SWITCH PR PAIR	
CT CURRENT TRANSFORMER PT POTENTIAL TRANSFORMER	
CU COPPER PTT PUSH-TO-TALK	
DN DOWN PTZ PAN-TILT-ZOOM CAMERA	
DSP DIGITAL SIGNAL PROCESSOR PVC POLYVINYL CHLORIDE	
ELEC ELECTRICAL QTY QUANTITY	
ELEV ELEVATION SCADA SUPERVISORY CONTROL AND DATA	
EM EMERGENCY ACQUISITION	
ETEL EMERGENCY TELEPHONE SCU STATION CONTROL UNIT	
FBO FURNISHED BY OTHERS SEC SECONDS OR SECONDARY	
FDP FIBER DISTRIBUTION PANEL SH SHIELDED OR SHEET	
FO FIBER OPTIC SMFO SINGLE MODE FIBER OPTIC	
FRP FIBERGLASS REINFORCED POLYESTER SN SOLID NEUTRAL	
FU FUSE SPKR SPEAKER	
FUT FUTURE SS STAINLESS STEEL	
G, GRD GROUND SVV STORED VALUE VALIDATOR	
GF GROUND FAULT INTERRUPTER SW SWITCH	
GRS GALVANIZED RIGID STEEL TC TIME DELAY ON CLOSING	
HH HANDHOLE TCC TRANSIT CONTROL CENTER	
HT HEIGHT TEL TELEPHONE	
HZ HERTZ TO TIME DELAY ON OPENING	
IB INBOUND TVM TICKET VENDING MACHINE	
INST INSTANTANEOUS TWP TWISTED PAIR	
INSTR INSTRUMENT TYP TYPICAL	
ITC INTERFACE TERMINAL CABINET UG UNDERGROUND	
KAIC KILO AMPERE INTERRUPTING CAPACITY UPS UNINTERRUPTABLE POWER SUPPLY	
KVA KILOVOLT AMPERE V VOLTS	
LA LIGHTNING ARRESTER VOIP VOICE OVER IP	
LP LIGHTING PANEL VMS VARIABLE MESSAGE SIGN	
MCC MAIN COMMUNCATION CABINET W WIRE	
MFR MANUFACTURER WP WEATHERPROOF	
MH MANHOLE XFMR TRANSFORMER	
MIC MICROPHONE	

SYMBOL	DESCRIPTION
	COMMUNICATION SYSTEMS
R—	SECURITY SYSTEM CARD ACCESS READER
CCTV	CLOSED CIRCUIT TV CAMERA
DS	SECURITY ALARM DOOR SWITCH
SA	SECURITY ALARM PANEL
\( \sum_{\text{E}} \)	EMERGENCY TELEPHONE HANDSET
DSH	PAGING SPEAKER, POLE MOUNTED, BI-DIRECTIONAL
S	PA SPEAKER, SURFACE MOUNTED CEILING TYPE
	MICROPHONE
Ġ.	ADA DOOR OPERATOR
НН	HANDHOLE
МН	MANHOLE

1. THE BLOCK DIAGRAMS, QUANTITY AND SIZE OF DEVICES REPRESENT A SUGGESTED ARRANGEMENT BASED UPON SELECTED STANDARD COMPONENTS OF COMMUNICATIONS EQUIPMENT. MODIFICATIONS ACCEPTABLE TO THE ENGINEER MAY BE MADE BY THE CONTRACTOR TO ACCOMMODATE EQUIPMENT ACTUALLY PURCHASED. THE BASIC SEQUENCE FUNCTION AND METHOD OF CONTROL MUST BE MAINTAINED AS INDICATED ON THE DRAWINGS AND/OR SPECIFICATIONS.



#### SYMBOL WHERE THERE IS A SECTION



SYMBOL WHERE SECTION IS DRAWN

SECTION SYMBOL



SYMBOL WHERE THERE IS A DETAIL

SUBTITLE DETAIL 1" = 1" E-2 SHEET NO. WHERE THERE IS A DETAIL SYMBOL WHERE DETAIL IS DRAWN

**DETAIL SYMBOL** 

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL

**AECOM** M-P Consultants

PRELIMINARY ENGINEERING






WEST - VOLUME 3 (SYSTEMS)
COMMUNICATIONS SYSTEM
GENERAL
SYMBOLS, LEGEND AND GENERAL NOTES


DISCIPLINE: SYSTEMS COM-SYM-000

186 OF

202

SHEET





- DRAWING IS MEANT AS A GUIDELINE FOR CONTRACTOR'S DESIGN, WHICH SHALL BE SUBMITTED THROUGH SHOP DRAWING REVIEW PROCESS; SYSTEM AND COMPONENTS SHOULD NOT BE CONSTRUCTED DIRECTLY FROM THIS DRAWING.
- 2. DRAWING NOT TO SCALE; EXACT QUANTITIES AND LOCATIONS OF DEVICES SHOWN ON STATION PLATFORM AND CANOPY PLAN
- 3. THIS DIAGRAM PROVIDES A GENERAL OVERVIEW OF THE CCTV SYSTEM WITH FIELD SITES SHOWN IN TYPICAL CONFIGURATION; REFERENCE INDIVIDUAL STATION DRAWINGS AND DETAIL SHEETS FOR MORE DETAILED INSTALLATION AND CONFIGURATION INFORMATION.
- 4. NOT ALL LOCATIONS WHERE CCTV CAMERAS WILL BE INSTALLED ARE

KEYNOTES:

- ALL ITEMS AT RCC AND EBC ARE EXISTING. CONTRACTOR SHALL EXPAND HEAD END SYSTEMS TO THE EXTENT NECESSARY TO PROVISION ALL NEW SWLRT CAMERAS ON CCTV HEADEND SYSTEM, AND FURNISH ADDITIONAL NVR STORAGE TO ACCOMMODATE ALL NEW
- 2. PARKING RAMPS AND LOTS MAY REQUIRE A SEPARATE CABINET AND NETWORK SWITCH TO ACCOMMODATE MINIMUM CABLE LENGTHS; THESE CABINETS ARE NOT SHOWN ON THIS DRAWING.

**AECOM** M-P Consultants PRELIMINARY ENGINEERING





**WEST - VOLUME 3 (SYSTEMS) COMMUNICATIONS SYSTEM SYSTEMWIDE BLOCK DIAGRAMS CCTV SYSTEM OVERVIEW** 

OF


188

SHEET

DISCIPLINE:

COM-SWB-002

**SYSTEMS** 



- DRAWING IS MEANT AS A GUIDELINE FOR CONTRACTOR'S DESIGN, WHICH SHALL BE SUBMITTED THROUGH SHOP DRAWING REVIEW PROCESS; SYSTEM AND COMPONENTS SHALL NOT BE CONSTRUCTED DIRECTLY
- 2. DRAWING NOT TO SCALE; EXACT QUANTITIES AND LOCATIONS OF DEVICES SHOWN ON STATION PLATFORM AND CANOPY PLAN DRAWINGS
- 3. THIS DIAGRAM PROVIDES A GENERAL OVERVIEW OF THE ACCESS CONTROL SYSTEM WITH FIELD SITES SHOWN IN TYPICAL CONFIGURATION; REFERENCE INDIVIDUAL STATION DRAWINGS AND DETAIL SHEETS FOR MORE DETAILED INSTALLATION AND CONFIGURATION INFORMATION.

#### KEYNOTES:

ALL ITEMS AT RCC AND EBC ARE EXISTING. CONTRACTOR SHALL PROVIDE PROGRAMMING FOR ALL NEW ACCESS CONTROLLERS AND ACCESS CARD READERS, AND WORK WITH MET COUNCIL TO THE EXTENT NECESSARY TO PROVISION ALL NEW SWLRT STATION ACCESS CARD READERS ON EXISTING GE FACILITY COMMANDER SYSTEM.

ACCESS CONTROL SYSTEM OVERVIEW

ю.	DAIL	01	CHECK	DESIGN	REVISION / SUBMITTAL

**AECOM** M-P Consultants

PRELIMINARY ENGINEERING





**WEST - VOLUME 3 (SYSTEMS) COMMUNICATIONS SYSTEM SYSTEMWIDE BLOCK DIAGRAMS** ACCESS CONTROL SYSTEM OVERVIEW

**SYSTEMS** 


COM-SWB-003

202

SHEET

189

OF



- DRAWING IS MEANT AS A GUIDELINE FOR CONTRACTOR'S DESIGN, WHICH SHALL BE SUBMITTED THROUGH SHOP DRAWING REVIEW PROCESS; SYSTEM AND COMPONENTS SHALL NOT BE
- DRAWING NOT TO SCALE; EXACT QUANTITIES AND LOCATIONS OF DEVICES SHOWN ON STATION PLATFORM AND CANOPY PLAN
- 3. THIS DIAGRAM PROVIDES A GENERAL OVERVIEW OF THE FARE COLLECTION SYSTEM WITH FIELD SITES SHOWN IN TYPICAL CONFIGURATION; REFERENCE INDIVIDUAL STATION DRAWINGS AND DETAIL SHEETS FOR MORE DETAILED INSTALLATION AND CONFIGURATION INFORMATION.
- SCADA POINTS SHOWN ON THIS DRAWING ARE AN ARBITRARY SAMPLE OF POINTS; SEE SPECIFCATION DOCUMENTS FOR ACTUAL REQUIRED LIST OF SCADA POINTS.

#### KEYNOTES:

- ALL ITEMS AT RCC AND EBC ARE EXISTING. CONTRACTOR SHALL EXPAND HEAD END SYSTEMS AND PROVIDE SCADA PROGRAMMING TO THE EXTENT NECESSARY TO PROVISION ALL NEW SWLRT SCADA POINTS, ALARMS AND CONTROLS ON SCS CENTRAL CONTROL SYSTEM.
- 2. TYPICAL SIGNAL-COMMUNICATION HOUSE CONTAINS 15-20 DISCREET AND 3 ANALOG I/O SCADA POINTS.
- 3. TYPICAL STATION COMMUNICATION CABINET CONTAINS 25-30 DISCREET AND 1-2 ANALOG I/O SCADA POINTS.
- 4. TYPICAL SIGNAL HOUSE CONTAINS 10-15 DISCREET AND 1-2 ANALOG SCADA POINTS.
- TYPICAL TPSS CONTAINS 140 DISCREET SCADA I/O POINTS, (10 OF WHICH ARE CONTROLS, THE REST ARE INDICATIONS) AND 10 ANALOG SCADA INDICATIONS.

SCADA SYSTEM OVERVIEW SCALE: NTS

NO. DATE BY CHECK DESIGN REVISION / SUBMITTA

**AECOM** M-P Consultants PRELIMINARY ENGINEERING





**WEST - VOLUME 3 (SYSTEMS) COMMUNICATIONS SYSTEM SYSTEMWIDE BLOCK DIAGRAMS** SCADA SYSTEM OVERVIEW


190 OF

SHEET

DISCIPLINE:

202

**SYSTEMS** COM-SWB-004



- 1. DRAWING IS MEANT AS A GUIDELINE FOR CONTRACTOR'S DESIGN. WHICH SHALL BE SUBMITTED THROUGH SHOP DRAWING REVIEW PROCESS; SYSTEM AND COMPONENTS SHALL NOT BE CONSTRUCTED DIRECTLY FROM THIS DRAWING.
- 2. DRAWING NOT TO SCALE; EXACT QUANTITIES AND LOCATIONS OF DEVICES SHOWN ON STATION PLATFORM AND CANOPY PLAN
- 3. THIS DIAGRAM PROVIDES A GENERAL OVERVIEW OF THE PA/VMS SYSTEM WITH FIELD SITES SHOWN IN TYPICAL CONFIGURATION; REFERENCE INDIVIDUAL STATION DRAWINGS AND DETAIL SHEETS FOR MORE DETAILED INSTALLATION AND CONFIGURATION

#### KEYNOTES:

- 1. ALL ITEMS AT RCC AND EBC ARE EXISTING. CONTRACTOR SHALL EXPAND HEAD END SYSTEMS AND PROVIDE PROGRAMMING TO THE EXTENT NECESSARY TO PROVISION ALL NEW SWLRT STATION PA/VMS SYSTEMS ON PA/VMS HEADEND SYSTEM.
- 2. STATION CONTROL PANEL SHALL BE PROVIDED WITH LOCKABLE DOOR SET INTO COMMUNICATION CABINET ON PLATFORMS; KEYING SHALL MATCH EXISTING METRO TRANSIT LRT SCP LOCKS.

PA/VMS SYSTEM OVERVIEW

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL

**AECOM** M-P Consultants PRELIMINARY ENGINEERING






**WEST - VOLUME 3 (SYSTEMS) COMMUNICATIONS SYSTEM SYSTEMWIDE BLOCK DIAGRAMS PA/VMS SYSTEM OVERVIEW** 

191 OF

SHEET

DISCIPLINE: **SYSTEMS** 

COM-SWB-005



- 1. DRAWING IS MEANT AS A GUIDELINE FOR CONTRACTOR'S DESIGN. WHICH SHALL BE SUBMITTED THROUGH SHOP DRAWING REVIEW PROCESS; SYSTEM AND COMPONENTS SHALL NOT BE CONSTRUCTED DIRECTLY FROM THIS DRAWING.
- 2. DRAWING NOT TO SCALE; EXACT QUANTITIES AND LOCATIONS OF DEVICES SHOWN ON STATION PLATFORM AND CANOPY PLAN
- 3. THIS DIAGRAM PROVIDES A GENERAL OVERVIEW OF THE TELEPHONE SYSTEM WITH FIELD SITES SHOWN IN TYPICAL CONFIGURATION; REFERENCE INDIVIDUAL STATION DRAWINGS AND DETAIL SHEETS FOR MORE DETAILED INSTALLATION AND CONFIGURATION INFORMATION.

#### KEYNOTES:

1. ALL ITEMS AT RCC AND EBC ARE EXISTING. CONTRACTOR SHALL PROVIDE LICENSES FOR ALL NEW PHONES, AND WORK WITH MET COUNCIL TO THE EXTENT NECESSARY TO PROVISION ALL NEW SWLRT STATION TELEPHONES ON EXISTING MITEL PHONE SYSTEM.

TELEPHONE SYSTEM OVERVIEW

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL

**AECOM** M-P Consultants PRELIMINARY ENGINEERING






**WEST - VOLUME 3 (SYSTEMS) COMMUNICATIONS SYSTEM SYSTEMWIDE BLOCK DIAGRAMS TELEPHONE SYSTEM OVERVIEW** 

192 OF

SHEET

DISCIPLINE: **SYSTEMS** 

COM-SWB-006



FARE COLLECTION SYSTEM OVERVIEW

SCALE: NTS

NO. DATE BY CHECK DESIGN REVISION / SUBMITTAL

**AECOM** M-P Consultants PRELIMINARY ENGINEERING





### **WEST - VOLUME 3 (SYSTEMS) COMMUNICATIONS SYSTEM SYSTEMWIDE BLOCK DIAGRAMS FARE COLLECTIONS SYSTEM OVERVIEW**

OF

**SYSTEMS** 

GENERAL NOTES:

KEYNOTES:

1. DRAWING IS MEANT AS A GUIDELINE FOR CONTRACTOR'S DESIGN, WHICH SHALL BE SUBMITTED THROUGH SHOP

DRAWING REVIEW PROCESS; SYSTEM AND COMPONENTS SHALL NOT BE CONSTRUCTED DIRECTLY FROM THIS DRAWING.

OF DEVICES SHOWN ON STATION PLATFORM AND CANOPY PLAN

CONFIGURATION; REFERENCE INDIVIDUAL STATION DRAWINGS

AND DETAIL SHEETS FOR MORE DETAILED INSTALLATION AND

2. DRAWING NOT TO SCALE; EXACT QUANTITIES AND LOCATIONS

3. THIS DIAGRAM PROVIDES A GENERAL OVERVIEW OF THE FARE COLLECTION SYSTEM WITH FIELD SITES SHOWN IN TYPICAL

1. ALL ITEMS AT RCC AND EBC ARE EXISTING. CONTRACTOR SHALL EXPAND HEAD END SYSTEMS AND PROVIDE SCADA PROGRAMMING TO THE EXTENT NECESSARY TO PROVISION ALL NEW SWLRT FARE COLLECTION POINTS ON SCADA HEADEND


CONFIGURATION INFORMATION.


COM-SWB-007


193


202

SHEET










- 1. 144-SMFO BACKBONE CABLE SHALL BE ROUTED DIVERSELY IN ALL INSTANCES; ROUTE 'A' AND 'B' CABLES IN SEPARATE DUCTS OF S/C DUCTBANK, AND PROVIDE ENTRANCES/EXITS OF 'A' AND 'B' CABLES INTO HOUSES AND ENCLOSURES VIA SEPARATE CONDUITS.
- 2. ALL BACKBONE NETWORK LINKS SHALL BE
- 3. ALL SPUR NETWORK LINKS OVER 12-SMFO
- 4. UNLESS OTHERWISE NOTED, COPPER NETWORK LINKS FROM SITE ACCESS SWITCHES TO NETWORK DEVICES SHALL BE 1000/100/10



TPSS SW19

1-Gb/s BASE-LX

MITCHELL RD XING SIGNAL HOUSE

1-Gb/s BASE-LX

PARKING RAMP

COMM CABINET

1-Gb/s BASE-LX

## **AECOM**

M-P Consultants

PRELIMINARY ENGINEERING





### **WEST - VOLUME 3 (SYSTEMS) COMMUNICATIONS SYSTEM NETWORK AND CABLE PLANS** SHEET 1 OF 4


OF 202

SHEET

198

DISCIPLINE: **SYSTEMS** COM-NCP-001

- 1. 144-SMFO BACKBONE CABLE SHALL BE ROUTED DIVERSELY IN ALL INSTANCES; ROUTE 'A' AND 'B' CABLES IN SEPARATE DUCTS OF S/C DUCTBANK, AND PROVIDE ENTRANCES/EXITS OF 'A' AND 'B' CABLES INTO HOUSES AND ENCLOSURES VIA SEPARATE CONDUITS.
- 2. ALL BACKBONE NETWORK LINKS SHALL BE
- 3. ALL SPUR NETWORK LINKS OVER 12-SMFO CABLE SHALL BE 1-Gb/s.
- 4. UNLESS OTHERWISE NOTED, COPPER NETWORK LINKS FROM SITE ACCESS SWITCHES TO NETWORK DEVICES SHALL BE 1000/100/10



NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL

TECHNOLOGY DR XING SIGNAL HOUSE

VIKING DR

XING SIGNAL HOUSE

PRAIRIE CENTER DR

SIGNAL HOUSE

TPSS

SW16

## **AECOM**

M-P Consultants

PRELIMINARY ENGINEERING





### **WEST - VOLUME 3 (SYSTEMS) COMMUNICATIONS SYSTEM NETWORK AND CABLE PLANS** SHEET 2 OF 4


OF 202

SHEET

199

DISCIPLINE: **SYSTEMS** COM-NCP-002

- 1. 144-SMFO BACKBONE CABLE SHALL BE ROUTED DIVERSELY IN ALL INSTANCES; ROUTE 'A' AND 'B' CABLES IN SEPARATE DUCTS OF S/C DUCTBANK, AND PROVIDE ENTRANCES/EXITS OF 'A' AND 'B' CABLES INTO HOUSES AND ENCLOSURES VIA SEPARATE CONDUITS.
- 2. ALL BACKBONE NETWORK LINKS SHALL BE
- 3. ALL SPUR NETWORK LINKS OVER 12-SMFO CABLE SHALL BE 1-Gb/s.
- 4. UNLESS OTHERWISE NOTED, COPPER NETWORK LINKS FROM SITE ACCESS SWITCHES TO NETWORK DEVICES SHALL BE 1000/100/10 BASE-T LINKS.



PARK AND RIDE COMM CABINET

TPSS SW15

NO.	DATE	BY	CHECK	DESIGN	REVISION / SUBMITTAL

## **AECOM**

M-P Consultants





## **WEST - VOLUME 3 (SYSTEMS) COMMUNICATIONS SYSTEM NETWORK AND CABLE PLANS**

SHEET 3 OF 4

**SYSTEMS** 

202 COM-NCP-003


SHEET

200

OF

PRELIMINARY ENGINEERING

- 1. 144-SMFO BACKBONE CABLE SHALL BE ROUTED DIVERSELY IN ALL INSTANCES; ROUTE 'A' AND 'B' CABLES IN SEPARATE DUCTS OF S/C DUCTBANK, AND PROVIDE ENTRANCES/EXITS OF 'A' AND 'B' CABLES INTO HOUSES AND ENCLOSURES VIA SEPARATE CONDUITS.
- 2. ALL BACKBONE NETWORK LINKS SHALL BE
- 3. ALL SPUR NETWORK LINKS OVER 12-SMFO CABLE SHALL BE 1-Gb/s.
- 4. UNLESS OTHERWISE NOTED, COPPER NETWORK LINKS FROM SITE ACCESS SWITCHES TO NETWORK DEVICES SHALL BE 1000/100/10 BASE-T LINKS.



NO. DATE BY CHECK DESIGN REVISION / SUBMITTAL

**AECOM** 

M-P Consultants

PRELIMINARY ENGINEERING






**WEST - VOLUME 3 (SYSTEMS) COMMUNICATIONS SYSTEM NETWORK AND CABLE PLAN** 4 OF 4

DISCIPLINE: **SYSTEMS**  COM-NCP-004

OF

202

SHEET



- 1. DRAWING IS MEANT AS A GUIDELINE FOR CONTRACTOR'S DESIGN, WHICH SHALL BE SUBMITTED THROUGH SHOP DRAWING REVIEW PROCESS; SYSTEM AND COMPONENTS SHALL NOT BE CONSTRUCTED DIRECTLY FROM THIS DRAWING.
- DRAWING NOT TO SCALE; EXACT QUANTITIES AND LOCATIONS OF DEVICES SHOWN ON STATION PLATFORM AND CANOPY PLAN DRAWINGS.
- 3. THIS DIAGRAM PROVIDES A GENERAL OVERVIEW OF THE TUNNEL COMMUNICATION SYSTEMS WITH FIELD SITES SHOWN IN TYPICAL CONFIGURATION.

#### KEYNOTES:

- A HORN AND STROBE SHALL BE INSTALLED AT TUNNEL PORTALS FOR INTRUSION DETECTION. STROBE SHALL BE MOUNTED IN LOCATION VISIBLE TO TRAIN OPERATOR; HORN SHALL BE MOUNTED IN LOCATION AUDIBLE TO INTRUDERS.
- 2. UPS/BATTERY BACKUP SHALL BE PROVIDED FOR EACH LOCATION NOTED; BATTERY RUNTIME SHALL BE 8 HOURS
- 3. TYPICAL TUNNEL MCC HOUSE WILL CONTAIN 50-75 DISCREET (10-15 CONTROLS, THE REST INDICATIONS) AND 5-10 ANALOG SCADA I/O POINTS.
- 4. SCADA SYSTEM SHALL INTERFACE WITH FIRE MANAGEMENT INFORMATION SYSTEM.

NO. DATE BY CHECK DESIGN REVISION / SUBMITTAL **AECOM** M-P Consultants

PRELIMINARY ENGINEERING





**WEST - VOLUME 3 (SYSTEMS) COMMUNICATIONS SYSTEM TUNNEL SYSTEM TUNNEL COMMUNICATIONS OVERVIEW** 

**SYSTEMS** 

202 OF

202

SHEET

COM-TUN-001